

OS LAB MANUAL (CS23431)

Roll No:230701258

EX.NO:12

File Organization Technique- Single and Two level directory

Aim: To implement File Organization Structures in C are:

- a. Single Level Directory
 - b. Two-Level Directory
-

A) Single Level Directory

Program:

```
#include <stdio.h>
#include <string.h>
int main() {
    int n, i;
    char files[10][30];
    printf("Enter the number of files: ");
    scanf("%d", &n);
    printf("\nCreating Single-Level Directory Structure...\n");
    for (i = 0; i < n; i++) {
        printf("\nEnter the name of file %d: ", i + 1);
        scanf("%s", files[i]);
        printf("\n+-----+\n");
        printf("| Root Directory |\n");
        printf("+ -----+\n");
    }
}
```

```

        for (int j = 0; j <= i; j++) {
            printf("        |\n");
            printf("        +--> [ %s ]\n", files[j]);
        }
    }
    return 0;
}

```

Input:

```

Enter the number of files: 2

Creating Single-Level Directory Structure...

Enter the name of file 1: A

```

Output:

```

Enter the number of files: 2

Creating Single-Level Directory Structure...

Enter the name of file 1: A

+-----+
| Root Directory |
+-----+
      |
      +--> [ A ]

Enter the name of file 2: D

+-----+
| Root Directory |
+-----+
      |
      +--> [ A ]
      |
      +--> [ D ]

```

B) Two-Level Directory :

Program:

```
#include <stdio.h>

#include <string.h>

struct File {
    char name[30];
};

struct User {
    char name[30];
    int fileCount;
    struct File files[10];
};

int main() {
    int userCount, i, j;
    struct User users[10];
    printf("Enter the number of users (directories): ");
    scanf("%d", &userCount);
    for (i = 0; i < userCount; i++) {
        printf("\nEnter the name of User %d: ", i + 1);
        scanf("%s", users[i].name);
        printf("Enter number of files for %s: ", users[i].name);
        scanf("%d", &users[i].fileCount);
        for (j = 0; j < users[i].fileCount; j++) {
            printf("Enter file %d name for %s: ", j + 1, users[i].name);
            scanf("%s", users[i].files[j].name);
        }
    }
    printf("\n\nTwo-Level Directory Structure:\n");
    printf("+-----+\n");
    printf("|    Root Directory    |\n");
    printf("+-----+\n");
```

```

for (i = 0; i < userCount; i++) {
    printf("    |\n");
    printf("    +--> User: %s\n", users[i].name);
    for (j = 0; j < users[i].fileCount; j++) {
        printf("        |\n");
        printf("        +--> File: %s\n", users[i].files[j].name);
    }
}
return 0;
}

```

Input:

```

Enter the number of users (directories): 2

Enter the name of User 1: joe
Enter number of files for joe: 2
Enter file 1 name for joe: A
Enter file 2 name for joe: B

Enter the name of User 2: ram
Enter number of files for ram: 2
Enter file 1 name for ram: A
Enter file 2 name for ram: B

```

Output:

```

Two-Level Directory Structure:
+-----+
|   Root Directory   |
+-----+
|
|   +--> User: joe
|       |
|       +--> File: A
|       |
|       +--> File: B
|
|   +--> User: ram
|       |
|       +--> File: A
|       |
|       +--> File: B

```