OS LAB MANUAL (CS23431)

Roll No:230701258

EX.NO:11(B)

LRU

Aim: To write a c program to implement LRU page replacement algorithm.

```
Program:
```

```
#include <stdio.h>
int findLRU(int time[], int n) {
  int i, minimum = time[0], pos = 0;
  for (i = 1; i < n; ++i) {
    if (time[i] < minimum) {</pre>
       minimum = time[i];
      pos = i;
    }
  }
  return pos;
}
int main() {
  int no_of_frames, no_of_pages, frames[10], pages[30];
  int counter = 0, time[10], flag1, flag2, i, j, pos, faults = 0;
  printf("Enter number of frames: ");
  scanf("%d", &no_of_frames);
  printf("Enter number of pages: ");
  scanf("%d", &no_of_pages);
  printf("Enter reference string: ");
  for (i = 0; i < no_of_pages; ++i) {
    scanf("%d", &pages[i]);
  }
```

```
for (i = 0; i < no_of_frames; ++i) {
  frames[i] = -1;
}
for (i = 0; i < no_of_pages; ++i) {
  flag1 = flag2 = 0;
  for (j = 0; j < no_of_frames; ++j) {
    if (frames[j] == pages[i]) {
       counter++;
       time[j] = counter;
       flag1 = flag2 = 1;
       break;
    }
  }
  if (flag1 == 0) {
    for (j = 0; j < no_of_frames; ++j) {
       if (frames[j] == -1) {
         counter++;
         faults++;
         frames[j] = pages[i];
         time[j] = counter;
         flag2 = 1;
         break;
       }
    }
  }
  if (flag2 == 0) {
    pos = findLRU(time, no_of_frames);
    counter++;
    faults++;
    frames[pos] = pages[i];
    time[pos] = counter;
```

```
}
for (j = 0; j < no_of_frames; ++j) {
    if (frames[j] != -1)
        printf("%d ", frames[j]);
    else
        printf("-1 ");
    }
    printf("\n");
}
printf("Total Page Faults = %d\n", faults);
return 0;
}
</pre>
```

Input:

```
Enter number of frames: 3
Enter number of pages: 12
Enter reference string: 1 2 3 4 5 6 7 8 9 2 3 4
```

Output:

```
1 -1 -1

1 2 -1

1 2 3

4 2 3

4 5 3

4 5 6

7 5 6

7 8 6

7 8 9

2 8 9

2 3 9

2 3 4

Total Page Faults = 12
```