Field-Level Financial Document Extraction with YOLO26 and Apache Spark: A Reproducible Pipeline, Its Failure Modes, and a Controlled Evaluation

Anonymous Authors
Under double-blind review

Abstract. ***Putting a vision model inside a Spark job looks routine and fails quietly. We build a field-level document extraction pipeline in which YOLO26 localizes fields and Tesseract reads each crop, executed with `mapInPandas` so the model loads once per partition. We catalog the integration defects that made a first version wrong, each checked against a running system, including a Spark image source that returns decoded pixels instead of file bytes and an Arrow failure on Spark 3.5 with JDK 21. On a synthetic form dataset with exact ground truth, a CPU-fine-tuned YOLO26n reaches 98.7% detection precision and 99.3% recall, and 97.1% of text fields are read correctly end to end. Without class-wise suppression the end-to-end head emitted 90 duplicate boxes and precision fell to 75.9%. Full-page Tesseract captured 99.6% of the strings but does not say which field they belong to, so we do not claim an accuracy advantage. Loading the model per partition was 1.7 times faster than per row on two CPU cores. Data are synthetic and no GPU, EMR, or Textract measurements are reported. All numbers are generated from files in the released repository.***

Index Terms. ***Financial document intelligence, YOLO26, Apache Spark, document field extraction, OCR, reproducibility.***

I. Introduction

Financial institutions ingest checks, identification forms, and statements as images, and downstream systems need to know which string is the account number, which is the date, and which is the amount. Page-level OCR returns text but not that mapping, and its accuracy is not a fixed number: independent studies report Tesseract anywhere from about 47 percent to over 92 percent depending on document type, resolution, and preprocessing [2], [3]. A detect-then-read design addresses both problems. An object detector localizes each field, and OCR runs only on the cropped region, so every extracted string arrives already labeled with its field class.

Ultralytics YOLO26 [8] is a natural detector for this role. Its end-to-end head does not need non-maximum suppression at inference, which removes a post-processing pass from the serving path. Running it over millions of documents calls for a distributed engine, and Apache Spark [14] is the usual choice.

The difficulty is that a model call inside a Spark job looks routine and fails quietly. The RAPIDS Accelerator for Apache Spark [15], [16] accelerates Spark's own SQL and DataFrame plan on GPU. It does not accelerate Python code that loads a model inside a user-defined function, so enabling it does not make model inference fast. The first version of this pipeline contained several such defects, some in the model call pattern, some in data access, and some in the toolchain. We found them only after running the code, which is the reason this paper reports a running system and not a design alone.

This paper builds the pipeline, runs it, measures it, and releases it. Its scope is deliberately narrow. All reported accuracy is on a synthetic form dataset whose labels are exact by construction, all timing is on a two-core CPU, and the AWS EMR and GPU deployment is presented as design, not as measurement.

II. Contributions

- A complete open implementation of field detection, field-level OCR, and aggregation as one Spark job, with unit and end-to-end tests and a single command that reproduces every number in this paper.
- A catalog of integration defects, each checked against a running system, and the corrected partition-level inference pattern that resolves them (Section V).
- A controlled evaluation on a dataset with exact ground truth: detection precision and recall, end-to-end field accuracy against a full-page Tesseract baseline, and a measured comparison of three ways to run the same model inside Spark (Section VII).
- A deployment design for AWS EMR with RAPIDS, kept separate from what was measured, including when the batch design is and is not appropriate (Section IV).

III. Related Work

Detection. Single-network detection was introduced by Redmon et al. [5]. YOLOv9 added programmable gradient information [6], and YOLOv10 was the first in the line to remove non-maximum suppression [7]. YOLO26 keeps native

end-to-end inference, removes Distribution Focal Loss, and is the current Ultralytics release [8]. DocLayout-YOLO adapts the family to document layout analysis [9]. We use YOLO26 because it is the maintained production model and its NMS-free head simplifies the serving path. We do not claim it is the best detector for financial fields, and we do not compare against other detectors.

OCR and document understanding. Tesseract [1] remains a common open-source engine, and its accuracy varies widely with document type and preprocessing [2], [3]. Managed services such as Amazon Textract [4] are an obvious comparison, which we do not make because it needs an AWS account and real documents. Layout-aware transformers such as LayoutLMv3 [10] and OCR-free models such as Donut [11] are stronger, heavier alternatives that solve a broader problem. Our baseline is Tesseract alone, which makes the comparison one of pipeline structure, not one against the state of the art.

Datasets. FUNSD [12] and SROIE [13] are the public datasets closest to this domain, and neither fits. FUNSD annotates form entities as question, answer, header, and other. SROIE provides text-line boxes and key-information strings for receipts. Neither provides region boxes for classes such as account number, date, amount, name, and signature. For that reason we evaluate on a synthetic dataset whose boxes and strings are exact, and we say plainly what that does and does not show.

Systems. Spark's resilient distributed datasets [14] underlie its DataFrame engine. Spark exchanges data with Python through Apache Arrow, and `mapInPandas` [17] exposes that path at partition granularity. Spark can schedule GPUs as task resources [18], and the RAPIDS documentation describes how GPU-scheduled Python workers share a device with the executor [15].

IV. System Design

Fig. 1 shows the full ingestion-to-analytics design. Solid boxes inside the Spark job are implemented and measured in this paper. Dashed boxes are the AWS deployment around it, which we describe but did not run.

A. Spark job

The job reads images with Spark's `binaryFile` source, which returns the encoded file bytes unchanged. A `mapInPandas` function then runs once per partition. It loads the model once, decodes each Arrow batch of images, makes one batched detector call, crops every detected field from the original image, and runs Tesseract in single-line mode on each crop. Signature regions are detected but not read. Output is long format, one row per detected field, written as Parquet. A final step computes per-class mean confidence with a two-phase aggregation: each partition emits a partial sum and count, and Spark performs the final reduce. That step uses cuDF when RAPIDS is installed and pandas otherwise.

B. Target deployment on AWS

An upload to S3 raises an event, AWS Step Functions [20] launches or resizes an Amazon EMR [19] cluster, the Spark job runs, and structured output reaches Redshift through Glue. On a GPU cluster the detector would run on the device that Spark assigns to each task, using Spark's custom resource scheduling [18], with one GPU per task slot. The pipeline module reads that device index from the task context and sets the corresponding Spark configuration when started with `-gpu`. We could not exercise this path, because no GPU was available, so it is untested.

C. Where this design applies

The design targets batch and micro-batch workloads, such as an overnight queue of scanned documents or a stream drained every few minutes. It does not target sub-second per-request latency. A cold EMR cluster adds a start-up cost that we did not measure and that no steady-state throughput figure includes. Interactive use would call for a warm cluster, EMR Serverless, or a plain model server in front of the same detector and OCR code.

V. Implementation and Verified Defects

Table I lists the defects found in the first version of this pipeline. Each row records what was observed when the code was run, not what documentation predicts, except where marked as untested.

Listing 1 shows the core of the corrected pattern. The complete module, tests, and a one-command reproduction are in the released repository.[1]

```
def detect_partition(batches):
  device = _task_device()   # GPU from Spark, else CPU
  model = YOLO(SparkFiles.get(name))  # once
  for batch in batches:     # one Arrow batch
    imgs = [cv2.imdecode(
              np.frombuffer(bytes(raw), np.uint8),
              cv2.IMREAD_COLOR)
            for raw in batch["content"]]
    results = model(imgs, device=device)  # 1 call
    for path, im, res in zip(batch["path"],
                             imgs, results):
      for b in res.boxes:   # original pixels
        x1, y1, x2, y2 = map(int,
                             b.xyxy[0].tolist())
        text = pytesseract.image_to_string(
            gray(im[y1:y2, x1:x2]),
            config="--psm 7").strip()
        rows.append((path, cls(b), ..., text))
    yield pd.DataFrame(rows, columns=COLS)
```

Listing 1. Partition-level detection and OCR (abridged from `findoc/pipeline.py`).

VI. Experimental Setup

Data. A deterministic generator renders account forms at 960 by 640 pixels with five field classes: account number, date, amount, name, and signature. Layout, font, field order, noise, and blur vary per document. Every box and every text string is known exactly. The split is 240 training, 60 validation, and 60 test documents, with disjoint random seeds. The test split holds 300 fields, of which 240 carry text.

Model. YOLO26n fine-tuned from the COCO checkpoint for 15 epochs at 640 pixels, batch size 8, AdamW, on CPU, in about 32 minutes. We use the nano model because it is the

[1] ANONYMOUS-REPO-URL




Fig. 1. Target architecture. The Spark job (solid) is implemented and measured here on a two-core CPU. Dashed components, including EMR with GPU nodes, Step Functions, Glue, and Redshift, are design only and were not exercised.

TABLE I
INTEGRATION DEFECTS FOUND BY RUNNING THE PIPELINE, AND THE FIX APPLIED IN THE RELEASED CODE.

Defect	Observed behavior	Fix
Spark `image` source fed to an image decoder	Returns decoded pixels, not file bytes. A 640 by 960 image gave 1,843,200 bytes against a 132,098 byte JPEG, and `imdecode` returned `None`.	Read with `binaryFile`, which returned bytes identical to the file.
Re-opening a path with `cv2.imread`	An `s3://` URI returns `None`. The path cannot be opened by OpenCV.	Decode the bytes Spark already read; never re-open the path.
`mapInPandas` on Spark 3.5.3 with JDK 21	Fails in the JVM with `sun.misc.Unsafe or DirectByteBuffer.<init>(long, int) not available`, including with `-add-opens` and the Netty reflection flag.	Spark 4.0.1 on JDK 21 ran correctly. Spark 3.5 on JDK 17 is the documented alternative and was not tested.
Model constructed inside a row-wise UDF	The model loads once per row. Cost measured in Section VII.	Load once per partition inside `mapInPandas`.
Per-image Python loop around the model call	Inference is one image at a time.	One batched call per Arrow batch, with a dynamic-batch ONNX export.
Manual resize to 640 by 640	Distorts non-square pages, and every box then needs mapping back to page coordinates.	Pass the original image. Ultralytics letterboxes internally and returns boxes in original pixels.
Hard-coded `device=0` with two concurrent GPU tasks	Two model copies can land on one device. *Untested, no GPU available.*	Read the device from the task context and schedule one GPU per task.
cuDF used to count a substring in one JSON string	Too small an operation to benefit from a GPU, and the key it searched for did not match the output schema.	Per-partition partial sums and counts by class, reduced by Spark.

one that trains on this hardware. The paper's design uses the largest model on GPUs, and those results would differ.

Hardware and software. Two virtual CPU cores, 7 GB of memory, no GPU. Python 3.13, Spark 4.0.1, OpenJDK 21, Ultralytics 8.4, ONNX Runtime 1.29, Tesseract 5.3.4.

Metrics. A detection is correct if its class matches and its IoU with an unmatched ground-truth box is at least 0.5. We report precision and recall. End-to-end field accuracy is the share of text fields that are both localized and read with an exact string match after whitespace is removed. The baseline is Tesseract run on the full page. We count a field as captured if its exact string appears anywhere in the page text. That rule is lenient, because the baseline is never required to say which field a string belongs to, so it is an upper bound on what page-level OCR delivers and is not a like-for-like extractor.

Inference-pattern timing. The same fine-tuned model scores 48 test documents on two partitions in three configurations: a row-wise UDF that builds the model on every call, and `mapInPandas` with Arrow batch sizes 1 and 16. Detection only, no OCR, so the comparison isolates the pattern. Each configuration has one discarded warm-up run and 3 timed runs.

Limits of the design. There is one training seed, and the test split is 60 documents, so intervals are wide and we report Wilson 95 percent intervals where they matter. The dataset is synthetic, clean, and easy by comparison with scanned documents, so absolute accuracy here says little about real documents.

VII. RESULTS

All numbers in this section are generated from the result files in the repository. The confidence threshold for each variant was chosen on the validation split by detection F1, and each variant was then scored once on the test split.

A. Detection and end-to-end accuracy

Table II compares three operating points of the same fine-tuned model, which reaches a validation mAP50 of 0.995 and mAP50-95 of 0.934. Those headline scores say little about deployment behavior. At the default confidence of 0.25, the exported end-to-end head produced 374 boxes for 300 true

TABLE II
TEST-SPLIT RESULTS, 60 DOCUMENTS AND 300 FIELDS (240 WITH TEXT). P AND R ARE DETECTION PRECISION AND RECALL AT IOU 0.5. OCR IS EXACT MATCH AMONG LOCALIZED TEXT FIELDS. END-TO-END (E2E) IS THE SHARE OF TEXT FIELDS BOTH LOCALIZED AND READ EXACTLY, WITH ITS WILSON 95% INTERVAL.

Variant (conf)	P	R	OCR	E2E	95% interval
NMS-free (0.25, default)	75.9	94.7	98.7	92.1	88.0 to 94.9
NMS-free (0.45, tuned)	88.8	87.0	100.0	84.6	79.5 to 88.6
Class NMS (0.15, tuned)	98.7	99.3	97.9	97.1	94.1 to 98.6




Fig. 2. Precision, recall, and end-to-end accuracy for the three operating points in Table II. All values are percentages on one axis.




Fig. 3. Per-class detection precision, recall, and OCR exact match for the class-NMS variant on the test split. The vertical axis starts at 60 percent. Signatures are detected but not read.

TABLE III
INFERENCE PATTERN TIMING, MEAN AND STANDARD DEVIATION OF 3 RUNS AFTER ONE WARM-UP. CPU ONLY, TWO CORES.

Pattern	Seconds	Docs/s	Speedup
Row-wise UDF, model per row	9.4 ± 0.4	5.1	1.0
`mapInPandas`, batch 1	5.7 ± 0.1	8.5	1.7
`mapInPandas`, batch 16	5.6 ± 0.1	8.6	1.7

fields, and precision was only 75.9%. Of those, 90 were duplicates of a field that already had a box, with a mean confidence of 0.59 against 0.72 for the top box of each field, and 16 fields had no box above the threshold. The NMS-free head is therefore not duplicate-free after a short nano fine-tune.

Three observations follow. First, adding class-wise suppression before OCR lifts precision from 75.9% to 98.7% and end-to-end accuracy to 97.1%, and it also removes duplicate crops from the OCR stage. Second, tuning an NMS-free detector for validation F1 chose a high threshold (0.45) that traded away recall, and end-to-end accuracy fell to 84.6%, below the untuned default. F1 is not the end-to-end objective, and a threshold chosen for one can hurt the other. Third, the OCR stage is rarely the bottleneck. Among correctly localized text fields it was exact 97.9% of the time with class NMS, and all 5 errors were on account numbers: `8302653675` read as `B302653675`; `4077916523` read as `1077916523`; `0188416938` read as `018841693`.

Fig. 3 gives the per-class breakdown for the class-NMS variant. Account number is the weakest class, in both recall (96.7%) and OCR (91.4%).

B. Comparison with full-page Tesseract

Full-page Tesseract found 99.6% of the 240 text strings somewhere on the page (95% interval 97.7 to 99.9), which is higher than the 97.1% end-to-end figure. We do not read this as a win for either side. On clean, large, printed text, page-level OCR reads almost every string, and our matching rule is lenient to it, because it never has to say which field a string belongs to. The detect-then-read pipeline pays for field attribution, which the baseline does not provide at all, and on this dataset it does not buy better reading. Whether detection helps on degraded scans, where page-level OCR loses accuracy [2], [3], is the question this dataset cannot answer. Baseline cost was 0.63 seconds per document on one process.

C. Inference pattern

Table III and Fig. 4 compare three ways of running the same detector over 48 documents in Spark on two partitions, with detection only. All three produced the same 300 boxes, so they compute the same thing.

Loading the model once per partition was 1.7 times faster than loading it per row. The implied cost of one model load is about 167 ms, which is small because the nano model is small, and the benefit would grow with a larger model and a CUDA context to initialize, which we did not measure. Arrow batch size 16 was not distinguishable from batch size 1 here (5.6 against 5.7 seconds, within one standard deviation). The batching benefit that matters on a GPU is therefore untested by this experiment.

D. Dataflow

Fig. 5 contrasts the two inference patterns that Table III measures.

VIII. DISCUSSION AND LIMITATIONS

What this supports. The pipeline runs end to end under Spark, produces field-labeled text, and is reproducible from




Fig. 4. Wall time for 48 documents under three inference patterns. Error bars are one standard deviation over 3 runs.




Fig. 5. Row-wise UDF versus partition-level `mapInPandas`. The first reloads the model for every row. The second loads it once per partition and then scores Arrow batches.

one repository. Loading the model per partition is faster than per row, and detection quality at a fixed threshold can differ sharply from the threshold-free mAP that training reports.

What it does not support. The dataset is synthetic, clean, and generated from five templates of font and layout variation, so it is easy, and the high validation mAP reflects that. The results do not show that detection beats full-page OCR on real documents, and on this data it did not. There is a single training run and a 60-document test split, so intervals are wide. The detector is the nano model, trained on CPU. GPU execution, multi-node scaling, cluster start-up, cost, and Amazon Textract were not measured, and the GPU configuration in the released code is untested. Stronger baselines, such as LayoutLMv3 [10], Donut [11], and other open OCR engines, were not run.

Cold start. The batch design assumes cluster start-up cost is amortized over a queue of documents. It is a poor fit for sub-second interactive requests, for which a warm cluster or a dedicated model server is the better choice.

Next steps. The most informative next experiment is the same protocol on real, degraded scans with field-level labels, where the comparison with page-level OCR could go either way, followed by the GPU path on EMR.

IX. Ethical Considerations

Checks and identification documents contain sensitive personal data. All data here is synthetic. Any use of real documents should follow the institution's data-governance process and data-minimization principles such as those in the GDPR [21], with encryption at rest, separate access scopes for raw images and structured output, and human review for low-confidence detections rather than automated decisions. Synthetic data from a few templates does not establish fair performance across banks, regions, and languages, and that should be tested directly.

X. Conclusion

We built and released a Spark pipeline that detects financial form fields with YOLO26 and reads each with Tesseract, and we checked it by running it. The integration defects were real and are cataloged. On clean synthetic forms the pipeline reaches 97.1% end-to-end field accuracy with class-wise suppression, the end-to-end head emitted duplicates without it, and full-page OCR read the same strings at least as well, without saying which field each belonged to. Loading the model once per partition was 1.7 times faster than per row on CPU. Real scanned documents, GPU execution, and stronger baselines are the open questions, and the released code is meant to make those experiments cheap to run.

References

[1] R. Smith, "An overview of the Tesseract OCR engine," in *Proc. Int. Conf. Document Analysis and Recognition (ICDAR)*, vol. 2, 2007, pp. 629 to 633.

[2] K. Thammarak, P. Kongkla, Y. Sirisathitkul, and S. Intakosum, "Comparative analysis of Tesseract and Google Cloud Vision for Thai vehicle registration certificate," *Int. J. Electrical and Computer Engineering*, vol. 12, no. 2, pp. 1849 to 1858, Apr. 2022.

[3] C. Reisswig, A. R. Katti, M. Spinaci, and J. Höhne, "Chargrid-OCR: end-to-end trainable optical character recognition for printed documents using instance segmentation," arXiv:1909.04469, 2019.

[4] Amazon Web Services, "Amazon Textract." [Online]. Available: https://aws.amazon.com/textract/

[5] J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, "You only look once: unified, real-time object detection," in *Proc. IEEE Conf. Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 779 to 788.

[6] C.-Y. Wang, I.-H. Yeh, and H.-Y. M. Liao, "YOLOv9: learning what you want to learn using programmable gradient information," in *Proc. European Conf. Computer Vision (ECCV)*, 2024.

[7] A. Wang, H. Chen, L. Liu, K. Chen, Z. Lin, J. Han, and G. Ding, "YOLOv10: real-time end-to-end object detection," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.

[8] G. Jocher, J. Qiu, M. Liu, S. Lyu, F. C. Akyon, and M. E. Kalfaoglu, "Ultralytics YOLO26: unified real-time end-to-end vision models," arXiv:2606.03748, 2026.

[9] Z. Zhao, H. Kang, B. Wang, and C. He, "DocLayout-YOLO: enhancing document layout analysis through diverse synthetic data and global-to-local adaptive perception," arXiv:2410.12628, 2024.

[10] Y. Huang, T. Lv, L. Cui, Y. Lu, and F. Wei, "LayoutLMv3: pre-training for document AI with unified text and image masking," in *Proc. ACM Int. Conf. Multimedia*, 2022.

[11] G. Kim *et al.*, "OCR-free document understanding transformer," in *Proc. European Conf. Computer Vision (ECCV)*, 2022.

[12] G. Jaume, H. K. Ekenel, and J.-P. Thiran, "FUNSD: a dataset for form understanding in noisy scanned documents," in *Proc. Int. Conf. Document Analysis and Recognition Workshops (ICDARW)*, 2019.

[13] Z. Huang, K. Chen, J. He, X. Bai, D. Karatzas, S. Lu, and C. V. Jawahar, "ICDAR2019 competition on scanned receipt OCR and information extraction," in *Proc. Int. Conf. Document Analysis and Recognition (ICDAR)*, 2019.

[14] M. Zaharia *et al.*, "Resilient distributed datasets: a fault-tolerant abstraction for in-memory cluster computing," in *Proc. USENIX Symp. Networked Systems Design and Implementation (NSDI)*, 2012, pp. 15 to 28.

[15] NVIDIA, "RAPIDS accelerated user-defined functions," RAPIDS Accelerator for Apache Spark documentation. [Online]. Available: https://nvidia.github.io/spark-rapids/docs/additional-functionality/rapids-udfs.html
[16] NVIDIA, "RAPIDS Accelerator for Apache Spark," GitHub repository. [Online]. Available: https://github.com/NVIDIA/spark-rapids
[17] Apache Software Foundation, "pyspark.sql.DataFrame.mapInPandas," Apache Spark documentation. [Online]. Available: https://spark.apache.org/docs/latest/api/python/reference/pyspark.sql/api/pyspark.sql.DataFrame.mapInPandas.html
[18] Apache Software Foundation, "Custom resource scheduling and configuration overview," Apache Spark configuration documentation. [Online]. Available: https://spark.apache.org/docs/latest/configuration.html
[19] Amazon Web Services, "Amazon EMR documentation." [Online]. Available: https://docs.aws.amazon.com/emr/
[20] Amazon Web Services, "AWS Step Functions documentation." [Online]. Available: https://docs.aws.amazon.com/step-functions/
[21] European Parliament and Council of the European Union, "Regulation (EU) 2016/679 (General Data Protection Regulation)," *Official Journal of the European Union*, 2016.