

Carleton University
Department of Systems and Computer Engineering
SYSC 2006 - Foundations of Imperative Programming - Winter 2014

Lab 8 - Developing a List Collection, Second Iteration

Objective

To continue the development of a C module that implements a list collection. This lab provides a comprehensive review of structures, pointers to structures, dynamically allocated arrays and pointers to arrays.

Attendance/Demo

To receive credit for this lab, you must make the effort to finish a reasonable number of exercises and demonstrate the code you complete. **Also, you must submit your lab work to cuLearn by the end of the lab period.** (Instructions are provided in the *Wrap Up* section at the end of this handout.)

When you have finished all the exercises, call a TA, who will review the code you wrote. For those who don't finish early, a TA will ask you to demonstrate whatever code you've completed, starting about 30 minutes before the end of the lab period. **Any unfinished exercises should be treated as "homework" and must be completed before you work on Lab 9.**

General Requirements

Finish each exercise (i.e., write the function and verify that it passes all of its tests) before you move on to the next one. Don't leave testing until after you've written all your functions.

None of the functions you write should perform console input; i.e., contain `scanf` statements. Unless otherwise specified, none of your functions should produce console output; i.e., contain `printf` statements.

You have been provided with four files:

- `additional_functions.c` contains incomplete definitions of several functions you have to design and code;
- `additional_prototypes.h` contains declarations (function prototypes) for the functions you'll implement.
- `main.c` and `sput.h` implement a *test harness* (functions that will test your code, and a `main` function that calls these test functions). **Do not modify `main()` or any of the test functions.**

Instructions

1. Create a new folder named **Lab 8**.
2. Launch Pelles C and create a new Pelles C project named `array_list` inside your **Lab 8** folder. The project type must be Win32 Console program (EXE). You should now have a folder

named `array_list` inside your Lab 8 folder (check this).

3. Copy your `array_list.c` and `array_list.h` files from Lab 7 into your `array_list` folder. **Do not copy `main.c` (the test harness) from Lab 7.** You've been provided with a new `main.c` for this week's lab.
4. Download file `main.c`, `additional_functions.c`, `additional_prototypes.h` and `sput.h` from cuLearn. Move these files into your `array_list` folder.
5. You must add `main.c` and `array_list.c` to your project. From the menu bar, select **Project > Add files to project...** In the dialogue box, select `main.c`, then click **Open**. An icon labelled `main.c` will appear in the Pelles C project window. Repeat this for `array_list.c`.

Do not add `additional_functions.c` and `additional_prototypes.h` to your project.

You don't need to add `array_list.h` and `sput.h` to the project. Pelles C will do this after you've added `main.c`.

6. In this lab, you're going to implement several additional functions in the module you developed in Lab 7. To get started, you need to add the declarations (prototypes) for these functions to `array_list.h`, and incomplete implementations to `array_list.c`.

Open `array_list.h` and `additional_prototypes.h`. Copy all the function prototypes in `additional_prototypes.h` and paste them at the end of `array_list.h`. Close `additional_prototypes.h`.

Open `array_list.c` and `additional_functions.c`. Copy all the function definitions in `additional_prototypes.c` and paste them at the end of `array_list.c`. Close `additional_functions.h`.

7. Build the project. It should build without any compilation or linking errors.
8. Execute the project. The test harness will report several errors as it runs, which is what we'd expect, because you haven't started working on the functions that the harness tests.

Exercise 1

File `array_list.c` contains an incomplete definition of a function named `intlist_index`. This function returns the index (position) of the first occurrence of an integer in the list pointed to by parameter `list`. The function prototype is:

```
int intlist_index(const IntList *list, int target);
```

This function should terminate (via `assert`) if parameter `list` is `NULL`.

If `target` is in the list, the function should return the index of the first occurrence. If `target` is not in the list, the function should return -1.

Finish the implementation of this function.

Build the project, correcting any compilation errors, then execute the project. The test harness will run. Inspect the console output, and verify that your `intlist_index` function passes all the tests in the test suite before you start Exercise 2.

Exercise 2

File `array_list.c` contains an incomplete definition of a function named `intlist_count`. This function counts the number of occurrences of a specified integer in the list pointed to by parameter `list`, and returns that number. The function prototype is:

```
int intlist_count(const IntList *list, int target);
```

This function should terminate (via `assert`) if parameter `list` is `NULL`.

The function returns the count of the number of times that `target` is found in the list.

Finish the implementation of this function.

Build the project, correcting any compilation errors, then execute the project. The test harness will run. Inspect the console output, and verify that your `intlist_count` function passes all the tests in the test suite before you start Exercise 3.

Exercise 3

File `array_list.c` contains an incomplete definition of a function named `intlist_contains`. This function determines if the list pointed to by parameter `list` contains a specified integer. The function prototype is:

```
_Bool intlist_contains(const IntList *list, int target);
```

This function should terminate (via `assert`) if parameter `list` is `NULL`.

If `target` is in the list, the function should return `true`; otherwise it should return `false`.

Finish the implementation of this function.

Hint: you can implement this function in only few lines of code by calling one or more of the other functions in your module.

Build the project, correcting any compilation errors, then execute the project. The test harness will run. Inspect the console output, and verify that your `intlist_contains` function passes all the tests in the test suite before you start Exercise 4.

Exercise 4

File `array_list.c` contains an incomplete definition of a function named `intlist_delete`. This function deletes the integer at the specified position in the list pointed to by parameter `list`. The function prototype is:

```
void intlist_delete(IntList *list, int index);
```

Parameter `index` is the index (position) of the integer that should be removed. If a list contains `size` integers, valid indices range from 0 to `size-1`.

This function should terminate (via `assert`) if parameter `list` is `NULL` or if parameter `index` is not valid.

When your function deletes the integer at position `index`, the array elements at positions 0 through `index-1` will not change; however, the elements at positions `index+1` through `size-1` must all be "shifted" one position to the left. Example: if a list contains `[2, 4, 6, 8, 10]`, then calling `intlist_delete` with `index` equal to 2 changes the list to `[2, 4, 8, 10]`. Notice that 8 has been copied from position 3 to position 2, and 10 has been copied from position 4 to position 3.

Finish the implementation of this function.

Build the project, correcting any compilation errors, then execute the project. The test harness will run. Inspect the console output, and verify that your `intlist_delete` function passes all the tests in the test suite before you start Exercise 5.

Exercise 5

File `array_list.c` contains an incomplete definition of a function named `intlist_remove`.

This function removes the first occurrence of a specified integer in the list pointed to by parameter `list`. The function prototype is:

```
_Bool intlist_remove(IntList *list, int target);
```

This function should terminate (via `assert`) if parameter `list` is `NULL`.

If `target` is found and removed from the list, this function should return `true`. If `target` is not found, the function should leave the list unchanged and return `false`.

If `target` is found at position i , the array elements at positions 0 through $i-1$ will not change; however, the elements at positions $i+1$ through `size-1` must all be "shifted" one position to the left. Example: if a list contains `[2, 4, 6, 8, 10]`, then calling `intlist_remove` with `target` equal to 8 changes the list to `[2, 4, 6, 10]`.

Finish the implementation of this function.

Hint: you can implement this function in only few lines of code by calling one or more of the other functions in your module.

Build the project, correcting any compilation errors, then execute the project. The test harness will run. Inspect the console output, and verify that your `intlist_remove` function passes all the tests in the test suite before you start Exercise 6.

Exercise 6

Lists created by `intlist_construct` have a fixed capacity, and `intlist_append` currently returns `false` if it attempts to add an integer to a full list. We would like to remove this limitation.

File `array_list.c` contains an incomplete definition of a function named `increase_capacity` that attempts to enlarge a list's capacity to the specified new capacity. Here is the function prototype:

```
void increase_capacity(IntList *list, int new_capacity);
```

This function should terminate (via `assert`) if parameter `list` is `NULL` or if the new capacity is not greater than the list's current capacity.

The function should not change the order of the integers stored in this list; for example, suppose a list contains `[4 7 3 -2 9]` when `increase_capacity` is called. When the function returns, the list's capacity will have been increased, and it will contain the same integers, in the same order (4 is stored at index 0, 7 is stored at index 1, etc.)

Finish the implementation of this function. It's up to you to decide how the function should handle any memory allocation errors that occur while it is executing.

Hint: it's not enough to change the value stored in the `IntList` structure's `capacity` member!

Build the project, correcting any compilation errors, then execute the project. The test harness will run.

Inspect the console output, and verify that your `increase_capacity` function passes all the tests in the test suite before you start Exercise 7.

Exercise 7

Modify your `intlist_append` function so that, if the list is full, it doubles the list's capacity before appending the element. The function's return type and parameter list must not be changed. Your function must call your `increase_capacity` function.

Build the project, correcting any compilation errors, then execute the project. The test harness will run. Inspect the console output, and verify that your `intlist_append` function passes all the tests in the test suite.

Wrap-up

1. Remember to have a TA review and grade your solutions to the exercises before you leave the lab.
2. The next thing you'll do is package the project in a ZIP file (compressed folder) named `array_list`.
 - From the menu bar, select **Project > ZIP Files...** A **Save As** dialog box will appear. If you named your Pelles C project `array_list`, the zip file will have the same name by default; otherwise, you'll have to edit the **File name:** field and rename the file to `array_list` before you save it. **Do not use any other name for your zip file** (e.g., `lab8.zip`, `my_project.zip`, etc.).
 - Click **Save**. Pelles C will create a compressed (zipped) folder, which will contain copies of the the source code and several other files associated with the project. (The original files will not be removed). The compressed folder will be stored in your project folder (i.e., folder `array_list`).
3. Log in to cuLearn and submit `array_list.zip`.
 - Click the **Submit Lab 8** link. After you click the **Add submission** button, drag `array_list.zip` to the **File submissions** box. Do not submit another type of file (e.g., a Pelles C `.ppj` file, RAR file, a `.txt` file, etc.)
 - After the icon for the file appears in the box, click the **Save changes** button. At this point, the submission status for your file is **"Draft (not submitted)"**. You can resubmit the file by clicking the **Edit my submission** button.
 - Once you're sure that you don't want to make any changes, click the **Submit assignment** button. This will change the submission status to **"Submitted for grading"**. **Note: after you've clicked the Submit assignment button, you cannot resubmit the file.**