# KEYWORD IN JAVA

**Java keywords** are also known as reserved words. Keywords are particular words that act as a key to a code. These are predefined words by Java so they cannot be used as a variable or object name or class name.

**Example:**

```
// Java Program to Illustrate What If We use the keywords as
// the variable name

// Driver Class
public class HelloWorld {
    // Main Function
    public static void main(String[] args)
    {
        // Note "this" is a reserved
        // word in java
        String this = "Hello World!";
        System.out.println(this);
    }
}
// Code Contributed by @Shubham Jain
```

**Output:**

```
HelloWorld.java:11: error: not a statement
        String this = "Hello World!";
        ^
HelloWorld.java:11: error: ';' expected
        String this = "Hello World!";
^
2 errors
```



©Topperworld

**Here's the complete list of all keywords in Java programming.**

- **abstract**: used to declare a class or method as abstract. An abstract class is a class that cannot be instantiated, and an abstract method is a method without a body that must be implemented in a subclass.
- **assert**: used to perform assertion testing in Java. An assertion is a statement that should always be true, and if it is false, then an **AssertionError** is thrown.
- **boolean**: used to declare a boolean variable, which can only have two values: true or false.
- **break**: used to break out of a loop or switch statement.
- **byte**: used to declare a byte variable, which is a data type that can store values from -128 to 127.
- **case**: used in a switch statement to define a case label.
- **catch**: used to catch and handle exceptions in Java.
- **char**: used to declare a char variable, which is a data type that can store a single character.
- **class**: used to declare a class in Java.
- **const**: a keyword that was reserved but never implemented in Java.
- **continue**: used to skip the current iteration of a loop and continue to the next iteration.
- **default**: used in a switch statement to define a default case.
- **do**: used to start a do-while loop.
- **double**: used to declare a double variable, which is a data type that can store decimal values.
- **else**: used in an if statement to define an alternative block of code to execute if the condition is false.


©Topperworld

- **enum**: used to declare an enumeration, which is a type that consists of a set of named constants.
- **extends**: used to extend a class in Java.
- **final**: used to declare a variable or method as final, which means that its value or implementation cannot be changed.
- **finally**: used in a try-catch block to define a block of code that will always be executed, regardless of whether an exception is thrown or not.
- **float**: used to declare a float variable, which is a data type that can store decimal values with less precision than double.
- **for**: used to start a for loop.
- **goto**: a keyword that was reserved but never implemented in Java.
- **if**: used to define a conditional statement in Java.
- **implements**: used to implement an interface in Java.
- **import**: used to import a package or class into a Java program.
- **instanceof**: used to check if an object is an instance of a particular class or interface.
- **int**: used to declare an int variable, which is a data type that can store whole numbers.
- **interface**: used to declare an interface in Java.
- **long**: used to declare a long variable, which is a data type that can store larger whole numbers than int.
- **native**: used to declare a method as native, which means that its implementation is provided by the underlying platform, rather than in Java code.
- **new**: used to create a new object in Java.
- **package**: used to define a package in Java.


©Topperworld

- **private**: used to declare a variable or method as private, which means that it can only be accessed within the same class.
- **protected**: used to declare a variable or method as protected, which means that it can be accessed within the same class or any subclass.
- **public**: used to declare a variable or method as public, which means that it can be accessed from anywhere in the Java program.
- **return**: used to return a value from a method or exit a method without returning a value.
- **short**: used to declare a short variable, which is a data type that can store smaller whole numbers than int.
- **static**: used to declare a variable or method as static, which means that it belongs to the class rather than to individual objects of the class.
- **strictfp**: used to enforce strict floating-point precision in Java.
- **super**: used to call a method or constructor in the superclass.
- **switch**: used to start a switch statement in Java.
- **synchronized**: used to ensure that only one thread can access a block of code or object at a time in Java.
- **this**: used to refer to the current object in Java.
- **throw**: used to throw an exception in Java.
- **throws**: used to declare that a method may throw an exception in Java.
- **transient**: used to declare a variable as transient, which means that it will not be serialized when the object is written to a file or transmitted over a network.
- **try**: used to start a try-catch block in Java.
- **void**: used to declare a method that does not return a value.


©Topperworld

- **volatile**: used to declare a variable as volatile, which means that it is subject to optimization by the Java Virtual Machine.

## Keywords in Java:

| | | | | |
|---|---|---|---|---|
| abstarct | continue | for | new | switch |
| assert | default | goto | package | synchronized |
| boolean | do | if | private | this |
| break | double | implements | protected | throw |
| byte | else | import | public | throws |
| case | enum | instanceof | return | transient |
| catch | extends | int | short | try |
| char | final | interface | static | void |
| class | finally | long | strictfp | volatile |
| const | float | native | super | while |


©Topperworld