Customize Switch with Network modules using CISCO PACKET TRACER

Aim:

To customize a modular switch by installing Fast ethernet and Gigabit Ethernet modules and verify network connectivity using ping.

Requirements:

Cisco Packet Tracer
Switch - PT-EMPTY
Two PCs and Cisco 2911 Router
PT-SWITCH-NM-1FFE (2 modules)
PT-SWITCH-NM-1FGE (1 module)
copper and fiber cables.

Procedure:

1. Place the switch, two PCs, and router in the workspace.
2. Open the switch's Physical tab, turn it OFF.
3. Install two PT-SWITCH-NM-1FFE modules in slots 0 and 1.
4. Install one PT-SWITCH-NM-1FGE module in slot 2.
5. Turn the switch ON and connect both PCs using copper cables.
6. Install a compatible fiber module.
7. Configure the router and PC IP addresses.
8. Verify interface and test connectivity using ping.

IP ADDRESS CONFIGURATION:

Device	IP Address	Subnet mask
Router	192.168.10.1	255.255.255.0
PC-0	192.168.10.2	255.255.255.0
PC-1	192.168.10.3	255.255.255.0

Router configuration:

Router> enable
Router# configure terminal
Router(config)# interface gigabitEthernet 0/0/1
Router(config-if)# ip address 192.168.10.1 255.255.255.0
Router(config-if)# no shutdown
Router(config-if)# exit
Router(config)# exit
Router# write memory

Verification:

On the switch, execute:

switch> enable
switch# show ip interface brief

ping 192.168.10.1
ping 192.168.10.3

Successful replies indicate connectivity

Result:

The modular switch was customized with Fast Ethernet and Gigabit Ethernet modules, the router interface was configured, and network connectivity was tested successfully using ping.