12/5/22, 8:27 PM exp11.py

```
1 # Author: Ramesh Pai
 2 # Affiliation: 201104047, TE-E&TC Engg, Sem.5, 2021-22, GCE.
 4 # importing python modules
 5 import matplotlib.pyplot as plt
 6 from scipy.fft import fft, fftshift
 7 import numpy as np
 8 import random
9
10 # vc: Amplitude of Carrier Signal
11 # fc: frequency(Hz) of Carrier Signal
12 # Td: Number of bits in the Binary Data(Bipolar NRZ)
13
14 def values(vc, fc, Td):
15
       fs = 600 #sampling frequency
16
       dt = 1/fs #sample time interval or time-steps for time-domain signal
17
18
       t = np.arange(0, 5, dt) #time indices for time-domain signal
       n = np.size(t) #number of samples
19
       df = fs/n #frquency interval or frequency-steps for frequency-spectrum
20
       f = np.arange(-fs/2, fs/2, df) #frequency indices for frquency-spectrum
21
22
23
       # plot1: Carrier Signal v/s Time
24
25
       v_c = vc*np.sin(2*np.pi*fc*t) #Carrier Signal
       plt.subplot(2, 2, 1)
26
27
       plt.plot(t, v_c)
       plt.title("Carrier Signal", loc='left')
28
       plt.xlabel("t(sec)", loc='right')
29
       plt.ylabel("v_c(Volts)")
30
31
32
       # plot2: Modulating Signal(Bipolar NRZ) v/s Time
33
34
       #list for storing random input bit sequence generated
35
       bitData = []
36
       for x in range(Td):
           x = random.randint(0, 1)
37
           bitData.append(x)
38
39
       print(f"input bit sequence: {bitData}") #printing the input bit sequence
40
41
42
       #number of points in the time duration
43
       Td len = int(len(t)/Td)
44
       #list for storing number of points in time duration
45
46
       Td_arr = []
       for x in range(Td+1):
47
48
           x *= Td_len
49
           Td_arr.append(x)
50
       sqSignal = [] #Modulating Signal(Bipolar NRZ)
51
       for x in range(len(bitData)):
52
53
           if bitData[x] == 1:
               x = [1]*(Td_arr[x+1] - Td_arr[x])
54
55
               sqSignal.extend(x)
56
               x = [-1]*(Td_arr[x+1] - Td_arr[x])
57
               sqSignal.extend(x)
58
59
```

12/5/22, 8:27 PM exp11.py

```
sqSignal = np.array(sqSignal) #converting list into numpy array
60
61
       plt.subplot(2, 2, 2)
62
       plt.plot(t, sqSignal)
       plt.title(f"Modulating Signal (Binary Data: {bitData})", loc='left')
63
       plt.xlabel("t(sec)", loc='right')
64
       plt.ylabel("sqSignal(Volts)")
65
66
       # plot3: FSK(Frequency Signal Keying) Signal v/s Time
67
68
       fd = 1 #frequency deviation
69
70
       v_f = vc*np.sin(2*np.pi*(fc + sqSignal*fd)*t)
       plt.subplot(2, 2, 3)
71
       plt.plot(t, sqSignal, color = 'r', linestyle = 'dotted', label = 'modulating
72
   signal')
73
       plt.plot(t, v_f, label = 'FSK Signal')
       plt.title("FSK Signal", loc='left')
74
       plt.xlabel("t(sec)", loc='right')
75
76
       plt.ylabel("v_f(Volts)")
77
78
       # plot4: Spectrum of the FSK(Frequency Shift Keying) Signal v/s Frequency
79
80
       v_f_spec = fftshift(fft(v_f)) #FFT of FSK Signal(Complex in nature)
81
       plt.subplot(2, 2, 4)
       plt.plot(f, abs(v_f_spec)/n) #PLotting frequency indices v/s Normalised magnitude
82
  of FFT ASK signal
       plt.xlim(-20, 20)
83
       plt.title("Spectrum of FSK Signal", loc='left')
84
       plt.xlabel("frequency(Hz)", loc='right')
85
       plt.ylabel("Magnitude")
86
87
       plt.subplot tool()
88
       plt.show()
89
90
91 values(1, 3, 5) #assigning values to parameters
```

localhost:4649/?mode=python 2/2