Overview Package   Class Use Tree Deprecated Index Help

Java Platform 1.2
Beta 4

PREV CLASS   NEXT CLASS

FRAMES   NO FRAMES

SUMMARY: INNER | FIELD | CONSTR | METHOD

DETAIL: FIELD | CONSTR | METHOD

Class java.net.URLEncoder

```
java.lang.Object
  |
  +--java.net.URLEncoder
```

public class **URLEncoder**
extends Object

The class contains a utility method for converting a `String` into a MIME format called "`x-www-form-urlencoded`" format.

To convert a `String`, each character is examined in turn:

- The ASCII characters '`a`' through '`z`', '`A`' through '`Z`', and '`0`' through '`9`' remain the same.
- The space character '` `' is converted into a plus sign '`+`'.
- All other characters are converted into the 3-character string "`%`*xy*", where *xy* is the two-digit hexadecimal representation of the lower 8-bits of the character.

Since:
> JDK1.0

Method Summary

static String	**encode**(String s) Translates a string into `x-www-form-urlencoded` format.

Methods inherited from class java.lang.Object
clone , equals , finalize , getClass , hashCode , notify , notifyAll , toString , wait , wait , wait

Method Detail

encode

```
public static String encode(String s)
```

> Translates a string into `x-www-form-urlencoded` format.
>
> **Parameters:**
> > `s` - `String` to be translated.
>
> **Returns:**
> > the translated `String`.

Overview Package   Class Use Tree Deprecated Index Help

Java Platform 1.2
Beta 4

PREV CLASS   NEXT CLASS

FRAMES   NO FRAMES

SUMMARY: INNER | FIELD | CONSTR | METHOD

DETAIL: FIELD | CONSTR | METHOD