
Table of Contents

.....	1
Import data	1
Test Input	1
Construct final window	2
Bandpass using Gammatone Filterbank	2
Segment the data as needed (nonoverlapping)	3

```
addpath('toolboxes/malcolm_toolbox/');
addpath('resources/heli_and_boat_short');

nsegments_in = 20; % select number of segments to process for testing
testing1 = 1; %1 if testing with synthetic data, 0 if not
testing2 = 0;
```

Import data

```
[x, fs] = audioread('resources/heli_and_boat_short/
heli6_short.wav'); %assume 44.1kHz
%[x, fs] = audioread('resources/Cessna.wav'); %assume 44.1kHz
x = mean(x,2); % col vector

% Resample to around 8KHz
x = resample(x,2,11);
fs = fs*2/11;
%x = resample(x,1,2);
%fs = fs/2;
xlen = length(x);
```

Test Input


```
if(testing1)
    clear all;
    fs = 1000;
    t = 1:1/fs:10;
    f = 2+sin(t); %frequency oscillation between 1 and 3 Hz
    x = sin(2*pi*cumsum(f)/1000);
    figure;
    plot(t,x);
    title('test input');
    xlen = length(x);
    nsegments_in = 20;
elseif testing2
    clear all;
    fs = 1000;
    fc = 200;
    t = 0:1/fs:10;
    xin = sin(2*pi*30*t);
    fDev = 50; % deviation of 50Hz
```

```

x = fmmmod(xin, fc, fs, fDev);
figure;
plot(t,x);
title('test input');
xlen = length(x);
nsegments_in = 20;

```

```
end
```



Construct final window

```

ham_t = .25; %250 ms duration window
ham_N = floor(ham_t*fs);
w = hamming(ham_N);
wshift = 4; %4hz
exp_modulator = exp(1j*wshift.*(1:ham_N)); %mod by 4 hz
exp_modulator = exp_modulator.';
w = w.*exp_modulator;

```

Bandpass using Gammatone Filterbank

```

% Make the center frequency vector
numChannels = 19;
lowFreq = 200; %?

```

```

fcoefs = MakeERBFilters(fs,numChannels,lowFreq);
%LOW_CF = 200;
%HIGH_CF = 4000;
%NUMCHANS = 18;
%CFS = iosr.auditory.makeErbCFs(LOW_CF,HIGH_CF,NUMCHANS);

```

Segment the data as needed (nonoverlapping)

```

segmentlen = fs;
nsegments_total = floor(xlen/segmentlen);

nsegments = min(nsegments_in,nsegments_total); % for testing

start_pos = 1;

% Operate on each time segment
for segmentind = 1:nsegments
    end_pos = start_pos + segmentlen - 1;

    x_segment = x(start_pos:end_pos);

    BM = ERBFilterBank(x_segment, fcoefs); %operate on every col
    BM = BM.';

    for channum = 1:numChannels

        % calculate envelope and downsample
        envt = envelope(BM(:,channum)); %operate on every col
        envt = downsample(envt, 100);

        % normalize
        envt = envt./mean(abs(envt));

        % bp filter
        bp_sig = log10(abs(filter(w, 1, envt)));

        % threshold
        bp_sig(bp_sig>0) = 0;
        bp_sig(bp_sig<(-30)) = -30;

        out_chann(:,channum) = bp_sig;
    end

    out(:, :, segmentind) = out_chann.';

    start_pos = start_pos + segmentlen;

end

for segmentind = 1:nsegments
    figure;
    data = out(:, :, segmentind);


```



```



imagesc(data);
title(['mod specgram for frame number ' num2str(segmentind)]);
ylabel('filterbank frequencies (Hz)');
xlabel('acoustic frequencies (Hz)');
axis xy; colormap(jet);
colorbar;



%   SPACING = (HIGH_CF-LOW_CF)/NUMCHANS;
%   yticklabels = LOW_CF:SPACING:HIGH_CF;
%   yticks = linspace(1, size(data,2), numel(yticklabels));
%   set(gca, 'YTick', yticks, 'YTickLabel', yticklabels);
end



```











Published with MATLAB® R2017a