
Table of Contents

.....	1
Import data	1
Bandpass using Gammatone Filterbank	1
Segment the data as needed (nonoverlapping)	1

```
addpath('toolboxes/');
nsegments_in = 20; % select number of segments to process for testing
```

Import data

```
%[x, fs] = audioread('resources/heli_and_boat_short/boat2_short.wav');
%assume 44.1kHz
[x, fs] = audioread('resources/Cessna.wav'); %assume 44.1kHz
x = mean(x,2);% col vector

% Resample to around 8KHz
x = resample(x,2,11);
fs = fs*2/11;
%x = resample(x,1,2);
%fs = fs/2;
xlen = length(x);

% Construct final window
ham_t = .25; %250 ms duration window
ham_N = floor(ham_t*fs);
w = hamming(ham_N);
wshift = 4; %4hz
exp_modulator = exp(1j*2*pi*wshift.*(1:ham_N)); %mod by 4 hz
exp_modulator = exp_modulator.';
w = w.*exp_modulator;
```

Bandpass using Gammatone Filterbank

```
% Make the center frequency vector
LOW_CF = 200;
HIGH_CF = 4000;
NUMCHANS = 18;
CFS = iosr.auditory.makeErbCFs(LOW_CF,HIGH_CF,NUMCHANS);
```

Segment the data as needed (nonoverlapping)

```
segmentlen = fs;
nsegments_total = floor(xlen/segmentlen);

nsegments = min(nsegments_in,nsegments_total); % for testing

start_pos = 1;
```

```

% Operate on each time segment
for segmentind = 1:nsegments
    end_pos = start_pos + segmentlen - 1;

    x_segment = x(start_pos:end_pos);

    BM = iosr.auditory.gammatoneFast(x_segment,CFS,fs); %operate on
every col

    for channum = 1:NUMCHANS

        % calculate envelope and downsample
        envt = envelope(BM(:,channum)); %operate on every col
        envt = downsample(envt, 100);

        % normalize
        envt = envt./mean(abs(envt));

        % bp filter
        bp_sig = log10(abs(filter(w, 1, envt)));

        % threshold
        bp_sig(bp_sig>0) = 0;
        bp_sig(bp_sig<(-30)) = -30;

        out_chann(:,channum) = bp_sig;
    end

    out(:, :, segmentind) = out_chann;

    start_pos = start_pos + segmentlen;

end

for segmentind = 1:nsegments
    figure;
    data = out(:, :, segmentind);
    imagesc(data);
    title(['mod specgram for frame number ' num2str(segmentind)]);
    xlabel('filterbank frequencies (Hz)');
    ylabel('acoustic frequencies (Hz)');
    axis xy; colormap(jet);
    colorbar;



    xticklabels = LOW_CF:NUMCHANS:HIGH_CF;
    xticks = linspace(1, size(data,2), numel(xticklabels));
    set(gca, 'XTick', xticks, 'XTickLabel', xticklabels);
end



```



Warning: Integer operands are required for colon operator when used as index



Warning: Integer operands are required for colon operator when used as index



[illegible]































Published with MATLAB® R2017a