



8.2.3.9.6 Transmit Descriptor Base Address High — TDBAH[n] (0x06004+0x40*n, n=0...127; RW)

Field	Bit(s)	Init Val	Description
TDBAH	31:0	X	Transmit Descriptor Base Address [63:32].

This register contains the upper 32 bits of the 64 bit Descriptor base address.

8.2.3.9.7 Transmit Descriptor Length — TDLEN[n] (0x06008+0x40*n, n=0...127; RW)

Field	Bit(s)	Init Val	Description
LEN	19:0	0x0	Descriptor Ring Length. This register sets the number of bytes allocated for descriptors in the circular descriptor buffer. It must be 128byte-aligned (7 LS bit must be set to zero). <i>Note:</i> Validated Lengths up to 128K (8K descriptors).
Reserved	31:20	0x0	Reads as 0x0. Should be written to 0x0.

8.2.3.9.8 Transmit Descriptor Head — TDH[n] (0x06010+0x40*n, n=0...127; RO)

Field	Bit(s)	Init Val	Description
TDH	15:0	0x0	Transmit Descriptor Head.
Reserved	31:16	0x0	Reserved. Should be written with 0x0.

This register contains the head pointer for the transmit descriptor ring. It points to a 16-byte datum. Hardware controls this pointer.

The values in these registers might point to descriptors that are still not in the host memory. As a result, the host cannot rely on these values in order to determine which descriptor to release.

The only time that software should write to this register is after a reset (hardware reset or CTRL.RST) and before enabling the transmit function (TXDCTL.ENABLE). If software were to write to this register while the transmit function was enabled, the on-chip descriptor buffers might be invalidated and the hardware could become confused.