

All Payment Options & High Performance with Printer

T300 Countertop Terminal is a powerful payment device can handle various payment transactions like credit card, debit card, EMV, loyalty, installment, contactless payment and QR code payment in a single terminal.























Features of T300 Countertop Terminal

- ARM® Cortex® 500MHz secure processor
- 2.8" LCD color large display
- Support EMV Chip & PIN (PCI PTS 5.x certified)
- Support Magstripe and contactless payment
- Support QR base application
- Communication interface with USB OTG & RS232
- Fast thermal printer
- Min. 2600mAh large capacity battery
- Wide keypad

Optional

- Built-in contactless reader
- Resistive touch screen
- GPRS/3G WCDMA communication, WIFI/Bluetooth® V4.x, Ethernet and dialup modem
- Dual SIM support
- Camera for barcode and QR code
- GPS
- Customize standpole

Specifications

Payment Magnetic track 1/2/3 acceptance types EMV

NFC Contactless (optional)
QR code base application

Processor ARM® Cortex® 500MHz secure processor

Memory 64MB RAM, 128/512MB Flash
Display 2.8" LCD color display (320 x 240)

Resistive touch screen & signature pad (optional)

Camera Optional

Thermal printer Printing speed: 30lines/sec Paper roll: 40mm diameter

Keys 20

Card slots SAM x max. 2 (optional) SIM x max. 2 (optional)

Communication Dial-up modem, Ethernet

interface Optional: GPRS/3G WCDMA, WIFI/Bluetooth®, GPS

Peripheral RS232 x max. 2 USB OTG x 1

Audio Optional

Battery Min. 2600mAh rechargeable battery

Power supply DC 9V 1A

Certifications PCI PTS 5.X EMV L1 & L2

Visa PayWave MasterCard Contactless
JCB J/Speedy American Express ExpressPay

CUP QuickPass SRED QPBOC TQM

FCC/CE

Operating 0 - 45°C

temperature

Storage -20 - 70°C

temperature

Operating humidity 5-95% non-condense

Dimensions & 165 (L) \times 80 (W) \times 63 (H) mm weight 360g (with battery)

*Specifications is subject to change without prior notice.



Standpole Peripherals

It is special designated for T300 Countertop Terminal which can move more than 270° tilt and swivel to fit for end-user needs.







