



Performance Accessibility Best Practices SEO PWA

There were issues affecting this run of Lighthouse:

- Chrome extensions negatively affected this page's load performance. Try auditing the page in incognito mode or from a Chrome profile without extensions.



Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)

▲ 0–49 50–89 90–100

METRICS

Expand view

First Contentful Paint

0.6 s

Largest Contentful Paint

2.4 s

Total Blocking Time

0 ms


Cumulative Layout Shift

0

Speed Index

1.1 s

View Treemap






# DIAGNOSTICS

## ▲ Properly size images — Potential savings of 2,175 KiB



Serve images that are appropriately-sized to save cellular data and improve load time. [Learn how to size images.](#)


	URL	Resource Size	Potential Savings
127.0.0.1 <span>1st Party</span>		2,187.5 KiB	2,175.5 KiB
 <div>d-img-top</div>	img...images/IMG_5400.jpg (127.0.0.1)	2,131.6 KiB	2,127.4 KiB
 <div>d-img-top</div>	img...images/OIP%20(2).jpg (127.0.0.1)	28.1 KiB	24.1 KiB
 <div>d-img-top</div>	img...images/OIP%20(1).jpg (127.0.0.1)	27.8 KiB	23.9 KiB

## ▲ Largest Contentful Paint element — 2,370 ms



This is the largest contentful element painted within the viewport. [Learn more about the Largest Contentful Paint element](#)

LCP

Element
 <div>img.card-img-top.mb-5.mb-md-0</div>



Phase	% of LCP	Timing
TTFB	5%	120 ms

Phase	% of LCP	Timing
Load Delay	8%	180 ms
Load Time	3%	70 ms
Render Delay	84%	1,990 ms

▲ Serve images in next-gen formats — Potential savings of 147 KiB



Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. [Learn more about modern image formats.](#)

URL	Resource Size	Potential Savings
127.0.0.1 <span>1st Party</span>	2,131.6 KiB	147.1 KiB
 <div>  <div>g-top</div> </div> <div> <div>im</div> <div>g.c</div> <div>ar</div> <div>d-</div> <div>im</div> </div> <div>...images/IMG_5400.jpg (127.0.0.1)</div>	2,131.6 KiB	147.1 KiB

▲ Enable text compression — Potential savings of 38 KiB



Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. [Learn more about text compression.](#) FCP LCP

URL	Transfer Size	Potential Savings
127.0.0.1 <span>1st Party</span>	51.9 KiB	37.7 KiB
...pages/Single-item.html (127.0.0.1)	26.2 KiB	19.3 KiB
...css/Main.css (127.0.0.1)	12.8 KiB	8.8 KiB
...js/progressbar.js (127.0.0.1)	8.1 KiB	6.3 KiB
...js/Main.js (127.0.0.1)	4.7 KiB	3.3 KiB

▲ Reduce unused CSS — Potential savings of 17 KiB



Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS.](#) FCP LCP

URL	Transfer Size	Potential Savings
JSDelivr CDN <span>Cdn</span>	<b>18.8 KiB</b>	<b>17.0 KiB</b>
...css/bootstrap.min.css (cdn.jsdelivr.net)	18.8 KiB	17.0 KiB

▲ Reduce unused JavaScript — Potential savings of 418 KiB



Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity.

[Learn how to reduce unused JavaScript.](#) LCP

☒ Show 3rd-party resources (3)

URL	Transfer Size	Potential Savings
Unattributable	<b>438.2 KiB</b>	<b>279.6 KiB</b>
chrome-extension://mmanaflgaempokjfbecabkdnkoidjam/screenshot.js	372.6 KiB	225.7 KiB
chrome-extension://fmkadmapgofadopljbjfkapdkoienihi/build/render.js	37.7 KiB	33.2 KiB
chrome-extension://efaidnbmninnibpcapjcgclclefindmkaj/libs/jquery-3.1.1.min.js	27.9 KiB	20.6 KiB
Selenium IDE <span>Chrome Extension</span>	<b>191.4 KiB</b>	<b>117.9 KiB</b>
chrome-extension://mooikfahbdckldjjndioackbalphokd/assets/atoms.js	159.9 KiB	91.4 KiB
chrome-extension://mooikfahbdckldjjndioackbalphokd/assets/playback.js	31.5 KiB	26.5 KiB
JSDelivr CDN <span>Cdn</span>	<b>24.5 KiB</b>	<b>20.2 KiB</b>
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	24.5 KiB	20.2 KiB
...js/src/tooltip.js	2.5 KiB	2.2 KiB
...js/src/dropdown.js	1.7 KiB	1.4 KiB
...js/src/carousel.js	1.6 KiB	1.3 KiB
...js/src/modal.js	1.4 KiB	1.2 KiB
...js/src/collapse.js	1.1 KiB	1.0 KiB

▲ Eliminate render-blocking resources — Potential savings of 280 ms



Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. [Learn how to eliminate render-blocking resources.](#) FCP LCP

URL	Transfer Size	Potential Savings
JSDelivr CDN <span>Cdn</span>	34.3 KiB	250 ms
...css/bootstrap.min.css (cdn.jsdelivr.net)	34.3 KiB	250 ms





▲ Page prevented back/forward cache restoration — 1 failure reason ^


Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. [Learn more about the bfcache](#)

Failure reason	Failure type
Pages with WebSocket cannot enter back/forward cache. ...pages/Single-item.html (127.0.0.1)	Pending browser support

Image elements do not have explicit width and height ^

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn how to set image dimensions](#) CLS

URL		
127.0.0.1 <span>1st Party</span>		
	img.card-img-top	...images/IMG_5400.jpg (127.0.0.1)
	img.card-img-top	...images/OIP%20(2).jpg (127.0.0.1)
	img.card-img-top.mb-5.mb-md-0	...images/OIP.jpg (127.0.0.1)
	img.card-img-top	...images/OIP%20(1).jpg (127.0.0.1)

URL
<div><div></div><div>img.card-img-top</div></div> <div>...images/OIP.jpg (127.0.0.1)</div>

Minify CSS — Potential savings of 7 KiB



Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS.](#) FCP LCP

URL	Transfer Size	Potential Savings
127.0.0.1 <span>1st Party</span>	13.2 KiB	6.8 KiB
...css/Main.css (127.0.0.1)	13.2 KiB	6.8 KiB

Minify JavaScript — Potential savings of 31 KiB



Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript.](#) FCP LCP

☒ Show 3rd-party resources (1)

URL	Transfer Size	Potential Savings
Unattributable	54.0 KiB	24.9 KiB
chrome-extension://dmghijelimhndkbmpgbldicpogfkceaj/data/content_script/resources/native.js	20.4 KiB	9.7 KiB
chrome-extension://cjpalhdlnbpfafiamejdnhcphjbkeiagm/js/contentscript.js	14.7 KiB	7.8 KiB
chrome-extension://dmghijelimhndkbmpgbldicpogfkceaj/data/content_script/vendor/tinycolor.js	11.8 KiB	5.2 KiB
chrome-extension://dmghijelimhndkbmpgbldicpogfkceaj/data/content_script/inject.js	7.1 KiB	2.3 KiB
127.0.0.1 <span>1st Party</span>	8.1 KiB	3.7 KiB
...js/progressbar.js (127.0.0.1)	8.1 KiB	3.7 KiB
Selenium IDE <span>Chrome Extension</span>	7.1 KiB	2.8 KiB

URL	Transfer Size	Potential Savings
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/prompt.js	7.1 KiB	2.8 KiB

Avoid serving legacy JavaScript to modern browsers — Potential savings of 14 KiB



Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. [Learn how to use modern JavaScript](#) TBT

☐ Show 3rd-party resources (1)

URL	Potential Savings
Unattributable	14.0 KiB
chrome-extension://mmanaf1gaempokjfbeeabkadnkoidjam/screenshot.js	14.0 KiB
screenshot.js:1	Array.prototype.fill
screenshot.js:1	Array.prototype.filter
screenshot.js:1	Array.prototype.find
screenshot.js:1	Array.from
screenshot.js:1	Array.prototype.map
screenshot.js:1	Object.entries
screenshot.js:1	Object.keys
screenshot.js:1	@babel/plugin-transform-classes
screenshot.js:1	String.fromCodePoint
JSDelivr CDN <span>Cdn</span>	0.0 KiB
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	0.0 KiB
<a href="#">intro.min.js:16</a>	@babel/plugin-transform-classes

○ User Timing marks and measures — 1 user timing




Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more about User Timing marks.](#)

Name	Type	Start Time	Duration
__v3	Mark		0.00 ms


○ Avoid large layout shifts — 1 layout shift found

These are the largest layout shifts observed on the page. Each table item represents a single layout shift, and shows the element that shifted the most. Below each item are possible root causes that led to the layout shift. Some of these layout shifts may not be included in the CLS metric value due to [windowing](#). [Learn how to improve CLS](#) CLS

Element	Layout shift score
<div></div> <div>li.list-group-item.border-0</div> <div>0.000</div>	
...fonts/bootstrap-icons.woff2?1bb8886... (cdn.jsdelivr.net)	Web font loaded
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	A late network request adjusted the page layout
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	A late network request adjusted the page layout
...js/progressbar.js (127.0.0.1)	A late network request adjusted the page layout
...js/Main.js (127.0.0.1)	A late network request adjusted the page layout
...minified/introjs.min.css (cdn.jsdelivr.net)	A late network request adjusted the page layout
...font/bootstrap-icons.css (cdn.jsdelivr.net)	A late network request adjusted the page layout
...css/bootstrap.min.css (cdn.jsdelivr.net)	A late network request adjusted the page layout
...css/Main.css (127.0.0.1)	A late network request adjusted the page layout

○ Avoid non-composited animations — 1 animated element found

Animations which are not composited can be janky and increase CLS. [Learn how to avoid non-composited animations](#) CLS

Element	Name
<div></div> <div>div.progress-bar.step-1-color</div> <div>Unsupported CSS Property: width</div> <div>width</div>	

○ Initial server response time was short — Root document took 0 ms

Keep the server response time for the main document short because all other requests depend on it. [Learn more about the Time to First Byte metric](#). FCP LCP



URL	Time Spent
127.0.0.1 <span>1st Party</span>	0 ms
...pages/Single-item.html (127.0.0.1)	0 ms

○ Avoids enormous network payloads — Total size was 2,478 KiB

Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes](#). LCP



☒ Show 3rd-party resources (5)

URL	Transfer Size
127.0.0.1 <span>1st Party</span>	2,234.3 KiB
...images/IMG_5400.jpg (127.0.0.1)	2,131.9 KiB
...images/OIP%20(2).jpg (127.0.0.1)	28.4 KiB
...images/OIP%20(1).jpg (127.0.0.1)	28.2 KiB
...pages/Single-item.html (127.0.0.1)	26.5 KiB
...images/OIP.jpg (127.0.0.1)	19.2 KiB
JSDelivr CDN <span>Cdn</span>	214.7 KiB
...fonts/bootstrap-icons.woff2?1bb8886... (cdn.jsdelivr.net)	128.1 KiB
...css/bootstrap.min.css (cdn.jsdelivr.net)	34.3 KiB
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	24.9 KiB
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	14.0 KiB
...font/bootstrap-icons.css (cdn.jsdelivr.net)	13.4 KiB

○ Avoids an excessive DOM size — 200 elements

A large DOM will increase memory usage, cause longer [style calculations](#), and produce costly [layout reflows](#). [Learn how to avoid an excessive DOM size](#). TBT

Statistic	Element	Value
Total DOM Elements		200

Statistic	Element	Value
Maximum DOM Depth		10
Maximum Child Elements		17

○ Avoid chaining critical requests — 8 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load.

[Learn how to avoid chaining critical requests.](#) FCP LCP

Maximum critical path latency: **194.216 ms**

*Initial Navigation*

...pages/Single-item.html (127.0.0.1)

...css/bootstrap.min.css (cdn.jsdelivr.net) - **14.382 ms, 34.32 KiB**

...css/Main.css (127.0.0.1) - **5.432 ms, 13.17 KiB**

...font/bootstrap-icons.css (cdn.jsdelivr.net)

...fonts/bootstrap-icons.woff2?1bb8886... (cdn.jsdelivr.net) - **24.06 ms, 128.07 KiB**

...minified/introjs.min.css (cdn.jsdelivr.net) - **20.331 ms, 1.95 KiB**

...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) - **18.923 ms, 24.90 KiB**

...js/Main.js (127.0.0.1) - **7.97 ms, 5.05 KiB**

...js/progressbar.js (127.0.0.1) - **8.11 ms, 8.50 KiB**

...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net) - **20.912 ms, 14.03 KiB**

○ JavaScript execution time — 0.2 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to reduce Javascript execution time.](#) TBT

URL	Total CPU Time	Script Evaluation	Script Parse
127.0.0.1 <span>1st Party</span>	171 ms	38 ms	18 ms
...pages/Single-item.html (127.0.0.1)	171 ms	38 ms	18 ms
Unattributable	150 ms	101 ms	48 ms

URL	Total CPU Time	Script Evaluation	Script Parse
chrome-extension://mmanafлгаempokjfbeeabkadnkoidjam/screenshot.js	150 ms	101 ms	48 ms

○ Minimizes main-thread work — 0.5 s



Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#) TBT

Category	Time Spent
Script Evaluation	208 ms
Script Parsing & Compilation	89 ms
Other	81 ms
Style & Layout	80 ms
Parse HTML & CSS	22 ms
Rendering	16 ms

○ Minimize third-party usage — Third-party code blocked the main thread for 0 ms



Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. [Learn how to minimize third-party impact](#). TBT

Third-Party	Transfer Size	Main-Thread Blocking Time
JSDelivr CDN <span>Cdn</span>	<b>217 KiB</b>	<b>0 ms</b>
...fonts/bootstrap-icons.woff2?1bb8886... (cdn.jsdelivr.net)	128 KiB	0 ms
...css/bootstrap.min.css (cdn.jsdelivr.net)	34 KiB	0 ms
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	25 KiB	0 ms
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	14 KiB	0 ms
...font/bootstrap-icons.css (cdn.jsdelivr.net)	13 KiB	0 ms
...minified/introjs.min.css (cdn.jsdelivr.net)	2 KiB	0 ms
Selenium IDE <span>Chrome Extension</span>	<b>7 KiB</b>	<b>0 ms</b>
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/prompt.js	7 KiB	0 ms



Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#) TBT

☒ Show 3rd-party resources (1)

URL	Start Time	Duration
Unattributable		<b>151 ms</b>
chrome-extension://cjpahdlnbpafamejdnhcphjbkeiagm/js/contentscript.js	264 ms	151 ms
Selenium IDE <span>Chrome Extension</span>		<b>72 ms</b>
chrome-extension://mooikfahbdckldjndioackbalphokd/assets/vendor/global.js	415 ms	72 ms

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

## PASSED AUDITS (16)

Hide

### Defer offscreen images



Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. [Learn how to defer offscreen images](#).

### Efficiently encode images



Optimized images load faster and consume less cellular data. [Learn how to efficiently encode images](#).

### Preconnect to required origins



Consider adding preconnect or dns-prefetch resource hints to establish early connections to important third-party origins. [Learn how to preconnect to required origins](#). FCP LCP

### Avoid multiple page redirects



Redirects introduce additional delays before the page can be loaded. [Learn how to avoid page redirects](#). FCP LCP

## ○ Preload key requests



Consider using `<link rel=preload>` to prioritize fetching resources that are currently requested later in page load. [Learn how to preload key requests](#). FCP LCP

### Use HTTP/2



HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. [Learn more about HTTP/2](#).

## Use video formats for animated content



Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. [Learn more about efficient video formats](#) LCP

## Remove duplicate modules in JavaScript bundles



Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. TBT

## Preload Largest Contentful Paint image



If the LCP element is dynamically added to the page, you should preload the image in order to improve LCP. [Learn more about preloading LCP elements](#). LCP

## Uses efficient cache policy on static assets — 0 resources found



A long cache lifetime can speed up repeat visits to your page. [Learn more about efficient cache policies](#).

## All text remains visible during webfont loads



Leverage the `font-display` CSS feature to ensure text is user-visible while webfonts are loading. [Learn more about font-display](#). FCP LCP

## ☐ Lazy load third-party resources with facades




Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. [Learn how to defer third-parties with a facade](#). TBT

## Largest Contentful Paint image was not lazily loaded



Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the largest contentful paint. [Learn more about optimal lazy loading](#). LCP

### Element



img.card-img-top.mb-5.mb-md-0

## Uses passive listeners to improve scrolling performance



Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. [Learn more about adopting passive event listeners](#).

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. [Learn how to avoid document.write\(\)](#).

Has a `<meta name="viewport">` tag with `width` or `initial-scale`

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag](#). TBT

76

## Accessibility


These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

### ARIA

▲ Elements with an ARIA `[role]` that require children to contain a specific `[role]` are missing some or all of those required children.

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements](#).

#### Failing Elements




ul



a.active







a



a


▲ `button`, `link`, and `menuitem` elements do not have accessible names.

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to make command elements more accessible.](#)

Failing Elements	
	a.active
	a
	a
	a

▲ Elements with `role="dialog"` or `role="alertdialog"` do not have accessible names. ^

ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. [Learn how to make ARIA dialog elements more accessible.](#)

Failing Elements	
	div.introjs-tooltip.introjs-bottom-left-aligned

▲ ARIA `progressbar` elements do not have accessible names. ^

When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#)

## Failing Elements



div.progress-bar.step-1-color

These are opportunities to improve the usage of ARIA in your application which may enhance the experience for users of assistive technology, like a screen reader.

## CONTRAST

▲ Background and foreground colors do not have a sufficient contrast ratio.



Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast.](#)


## Failing Elements



div.progress-bar.step-1-color



a



footer.py-3.my-4.text-center

These are opportunities to improve the legibility of your content.


## NAMES AND LABELS

▲ Form elements do not have associated labels



Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more about form element labels.](#)

## Failing Elements



input#inputQuantity.form-control.text-center.me-3



## Failing Elements



These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.


## NAVIGATION

### ▲ Heading elements are not in a sequentially-descending order




Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

## Failing Elements



h5.fw-bolder



h5

These are opportunities to improve keyboard navigation in your application.

## ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

### ○ Interactive controls are keyboard focusable



Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable.](#)

### ○ Interactive elements indicate their purpose and state



Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints.](#)

### ○ The page has a logical tab order



Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering.](#)

☐ Visual order on the page follows DOM order ^

DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering.](#)

☐ User focus is not accidentally trapped in a region ^

A user can tab into and out of any control or region without accidentally trapping their focus. [Learn how to avoid focus traps.](#)

☐ The user's focus is directed to new content added to the page ^

If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn how to direct focus to new content.](#)

☐ HTML5 landmark elements are used to improve navigation ^

Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more about landmark elements.](#)

☐ Offscreen content is hidden from assistive technology ^

Offscreen content is hidden with display: none or aria-hidden=true. [Learn how to properly hide offscreen content.](#)

☐ Custom controls have associated labels ^

Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. [Learn more about custom controls and labels.](#)

☐ Custom controls have ARIA roles ^

Custom interactive controls have appropriate ARIA roles. [Learn how to add roles to custom controls.](#)

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review.](#)

PASSED AUDITS (19) Hide

`[aria-*)` attributes match their roles ^

Each ARIA role supports a specific subset of `aria-*)` attributes. Mismatching these invalidates the `aria-*)` attributes. [Learn how to match ARIA attributes to their roles.](#)

`[aria-hidden="true"]` is not present on the document `<body>` ^

Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. [Learn how `aria-hidden` affects the document body.](#)

`[role]`s have all required `[aria-*)` attributes



Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#)

`[role]`s are contained by their required parent element



Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more about ARIA roles and required parent element.](#)

`[aria-*)` attributes have valid values



Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more about valid values for ARIA attributes.](#)

`[aria-*)` attributes are valid and not misspelled



Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more about valid ARIA attributes.](#)

Buttons have an accessible name



When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible.](#)

Image elements have `[alt]` attributes



Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

`[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5.



Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more about the viewport meta tag.](#)

`[role]` values are valid



ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more about valid ARIA roles.](#)

Document has a `<title>` element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

`[id]` attributes on active, focusable elements are unique



All focusable elements must have a unique `id` to ensure that they're visible to assistive technologies. [Learn how to fix duplicate ids.](#)

`<html>` element has a `[lang]` attribute

If a page doesn't specify a `lang` attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more about the `lang` attribute.](#)

`<html>` element has a valid value for its `[lang]` attribute

Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn how to use the `lang` attribute.](#)

Links are distinguishable without relying on color.

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#)

Links have a discernible name

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn how to make links accessible.](#)

No element has a `[tabindex]` value greater than 0

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more about the `tabindex` attribute.](#)

Values assigned to `role=""` are valid ARIA roles.

ARIA roles enable assistive technologies to know the role of each element on the web page. If the `role` values are misspelled, not existing ARIA `role` values, or abstract roles, then the purpose of the element will not be communicated to users of assistive technologies. [Learn more about ARIA roles.](#)

Image elements do not have `[alt]` attributes that are redundant text.

Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the `alt` attribute.](#)

NOT APPLICABLE (31)

Hide

☐ `[accesskey]` values are unique

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more about access keys.](#)

- `[aria-hidden="true"]` elements do not contain focusable descendents ^

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how aria-hidden affects focusable elements.](#)

- ARIA input fields have accessible names ^

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels.](#)

- ARIA `meter` elements have accessible names ^

When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#)

- Elements with the `role=text` attribute do not have focusable descendents. ^

Adding `role=text` around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. [Learn more about the `role=text` attribute.](#)

- ARIA toggle fields have accessible names ^

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about toggle fields.](#)

- ARIA `tooltip` elements have accessible names ^

When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name tooltip elements.](#)

- ARIA `treeitem` elements have accessible names ^

When a `treeitem` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about labeling `treeitem` elements.](#)

- The page contains a heading, skip link, or landmark region ^

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#)

- `<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#)

- Definition list items are wrapped in `<dl>` elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#)

○ ARIA IDs are unique ^

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#)

○ No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#)

○ `<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#)

○ `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the `lang` attribute.](#)

○ Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#)

○ `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#)

○ Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`). ^

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#)

○ List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements ^

Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. [Learn more about proper list structure.](#)

○ The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#)

☐ `<object>` elements have alternate text



Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#)

☐ Select elements have associated label elements.



Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element.](#)

☐ Skip links are focusable.



Including a skip link can help users skip to the main content to save time. [Learn more about skip links.](#)

☐ Tables have different content in the summary attribute and `<caption>`.



The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#)

☐ Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table.



Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more about the headers attribute.](#)

☐ `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe.



Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers.](#)

☐ `[lang]` attributes have a valid value



Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the lang attribute.](#)

☐ `<video>` elements contain a `<track>` element with `[kind="captions"]`



When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#)

☐ Document has a main landmark.



One main landmark helps screen reader users navigate a web page. [Learn more about landmarks.](#)

☐ Tables use `<caption>` instead of cells with the `[colspan]` attribute to indicate a caption.



Screen readers have features to make navigating tables easier. Ensuring that tables use the actual caption element instead of cells with the `[colspan]` attribute may improve the experience for screen reader users. [Learn more about captions.](#)

Screen readers have features to make navigating tables easier. Ensuring that <td> elements in a large table (3 or more cells in width and height) have an associated table header may improve the experience for screen reader users. [Learn more about table headers.](#)



## Best Practices

### GENERAL

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more about this errors in console diagnostic audit](#)

Source	Description
127.0.0.1 <span>1st Party</span>	
progressbar.js:100	TypeError: Cannot read properties of null (reading 'addEventListener') at HTMLDocument.<anonymous> (http://127.0.0.1:5500/Shopping%20Website/assets/js/progressbar.js:100:43)
progressbar.js:28	TypeError: Cannot read properties of null (reading 'addEventListener') at HTMLDocument.<anonymous> (http://127.0.0.1:5500/Shopping%20Website/assets/js/progressbar.js:28:43)

### TRUST AND SAFETY

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS](#)

Description	Directive	Severity
No CSP found in enforcement mode		High



## Uses HTTPS



All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more about HTTPS](#).

## Avoids deprecated APIs



Deprecated APIs will eventually be removed from the browser. [Learn more about deprecated APIs](#).

## Avoids third-party cookies



Support for third-party cookies will be removed in a future version of Chrome. [Learn more about phasing out third-party cookies](#).

## Allows users to paste into input fields



Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. [Learn more about user-friendly input fields](#).

## Avoids requesting the geolocation permission on page load



Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. [Learn more about the geolocation permission](#).

## Avoids requesting the notification permission on page load



Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more about responsibly getting permission for notifications](#).

## Displays images with correct aspect ratio



Image display dimensions should match natural aspect ratio. [Learn more about image aspect ratio](#).

## Serves images with appropriate resolution



Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. [Learn how to provide responsive images](#).

## Page has the HTML doctype



Specifying a doctype prevents the browser from switching to quirks-mode. [Learn more about the doctype declaration](#).

## Properly defines charset



A character encoding declaration is required. It can be done with a <meta> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more about declaring the character encoding](#).

Avoids `unload` event listeners

The `unload` event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Use `pagehide` or `visibilitychange` events instead. [Learn more about unload event listeners](#)

No issues in the `Issues` panel in Chrome Devtools

Issues logged to the `Issues` panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the `Issues` panel in Chrome DevTools for more details on each issue.

Page has valid source maps

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps](#).

☒ Show 3rd-party resources (7)

URL	Map URL
Selenium IDE <div>Chrome Extension</div>	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/record.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/record.js.map
Error: Failed fetching source map (null)	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/polyfills.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/polyfills.js.map
Error: Failed fetching source map (null)	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/playback.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/playback.js.map
Error: Failed fetching source map (null)	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/escape.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/escape.js.map
Error: Failed fetching source map (null)	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/atoms.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/atoms.js.map
Error: Failed fetching source map (null)	

URL	Map URL
Unattributable	
chrome-extension://mmanaflgaempokjfbeeabkadnkoidjam/screenshots.js	chrome-extension://mmanaflgaempokjfbeeabkadnkoidjam/source maps/screenshot.bundle.map
Error: Failed fetching source map (null)	
JSDelivr CDN <span>Cdn</span>	
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	...intro.js@7.2.0/intro.js.map (cdn.jsdelivr.net)
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	...js/bootstrap.bundle.min.js.map (cdn.jsdelivr.net)

NOT APPLICABLE (2)

Hide

- Fonts with `font-display: optional` are preloaded



Preload optional fonts so first-time visitors may use them. [Learn more about preloading fonts](#)

- Detected JavaScript libraries



All front-end JavaScript libraries detected on the page. [Learn more about this JavaScript library detection diagnostic audit.](#)



## SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search Essentials](#).

### CONTENT BEST PRACTICES

- ▲ Document does not have a meta description



Meta descriptions may be included in search results to concisely summarize page content. [Learn more about the meta description](#).


Format your HTML in a way that enables crawlers to better understand your app's content.

▲ Links are not crawlable


^

Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. [Learn how to make links crawlable](#)


Uncrawlable Link



a.text-light



a.text-light



a.text-light



a.text-light

To appear in search results, crawlers need access to your app.

ADDITIONAL ITEMS TO MANUALLY CHECK (1)

Hide

☐ Structured data is valid

^

Run the [Structured Data Testing Tool](#) and the [Structured Data Linter](#) to validate structured data. [Learn more about Structured Data.](#)

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (8)

Hide

Has a `<meta name="viewport">` tag with `width` or `initial-scale`

^

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag.](#) TBT

Document has a `<title>` element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

Page has successful HTTP status code



Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more about HTTP status codes.](#)

Links have descriptive text



Descriptive link text helps search engines understand your content. [Learn how to make links more accessible.](#)

Page isn't blocked from indexing



Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more about crawler directives.](#)

Image elements have `[alt]` attributes



Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

Document has a valid `hreflang`



hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more about hreflang.](#)

Document avoids plugins



Search engines can't index plugin content, and many devices restrict plugins or don't support them. [Learn more about avoiding plugins.](#)

NOT APPLICABLE (4)

Hide

☐ robots.txt is valid



If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. [Learn more about robots.txt.](#)

☐ Document has a valid `rel=canonical`



Canonical links suggest which URL to show in search results. [Learn more about canonical links.](#)

☐ Document uses legible font sizes



Font sizes less than 12px are too small to be legible and require mobile visitors to “pinch to zoom” in order to read. Strive to have >60% of page text  $\geq 12$ px. [Learn more about legible font sizes.](#)

○ Tap targets are sized appropriately



Interactive elements like buttons and links should be large enough (48x48px), or have enough space around them, to be easy enough to tap without overlapping onto other elements. [Learn more about tap targets.](#)

Alongside [Chrome's updated Installability Criteria](#), Lighthouse will be deprecating the PWA category in a future release. Please refer to the [updated PWA documentation](#) for future PWA testing.



## PWA

These checks validate the aspects of a Progressive Web App. [Learn what makes a good Progressive Web App.](#)

### INSTALLABLE

▲ Web app manifest or service worker do not meet the installability requirements — 1 reason



Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. [Learn more about manifest installability requirements.](#)

Failure reason
Page has no manifest <link> URL

### PWA OPTIMIZED

▲ Is not configured for a custom splash screen Failures: No manifest was fetched.



A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. [Learn more about splash screens.](#)

▲ Does not set a theme color for the address bar.  
Failures: No manifest was fetched, No ``<meta name="theme-color">`` tag found.



The browser address bar can be themed to match your site. [Learn more about theming the address bar.](#)

☐ Content is sized correctly for the viewport ^

If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. [Learn how to size content for the viewport.](#)

Has a `<meta name="viewport">` tag with `width` or `initial-scale` ^

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag.](#) TBT

 Manifest doesn't have a maskable icon **No manifest was fetched** ^

A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. [Learn about maskable manifest icons.](#)

ADDITIONAL ITEMS TO MANUALLY CHECK (3) Hide

☐ Site works cross-browser ^

To reach the most number of users, sites should work across every major browser. [Learn about cross-browser compatibility.](#)

☐ Page transitions don't feel like they block on the network ^

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. [Learn more about page transitions.](#)

☐ Each page has a URL ^

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. [Learn more about providing deep links.](#)

These checks are required by the baseline [PWA Checklist](#) but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

Captured at Mar 27, 2024, 3:20  
PM GMT  
Initial page load

Emulated Desktop with  
Lighthouse 11.5.0  
Custom throttling

Single page session  
  
Using Chromium 123.0.0.0 with  
devtools