



Performance



Accessibility



Best Practices



SEO



PWA

There were issues affecting this run of Lighthouse:


- Chrome extensions negatively affected this page's load performance. Try auditing the page in incognito mode or from a Chrome profile without extensions.



Performance

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)

▲ 0–49 50–89 90–100



METRICS

Expand view

First Contentful Paint

0.5 s

▲ Largest Contentful Paint

3.8 s

Total Blocking Time

40 ms


Cumulative Layout Shift

0

Speed Index

1.3 s

[View Treemap](#)







Show audits relevant to: All [FCP](#) [LCP](#) [TBT](#) [CLS](#)

▲ Properly size images — Potential savings of 2,461 KiB

^

Serve images that are appropriately-sized to save cellular data and improve load time. [Learn how to size images.](#)

	URL	Resource Size	Potential Savings
127.0.0.1 1st Party		2,544.5 KiB	2,460.7 KiB
img.img-fluid	...images/IMG_5400.jpg (127.0.0.1)	2,131.6 KiB	2,107.9 KiB
<div>img-fluid</div>	...portfolio/portfolio-2.jpg (127.0.0.1)	143.5 KiB	133.1 KiB
<div>img-fluid</div>	...portfolio/portfolio-7.jpg (127.0.0.1)	94.3 KiB	86.2 KiB
<div>img-fluid</div>	...portfolio/portfolio-8.jpg (127.0.0.1)	29.1 KiB	23.5 KiB
<div>img-fluid</div>	...portfolio/portfolio-9.jpg (127.0.0.1)	22.9 KiB	21.1 KiB
<div>img-fluid</div>	...portfolio/portfolio-1.jpg (127.0.0.1)	24.7 KiB	20.8 KiB
<div>img-fluid</div>	...portfolio/portfolio-3.jpg (127.0.0.1)	18.7 KiB	15.1 KiB

	URL	Resource Size	Potential Savings
g-fluid	m		
	i m g- i m ...portfolio/portfolio-4.jpg (127.0.0.1)	17.5 KiB	14.1 KiB
g-fluid			
	i m g- i m ...portfolio/portfolio-6.jpg (127.0.0.1)	21.3 KiB	13.5 KiB
g-fluid			
	i m g- i m ...portfolio/portfolio-5.jpg (127.0.0.1)	21.0 KiB	13.4 KiB
g-fluid			
	i m g ...images/accessibility.jpg (127.0.0.1)	19.8 KiB	12.1 KiB


▲ Largest Contentful Paint element — 3,750 ms



This is the largest contentful element painted within the viewport. [Learn more about the Largest Contentful Paint element](#)

LCP

Element



div.position-relative.overflow-hidden.p-3.p-md-5.m-md-3.text-center.student-shopping

Phase	% of LCP	Timing
TTFB	3%	130 ms

Phase	% of LCP	Timing
Load Delay	26%	960 ms
Load Time	4%	160 ms
Render Delay	67%	2,500 ms

▲ Serve images in next-gen formats — Potential savings of 1,055 KiB



Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. [Learn more about modern image formats.](#)

	URL	Resource Size	Potential Savings
127.0.0.1 1st Party		4,015.0 KiB	1,055.3 KiB
<div> <div></div> <div>div.position - relative.ov erflow- hidden.p-</div> </div> <div>3.p-md-5.m-md-3.text-center.student-shopping</div>	...images/john-schn....jpg (127.0.0.1)	1,547.6 KiB	733.8 KiB
img.img-fluid	...images/IMG_5400.jpg (127.0.0.1)	2,131.6 KiB	147.1 KiB
<div> <div></div> <div>img.i mg- fluid</div> </div> <div>...</div>	...portfolio/portfolio-2.jpg (127.0.0.1)	143.5 KiB	73.4 KiB
<div> <div></div> <div>img.i mg- fluid</div> </div> <div>...</div>	...portfolio/portfolio-7.jpg (127.0.0.1)	94.3 KiB	58.9 KiB
<div> <div></div> <div>img.i mg- fluid</div> </div> <div>...</div>	...portfolio/portfolio-8.jpg (127.0.0.1)	29.1 KiB	11.3 KiB
<div> <div></div> <div>img.i mg- fluid</div> </div> <div>...</div>	...portfolio/portfolio-1.jpg (127.0.0.1)	24.7 KiB	11.0 KiB

URL		Resource Size	Potential Savings
	img.img-fluid ...portfolio/portfolio-6.jpg (127.0.0.1)	21.3 KiB	10.7 KiB
	img.img-fluid ...portfolio/portfolio-9.jpg (127.0.0.1)	22.9 KiB	8.9 KiB

▲ Enable text compression — Potential savings of 40 KiB



Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. [Learn more about text compression.](#) FCP LCP

URL	Transfer Size	Potential Savings
127.0.0.1 1st Party	55.3 KiB	39.6 KiB
...pages/Homepage.html (127.0.0.1)	37.9 KiB	27.6 KiB
...css/Main.css (127.0.0.1)	12.8 KiB	8.8 KiB
...js/Main.js (127.0.0.1)	4.5 KiB	3.1 KiB

▲ Efficiently encode images — Potential savings of 19 KiB



Optimized images load faster and consume less cellular data. [Learn how to efficiently encode images.](#)

	URL	Resource Size	Potential Savings
127.0.0.1 1st Party		1,641.9 KiB	19.3 KiB
<div><div></div><div>div.position-relative.overflow-hidden.p-3.p-md-5.m-md-3.text-center.student-shopping</div></div>	...images/john-schn....jpg (127.0.0.1)	1,547.6 KiB	12.6 KiB
<div><div></div><div>img.img-fluid</div></div>	...portfolio/portfolio-7.jpg (127.0.0.1)	94.3 KiB	6.7 KiB

URL	Resource Size	Potential Savings

▲ Reduce unused CSS — Potential savings of 30 KiB

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. [Learn how to reduce unused CSS.](#) FCP LCP

URL	Transfer Size	Potential Savings
JSDelivr CDN Cdn	34.1 KiB	30.5 KiB
...css/bootstrap.min.css (cdn.jsdelivr.net)	34.1 KiB	30.5 KiB

▲ Eliminate render-blocking resources — Potential savings of 260 ms

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. [Learn how to eliminate render-blocking resources.](#) FCP LCP

☒ Show 3rd-party resources (3)

URL	Transfer Size	Potential Savings
JSDelivr CDN Cdn	36.6 KiB	730 ms
...css/bootstrap.min.css (cdn.jsdelivr.net)	34.4 KiB	300 ms
...css/bootstrap-icons.css (cdn.jsdelivr.net)	0.0 KiB	210 ms
...minified/introjs.min.css (cdn.jsdelivr.net)	2.2 KiB	210 ms
127.0.0.1 1st Party	13.2 KiB	90 ms
...css/Main.css (127.0.0.1)	13.2 KiB	90 ms

▲ Page prevented back/forward cache restoration — 1 failure reason

Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. [Learn more about the bfcache](#)

Failure reason	Failure type
Pages with WebSocket cannot enter back/forward cache. ...pages/Homepage.html (127.0.0.1)	Pending browser support

Preload Largest Contentful Paint image — Potential savings of 10 ms



If the LCP element is dynamically added to the page, you should preload the image in order to improve LCP. [Learn more about preloading LCP elements.](#) LCP





	URL	Potential Savings
127.0.0.1 1st Party		10 ms
 <div>div.position- relative.overflow-hidden.p- 3.p-md-5.m-md-3.text- center.student-shopping</div>	...images/john-schn....jpg (127.0.0.1)	10 ms


Image elements do not have explicit `width` and `height`



Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn how to set image dimensions](#) CLS


	URL
127.0.0.1 1st Party	
img.img-fluid	...images/IMG_5400.jpg (127.0.0.1)
 <div>img.img-fluid</div>	...portfolio/portfolio-2.jpg (127.0.0.1)
 <div>img.img-fluid</div>	...portfolio/portfolio-9.jpg (127.0.0.1)
 <div>img.img-fluid</div>	...portfolio/portfolio-7.jpg (127.0.0.1)

URL




img.img-fluid

...portfolio/portfolio-1.jpg (127.0.0.1)




img.img-fluid

...portfolio/portfolio-5.jpg (127.0.0.1)




img.img-fluid

...portfolio/portfolio-6.jpg (127.0.0.1)




img.img-fluid

...portfolio/portfolio-8.jpg (127.0.0.1)



img.img-fluid

...portfolio/portfolio-4.jpg (127.0.0.1)



img.img-fluid

...portfolio/portfolio-3.jpg (127.0.0.1)

img.img-fluid

...images/OIP%20(1).jpg (127.0.0.1)

Minify CSS — Potential savings of 7 KiB



Minifying CSS files can reduce network payload sizes. [Learn how to minify CSS.](#) FCP LCP

URL	Transfer Size	Potential Savings
127.0.0.1 1st Party	13.2 KiB	6.8 KiB

URL	Transfer Size	Potential Savings
...css/Main.css (127.0.0.1)	13.2 KiB	6.8 KiB

Minify JavaScript — Potential savings of 28 KiB



Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript.](#) FCP LCP


☒ Show 3rd-party resources (1)

URL	Transfer Size	Potential Savings
Unattributable	54.0 KiB	24.9 KiB
chrome-extension://dmghijelimhndkbmpgbldicpogfkceaj/data/content_script/resources/native.js	20.4 KiB	9.7 KiB
chrome-extension://cjpahdlnbpafiamejdnhcphjbkeiagm/js/contentscript.js	14.7 KiB	7.8 KiB
chrome-extension://dmghijelimhndkbmpgbldicpogfkceaj/data/content_script/vendor/tinycolor.js	11.8 KiB	5.2 KiB
chrome-extension://dmghijelimhndkbmpgbldicpogfkceaj/data/content_script/inject.js	7.1 KiB	2.3 KiB
Selenium IDE Chrome Extension	7.1 KiB	2.8 KiB
chrome-extension://mooikfahbdckldjndioackbalphokd/assets/prompt.js	7.1 KiB	2.8 KiB

Defer offscreen images — Potential savings of 28 KiB



Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. [Learn how to defer offscreen images.](#)

URL	Resource Size	Potential Savings
127.0.0.1 1st Party	28.1 KiB	28.1 KiB
 img .im g- fluid	...images/OIP%20(2).jpg (127.0.0.1)	28.1 KiB



Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. [Learn how to use modern JavaScript](#) TBT

☐ Show 3rd-party resources (1)

URL	Potential Savings
Unattributable	14.0 KiB
chrome-extension://mmanafлгаempokjfbbeeabkadnkoidjam/screenshot.js	14.0 KiB
screenshot.js:1	Array.prototype.fill
screenshot.js:1	Array.prototype.filter
screenshot.js:1	Array.prototype.find
screenshot.js:1	Array.from
screenshot.js:1	Array.prototype.map
screenshot.js:1	Object.entries
screenshot.js:1	Object.keys
screenshot.js:1	@babel/plugin-transform-classes
screenshot.js:1	String.fromCodePoint
JSDelivr CDN Cdn	0.0 KiB
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	0.0 KiB
intro.min.js:16	@babel/plugin-transform-classes



Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn how to reduce unused JavaScript](#). LCP

☒ Show 3rd-party resources (2)

URL	Transfer Size	Potential Savings
Unattributable	438.2 KiB	279.6 KiB
chrome-extension://mmanafлгаempokjfbbeeabkadnkoidjam/screenshot.js	372.6 KiB	225.7 KiB

URL	Transfer Size	Potential Savings
chrome-extension://fmkadmapgofadopljbjfkapdkoienihi/build/renderer.js	37.7 KiB	33.2 KiB
chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/libs/jquery-3.1.1.min.js	27.9 KiB	20.6 KiB
Selenium IDE Chrome Extension	191.4 KiB	117.9 KiB
chrome-extension://mooikfahbdckldjjndioackbalphokd/assets/atoms.js	159.9 KiB	91.4 KiB
chrome-extension://mooikfahbdckldjjndioackbalphokd/assets/playback.js	31.5 KiB	26.5 KiB

Avoid enormous network payloads — Total size was 4,315 KiB



Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes](#). LCP

☒ Show 3rd-party resources (2)

URL	Transfer Size
127.0.0.1 1st Party	4,042.6 KiB
...images/IMG_5400.jpg (127.0.0.1)	2,131.9 KiB
...images/john-schn....jpg (127.0.0.1)	1,547.9 KiB
...portfolio/portfolio-2.jpg (127.0.0.1)	143.9 KiB
...portfolio/portfolio-7.jpg (127.0.0.1)	94.6 KiB
...pages/Homepage.html (127.0.0.1)	38.2 KiB
...portfolio/portfolio-8.jpg (127.0.0.1)	29.4 KiB
...images/OIP%20(2).jpg (127.0.0.1)	28.4 KiB
...images/OIP%20(1).jpg (127.0.0.1)	28.2 KiB
JSDelivr CDN Cdn	34.4 KiB
...css/bootstrap.min.css (cdn.jsdelivr.net)	34.4 KiB
jQuery CDN Cdn	30.3 KiB
/jquery-3.6.0.min.js (code.jquery.com)	30.3 KiB



Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to reduce Javascript execution time](#). TBT

☒ Show 3rd-party resources (1)

URL	Total CPU Time	Script Evaluation	Script Parse
Unattributable	250 ms	133 ms	61 ms
chrome-extension://mmanafлгаempokjfbeeabkadmoidjam/screenshot.js	196 ms	130 ms	61 ms
Unattributable	54 ms	3 ms	0 ms
127.0.0.1 1st Party	247 ms	46 ms	16 ms
...pages/Homepage.html (127.0.0.1)	247 ms	46 ms	16 ms
JSDelivr CDN Cdn	77 ms	2 ms	1 ms
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	77 ms	2 ms	1 ms



Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#). TBT

Category	Time Spent
Script Evaluation	276 ms
Other	201 ms
Script Parsing & Compilation	103 ms
Style & Layout	94 ms
Rendering	27 ms
Parse HTML & CSS	27 ms
Garbage Collection	3 ms



Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#) TBT

☒ Show 3rd-party resources (3)

URL	Start Time	Duration
Unattributable		195 ms
chrome-extension://mmanaflgaempokjfbbeeabkadnkoidjam/screenshot.js	353 ms	195 ms
JSDelivr CDN Cdn		116 ms
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	3,812 ms	61 ms
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	700 ms	55 ms
127.0.0.1 1st Party		115 ms
...pages/Homepage.html (127.0.0.1)	277 ms	62 ms
...pages/Homepage.html (127.0.0.1)	222 ms	53 ms
Selenium IDE Chrome Extension		89 ms
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/vendor/global.js	561 ms	89 ms

User Timing marks and measures — 1 user timing

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. [Learn more about User Timing marks](#).

Name	Type	Start Time	Duration
__v3	Mark	0.00 ms	

Initial server response time was short — Root document took 0 ms

Keep the server response time for the main document short because all other requests depend on it. [Learn more about the Time to First Byte metric](#). FCP LCP

URL	Time Spent
127.0.0.1 1st Party	0 ms
...pages/Homepage.html (127.0.0.1)	0 ms

○ Avoids an excessive DOM size — 289 elements



A large DOM will increase memory usage, cause longer [style calculations](#), and produce costly [layout reflows](#). [Learn how to avoid an excessive DOM size](#). TBT

Statistic	Element	Value
Total DOM Elements		289
Maximum DOM Depth	 path	10
Maximum Child Elements	 ul	25

○ Avoid chaining critical requests — 8 chains found



The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. [Learn how to avoid chaining critical requests](#). FCP LCP

Maximum critical path latency: **116.348 ms**

Initial Navigation

...pages/Homepage.html (127.0.0.1)

- ...css/bootstrap.min.css (cdn.jsdelivr.net) - **18.616 ms, 34.40 KiB**
- ...css/Main.css (127.0.0.1) - **7.149 ms, 13.17 KiB**
- ...css/bootstrap-icons.css (cdn.jsdelivr.net) - **89.281 ms, 0.00 KiB**
- ...minified/introjs.min.css (cdn.jsdelivr.net) - **15.922 ms, 2.22 KiB**
- ...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) - **24.045 ms, 24.91 KiB**
- /jquery-3.6.0.min.js (code.jquery.com) - **38.907 ms, 30.26 KiB**
- ...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net) - **37.862 ms, 14.03 KiB**
- ...js/Main.js (127.0.0.1) - **21.717 ms, 4.90 KiB**

○ Minimize third-party usage — Third-party code blocked the main thread for 0 ms



Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. [Learn how to minimize third-party impact](#). TBT

Third-Party	Transfer Size	Main-Thread Blocking Time
JSDelivr CDN Cdn	76 KiB	0 ms
...css/bootstrap.min.css (cdn.jsdelivr.net)	34 KiB	0 ms
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	25 KiB	0 ms
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	14 KiB	0 ms
...minified/introjs.min.css (cdn.jsdelivr.net)	2 KiB	0 ms
...css/bootstrap-icons.css (cdn.jsdelivr.net)	0 KiB	0 ms
jQuery CDN Cdn	30 KiB	0 ms
/jquery-3.6.0.min.js (code.jquery.com)	30 KiB	0 ms
Selenium IDE Chrome Extension	7 KiB	0 ms
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/prompt.js	7 KiB	0 ms

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

PASSED AUDITS (15)

Hide

Preconnect to required origins	^
Consider adding preconnect or dns-prefetch resource hints to establish early connections to important third-party origins. Learn how to preconnect to required origins. FCP LCP	
Avoid multiple page redirects	^
Redirects introduce additional delays before the page can be loaded. Learn how to avoid page redirects. FCP LCP	
<input type="radio"/> Preload key requests	^
Consider using <link rel=preload> to prioritize fetching resources that are currently requested later in page load. Learn how to preload key requests. FCP LCP	
Use HTTP/2	^
HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Learn more about HTTP/2.	
Use video formats for animated content	^
Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. Learn more about efficient video formats LCP	
Remove duplicate modules in JavaScript bundles	^

Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity.

TBT

Uses efficient cache policy on static assets — 0 resources found

A long cache lifetime can speed up repeat visits to your page. [Learn more about efficient cache policies.](#)

All text remains visible during webfont loads

Leverage the `font-display` CSS feature to ensure text is user-visible while webfonts are loading. [Learn more about font-display.](#) FCP LCP


○ Lazy load third-party resources with facades

Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are required. [Learn how to defer third-parties with a facade.](#) TBT

Largest Contentful Paint image was not lazily loaded

Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the largest contentful paint. [Learn more about optimal lazy loading.](#) LCP

Element



div.position-relative.overflow-hidden.p-3.p-md-5.m-md-3.text-center.student-shopping

○ Avoid large layout shifts

These are the largest layout shifts observed on the page. Each table item represents a single layout shift, and shows the element that shifted the most. Below each item are possible root causes that led to the layout shift. Some of these layout shifts may not be included in the CLS metric value due to [windowing](#). [Learn how to improve CLS](#) CLS

Uses passive listeners to improve scrolling performance

Consider marking your touch and wheel event listeners as passive to improve your page's scroll performance. [Learn more about adopting passive event listeners.](#)

Avoids `document.write()`

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. [Learn how to avoid document.write\(\)](#).

○ Avoid non-composited animations

Animations which are not composited can be janky and increase CLS. [Learn how to avoid non-composited animations](#) CLS

Has a `<meta name="viewport">` tag with `width` or `initial-scale` ^

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag](#). TBT



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

ARIA

▲ Elements with an ARIA `[role]` that require children to contain a specific `[role]` are missing some or all of those required children. ^

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements](#).

Failing Elements

ul

a.active

a

a


▲ `button`, `link`, and `menuitem` elements do not have accessible names. ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to make command elements more accessible](#).


Failing Elements




a.active




a




a




a




a




a



a



a



a

Failing Elements

a

a

a

a

a


a

a


a

a


Failing Elements




a




a




a




a



a



a



a

▲ Elements with `role="dialog"` or `role="alertdialog"` do not have accessible names.



ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. [Learn how to make ARIA dialog elements more accessible.](#)

Failing Elements




div.introjs-tooltip.introjs-bottom-left-aligned

ARIA IDs are unique



The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. [Learn how to fix duplicate ARIA IDs.](#)

Failing Elements



div#collapseOne.accordion-collapse.collapse.show



div#collapseOne.accordion-collapse.collapse.show

These are opportunities to improve the usage of ARIA in your application which may enhance the experience for users of assistive technology, like a screen reader.


NAMES AND LABELS

Buttons do not have an accessible name




When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. [Learn how to make buttons more accessible.](#)

Failing Elements







button.btn.btn-outline-success



button#readScreenButton.btn.btn-secondary

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn how to make links accessible.](#)

Failing Elements



	a.text-light
	a.text-light
	a.text-light
	a.text-light

These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

CONTRAST

Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast.](#)

Failing Elements

	p
	body

Failing Elements

p



body



p



body



p



body



p



body



p



body



p



body



Failing Elements



p




body



p



body



a



footer.py-3.my-4.text-center

These are opportunities to improve the legibility of your content.

NAVIGATION


▲ Heading elements are not in a sequentially-descending order



Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

Failing Elements

h5




h4



h5

Failing Elements



These are opportunities to improve keyboard navigation in your application.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

☐ Interactive controls are keyboard focusable



Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable.](#)

☐ Interactive elements indicate their purpose and state



Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints.](#)

☐ The page has a logical tab order



Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering.](#)

☐ Visual order on the page follows DOM order



DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering.](#)

☐ User focus is not accidentally trapped in a region



A user can tab into and out of any control or region without accidentally trapping their focus. [Learn how to avoid focus traps.](#)

☐ The user's focus is directed to new content added to the page



If new content, such as a dialog, is added to the page, the user's focus is directed to it. [Learn how to direct focus to new content.](#)

☐ HTML5 landmark elements are used to improve navigation



Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. [Learn more about landmark elements.](#)

☐ Offscreen content is hidden from assistive technology



Offscreen content is hidden with display: none or aria-hidden=true. [Learn how to properly hide offscreen content.](#)

☐ Custom controls have associated labels ^

Custom interactive controls have associated labels, provided by `aria-label` or `aria-labelledby`. [Learn more about custom controls and labels.](#)

☐ Custom controls have ARIA roles ^

Custom interactive controls have appropriate ARIA roles. [Learn how to add roles to custom controls.](#)

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review](#).

PASSED AUDITS (20) Hide

`[aria-*]` attributes match their roles ^

Each ARIA role supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. [Learn how to match ARIA attributes to their roles.](#)

`[aria-hidden="true"]` is not present on the document `<body>` ^

Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. [Learn how `aria-hidden` affects the document body.](#)

`[role]`s have all required `[aria-*]` attributes ^

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#)

`[aria-*]` attributes have valid values ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. [Learn more about valid values for ARIA attributes.](#)

`[aria-*]` attributes are valid and not misspelled ^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. [Learn more about valid ARIA attributes.](#)

Image elements have `[alt]` attributes ^

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty `alt` attribute. [Learn more about the `alt` attribute.](#)

`[user-scalable="no"]` is not used in the `<meta name="viewport">` element and the `[maximum-scale]` attribute is not less than 5. ^

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more about the viewport meta tag.](#)

`[aria-hidden="true"]` elements do not contain focusable descendents



Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how aria-hidden affects focusable elements.](#)

`[role]` values are valid



ARIA roles must have valid values in order to perform their intended accessibility functions. [Learn more about valid ARIA roles.](#)

Document has a `<title>` element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles.](#)

`[id]` attributes on active, focusable elements are unique



All focusable elements must have a unique `id` to ensure that they're visible to assistive technologies. [Learn how to fix duplicate ids.](#)

`<html>` element has a `[lang]` attribute



If a page doesn't specify a `lang` attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#)

`<html>` element has a valid value for its `[lang]` attribute



Specifying a valid [BCP 47 language](#) helps screen readers announce text properly. [Learn how to use the lang attribute.](#)

Form elements have associated labels



Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more about form element labels.](#)

Links are distinguishable without relying on color.



Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#)

Lists contain only `` elements and script supporting elements (`<script>` and `<template>`).



Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#)

List items (``) are contained within ``, `` or `<menu>` parent elements



Screen readers require list items (``) to be contained within a parent ``, `` or `<menu>` to be announced properly. [Learn more about proper list structure.](#)

No element has a `[tabindex]` value greater than 0



A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. [Learn more about the `tabindex` attribute.](#)

Values assigned to `role=""` are valid ARIA roles.



ARIA roles enable assistive technologies to know the role of each element on the web page. If the `role` values are misspelled, not existing ARIA role values, or abstract roles, then the purpose of the element will not be communicated to users of assistive technologies. [Learn more about ARIA roles.](#)

Image elements do not have `[alt]` attributes that are redundant text.



Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the `alt` attribute.](#)

NOT APPLICABLE (31)

Hide

☐ `[accesskey]` values are unique



Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more about access keys.](#)

☐ ARIA input fields have accessible names



When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels.](#)

☐ ARIA `meter` elements have accessible names



When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#)

☐ ARIA `progressbar` elements have accessible names



When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#)

☐ `[role]`s are contained by their required parent element



Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions.

[Learn more about ARIA roles and required parent element.](#)

- Elements with the `role=text` attribute do not have focusable descendents. ^

Adding `role=text` around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. [Learn more about the `role=text` attribute.](#)

- ARIA toggle fields have accessible names ^

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about toggle fields.](#)

- ARIA `tooltip` elements have accessible names ^

When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name tooltip elements.](#)

- ARIA `treeitem` elements have accessible names ^

When a `treeitem` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about labeling `treeitem` elements.](#)

- The page contains a heading, skip link, or landmark region ^

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. [Learn more about bypass blocks.](#)

- `<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements. ^

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. [Learn how to structure definition lists correctly.](#)

- Definition list items are wrapped in `<dl>` elements ^

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. [Learn how to structure definition lists correctly.](#)

- No form fields have multiple labels ^

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. [Learn how to use form labels.](#)

- `<frame>` or `<iframe>` elements have a title ^

Screen reader users rely on frame titles to describe the contents of frames. [Learn more about frame titles.](#)

- `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute. ^

If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. [Learn more about the lang attribute.](#)

- Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#)

- `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#)

- The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#)

- `<object>` elements have alternate text ^

Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#)

- Select elements have associated label elements. ^

Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element.](#)

- Skip links are focusable. ^

Including a skip link can help users skip to the main content to save time. [Learn more about skip links.](#)

- Tables have different content in the summary attribute and `<caption>`. ^

The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#)

- Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table. ^

Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. [Learn more about the headers attribute.](#)

- `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe. ^

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. [Learn more about table headers.](#)

- `[lang]` attributes have a valid value



Specifying a valid [BCP 47 language](#) on elements helps ensure that text is pronounced correctly by a screen reader. [Learn how to use the `lang` attribute.](#)

- `<video>` elements contain a `<track>` element with `[kind="captions"]`



When a video provides a caption it is easier for deaf and hearing impaired users to access its information. [Learn more about video captions.](#)

- Identical links have the same purpose.



Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. [Learn more about identical links.](#)

- Document has a main landmark.



One main landmark helps screen reader users navigate a web page. [Learn more about landmarks.](#)

- Elements with visible text labels have matching accessible names.



Visible text labels that do not match the accessible name can result in a confusing experience for screen reader users. [Learn more about accessible names.](#)

- Tables use `<caption>` instead of cells with the `[colspan]` attribute to indicate a caption.



Screen readers have features to make navigating tables easier. Ensuring that tables use the actual caption element instead of cells with the `[colspan]` attribute may improve the experience for screen reader users. [Learn more about captions.](#)

- `<td>` elements in a large `<table>` have one or more table headers.



Screen readers have features to make navigating tables easier. Ensuring that `<td>` elements in a large table (3 or more cells in width and height) have an associated table header may improve the experience for screen reader users. [Learn more about table headers.](#)



Best Practices

GENERAL

- ▲ Browser errors were logged to the console



Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser

concerns. [Learn more about this errors in console diagnostic audit](#)

Source	Description
127.0.0.1 1st Party	
Main.js:118	TypeError: \$(...).carousel is not a function at http://127.0.0.1:5500/Shopping%20Website/assets/js/Main.js:118:16

Detected JavaScript libraries

All front-end JavaScript libraries detected on the page. [Learn more about this JavaScript library detection diagnostic audit.](#)

Name	Version
Bootstrap	5.3.2
jQuery	3.6.0

TRUST AND SAFETY

Ensure CSP is effective against XSS attacks

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS](#)

Description	Directive	Severity
No CSP found in enforcement mode		High

PASSED AUDITS (13) Hide

Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more about HTTPS.](#)

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. [Learn more about deprecated APIs.](#)

Avoids third-party cookies

Support for third-party cookies will be removed in a future version of Chrome. [Learn more about phasing out third-party cookies.](#)

Allows users to paste into input fields



Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. [Learn more about user-friendly input fields.](#)

Avoids requesting the geolocation permission on page load



Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. [Learn more about the geolocation permission.](#)

Avoids requesting the notification permission on page load



Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. [Learn more about responsibly getting permission for notifications.](#)

Displays images with correct aspect ratio



Image display dimensions should match natural aspect ratio. [Learn more about image aspect ratio.](#)

Serves images with appropriate resolution



Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. [Learn how to provide responsive images.](#)

Page has the HTML doctype



Specifying a doctype prevents the browser from switching to quirks-mode. [Learn more about the doctype declaration.](#)

Properly defines charset



A character encoding declaration is required. It can be done with a <meta> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. [Learn more about declaring the character encoding.](#)

Avoids `unload` event listeners



The unload event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Use `pagehide` or `visibilitychange` events instead. [Learn more about unload event listeners](#)

No issues in the `Issues` panel in Chrome Devtools



Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Page has valid source maps



Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps.](#)

☒ Show 3rd-party resources (7)

URL	Map URL
Selenium IDE <div>Chrome Extension</div>	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/record.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/record.js.map
Error: Failed fetching source map (null)	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/polyfills.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/polyfills.js.map
Error: Failed fetching source map (null)	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/playback.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/playback.js.map
Error: Failed fetching source map (null)	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/escape.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/escape.js.map
Error: Failed fetching source map (null)	
chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/atoms.js	chrome-extension://mooikfkahbdckldjjndioackbalphokd/assets/atoms.js.map
Error: Failed fetching source map (null)	
Unattributable	
chrome-extension://mmanafлгаempokjfbeeabkadnkoidjam/screenshots.js	chrome-extension://mmanafлгаempokjfbeeabkadnkoidjam/source maps/screenshot.bundle.map
Error: Failed fetching source map (null)	
JSDelivr CDN <div>Cdn</div>	
...intro.js@7.2.0/intro.min.js (cdn.jsdelivr.net)	...intro.js@7.2.0/intro.js.map (cdn.jsdelivr.net)
...js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	...js/bootstrap.bundle.min.js.map (cdn.jsdelivr.net)

- ☐ Fonts with `font-display: optional` are preloaded




Preload optional fonts so first-time visitors may use them. [Learn more about preloading fonts](#)



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on [Core Web Vitals](#). [Learn more about Google Search Essentials](#).

CONTENT BEST PRACTICES

-  Document does not have a meta description



Meta descriptions may be included in search results to concisely summarize page content. [Learn more about the meta description](#).

Format your HTML in a way that enables crawlers to better understand your app's content.

ADDITIONAL ITEMS TO MANUALLY CHECK (1)

- ☐ Structured data is valid



Run the [Structured Data Testing Tool](#) and the [Structured Data Linter](#) to validate structured data. [Learn more about Structured Data](#).

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (9)

Has a `<meta name="viewport">` tag with `width` or `initial-scale`



A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag](#). TBT

Document has a `<title>` element



The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. [Learn more about document titles](#).

Page has successful HTTP status code



Pages with unsuccessful HTTP status codes may not be indexed properly. [Learn more about HTTP status codes.](#)

Links have descriptive text



Descriptive link text helps search engines understand your content. [Learn how to make links more accessible.](#)

Links are crawlable



Search engines may use href attributes on links to crawl websites. Ensure that the href attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. [Learn how to make links crawlable](#)

Page isn't blocked from indexing



Search engines are unable to include your pages in search results if they don't have permission to crawl them. [Learn more about crawler directives.](#)

Image elements have [alt] attributes



Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. [Learn more about the alt attribute.](#)

Document has a valid hreflang



hreflang links tell search engines what version of a page they should list in search results for a given language or region. [Learn more about hreflang.](#)

Document avoids plugins



Search engines can't index plugin content, and many devices restrict plugins or don't support them. [Learn more about avoiding plugins.](#)

NOT APPLICABLE (4)

Hide

☐ robots.txt is valid



If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. [Learn more about robots.txt.](#)

☐ Document has a valid rel=canonical



Canonical links suggest which URL to show in search results. [Learn more about canonical links.](#)

☐ Document uses legible font sizes



Font sizes less than 12px are too small to be legible and require mobile visitors to “pinch to zoom” in order to read. Strive to have >60% of page text ≥ 12 px. [Learn more about legible font sizes.](#)

○ Tap targets are sized appropriately ^

Interactive elements like buttons and links should be large enough (48x48px), or have enough space around them, to be easy enough to tap without overlapping onto other elements. [Learn more about tap targets.](#)

Alongside [Chrome's updated Installability Criteria](#), Lighthouse will be deprecating the PWA category in a future release. Please refer to the [updated PWA documentation](#) for future PWA testing.



PWA

These checks validate the aspects of a Progressive Web App. [Learn what makes a good Progressive Web App.](#)

INSTALLABLE

▲ Web app manifest or service worker do not meet the installability requirements — 1 reason ^

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. [Learn more about manifest installability requirements.](#)

Failure reason
Page has no manifest <link> URL

PWA OPTIMIZED

▲ Is not configured for a custom splash screen Failures: No manifest was fetched. ^

A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. [Learn more about splash screens.](#)

▲ Does not set a theme color for the address bar.
Failures: No manifest was fetched, No `^

The browser address bar can be themed to match your site. [Learn more about theming the address bar.](#)

☐ Content is sized correctly for the viewport ^

If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. [Learn how to size content for the viewport.](#)

Has a `<meta name="viewport">` tag with `width` or `initial-scale` ^

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents [a 300 millisecond delay to user input](#). [Learn more about using the viewport meta tag.](#) TBT

 Manifest doesn't have a maskable icon **No manifest was fetched** ^

A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. [Learn about maskable manifest icons.](#)

ADDITIONAL ITEMS TO MANUALLY CHECK (3) Hide

☐ Site works cross-browser ^

To reach the most number of users, sites should work across every major browser. [Learn about cross-browser compatibility.](#)

☐ Page transitions don't feel like they block on the network ^

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. [Learn more about page transitions.](#)

☐ Each page has a URL ^

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. [Learn more about providing deep links.](#)

These checks are required by the baseline [PWA Checklist](#) but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

Captured at Mar 27, 2024,
11:43 AM GMT
Initial page load

Emulated Desktop with
Lighthouse 11.5.0
Custom throttling

Single page session

Using Chromium 123.0.0.0 with
devtools