

Permanent Magnet Alternating Current Motor Controller

Alex Simon

February 3, 2019

Abstract

This document explores the design decisions for a Permanent Magnet Alternating Current (PMAC) motor controller. Specifically, the hardware component design choices and the commutation techniques used within the project.

1 Introduction

This paper will explore the process of designing a PMAC motor controller and the difficulties discovered along the way. Beginning with the printed circuit board (PCB) design stage, each of the major components used in the PCB will be evaluated. Once the PCB has been designed two different commutation techniques will be explored. Trapezoidal commutation will be evaluated first to validate the hardware design because it is less complex than Field Oriented Control (FOC). Field Oriented Control will be evaluated last because the software complexity introduces a lot of area for error, but the hardware will already be validated from trapezoidal control. The advantage of this order allows one problem to be solved at a time; hardware then control strategy.

2 Hardware Design

The hardware is divided into two sections: the power and control stage. Each stage is designed on a separate PCBs to minimize cost and for ease of testing. This modular design also allows for each stage to be tested independently of the other and eventually costs less because fewer components will need to be replaced when something goes wrong.

2.1 Metal-Oxide-Semiconductor Field-Effect Transistor (MOSFET)

To evaluate the advantages and disadvantages of each MOSFET a power calculation can be done. The power consumed by a MOSFET can be estimated using Equations 1, 2, 3, and 4.

$$P_{Total} = P_{On} + P_{Off} + P_{Sw} \quad (1)$$

$$P_{On} = (I_{Continuous})^2 * R_{ds(on)} * DutyCycle \quad (2)$$

$$P_{Off} = (1 - DutyCycle) * V_{Off} * I_{Leakage} \quad (3)$$

$$P_{Sw} = \frac{V_{Off} * I_{Continuous} * (T_{Rise} + T_{Fall}) * F_{Sw}}{2} \quad (4)$$

Using the given parameters for each MOSFET and Equations 1, 2, 3, and 4 it becomes easier to compare each MOSFET. For this project 8 different MOSFETs were chosen for evaluation. As shown in Table 2.1, Infineons BSC016N06 consumes the least power, but due to the rated voltage, rated current and solderability Infineons IPB017N10N5 was chosen instead.

MOSFET	P_{On}	P_{Off}	P_{Sw}	P_{Total}
BSC047N08NS3	0.94	24μ	0.1344	1.07
CSD18540Q5B	0.44	24μ	0.0576	0.50
BSC014N06NS	0.29	24μ	0.1008	0.39
BSC016N06NS	0.32	24μ	0.0864	0.41
IPT012N08N5	0.24	2μ	0.2928	0.53
CSD18531Q5A	0.70	24μ	0.0504	0.75
IPB017N10N5	0.34	24μ	0.2400	0.58
IPB044N15N5	0.88	24μ	0.0528	0.93

Table 1: Power Consumption for each MOSFET assuming: $V_{Off} = 48v$, $f_{Sw} = 10kHz$, $I_{Continuous} = 20$, $DutyCycle = 50\%$. Note: Equation 4 uses rectangular commutation to estimate P_{Sw} .

2.2 Gate Driver

A MOSFET is only as good as the gate driver behind it. If the gate driver has slow rise and fall times, the MOSFET will have slow rise and fall times regardless of its own rise and fall times. In addition if the driver does not provide enough current fast the gate of the MOSFET will have slow rise and fall times, again regardless of its own rise and fall times. When choosing the gate driver a voltage rating of $150v \geq V_{rated} \geq 100v$ was desired. The 150v upper bound is for monetary and complexity reasons while the 100v lower bound is needed to withstand voltage transients.

After the voltage rating rise and fall times of the gate driver are most important. The goal is to have faster rise and fall times than the chosen MOSFET; $23\mu s$ and $27\mu s$ respectively for *Infineons* IPB017N10N5. The amount of peak current of the gate driver can also play a factor in rise and fall times as it needs to charge the MOSFET gate.

With these three constraints it came down to 2 different Gate Drivers, *Texas Instruments* UCC27201 and UCC27211, with UCC27211 being a revision later than UCC27201. Table 2.2 shows a comparison between several key characteristics of the drivers.

Characteristic	UCC27201A	UCC27211
Rated Voltage (V)	110	110
Rise Time (μs)	8.0	8.0
Fall Time (μs)	7.0	7.0
Peak Current (A)	3.0	4.0
Negative voltage handling at HS pin (V)	-15.0	-12.0
Cost (\$)	3.12	3.60
Footprint	SOIC-8	SOIC-8

Table 2: With four of the seven highlighted characteristics being the same both driver would work, but for the added peak current UCC27211 has an edge. In the event that more negative voltage handling is needed UCC27201A can be a drop in replacement for the UCC27211.

2.2.1 Bootstrap Capacitor

Write your subsection text here.

2.3 DC-DC Converter (5 Volts)

Write your subsection text here.

2.4 DC-DC Converter (12 Volts)

Write your subsection text here.

2.5 Microcontroller

Write your subsection text here.

$$\alpha = \sqrt{\beta} \tag{5}$$

3 Commutation Techniques

Write your section text here.

3.1 Trapezoidal Control

Write your subsection text here.

3.2 Field Oriented Control

Write your subsection text here.

4 Conclusion

Write your conclusion here.

5 Lessons Learned

Write your lessons learned here.