HTML Inline and Block Elements

Inline Elements (10)

- – Used to style small portions of text

  Example: <p>This is a red word.</p>

- <a> – Hyperlink

  Example: Visit Example

- <img> – Embeds an image

  Example: <img src="image.jpg" alt="Sample Image" width="100">

- – Makes text bold

  Example: Important information.

- – Italicizes text (emphasis)

  Example: This is very important.

- <label> – Label for form inputs

  Example: <label for="name">Name:</label>

- <input> – Form input

  Example: <input type="text" placeholder="Enter name">

- <abbr> – Abbreviation with tooltip

  Example: <abbr title="World Health Organization">WHO</abbr>

- <code> – For inline code

  Example: Use <code>console.log()</code> to print in JS.

- <button> – Inline depending on context

Example: <button>Click Me</button>

Block Elements (10)

- <div> – Generic block container

  Example: <div>This is a block element.</div>

- <p> – Paragraph

  Example: <p>This is a paragraph.</p>

- <h1> – Headings

  Example: <h1>Main Heading</h1>

- – Unordered list

  *Example: Item 1
Item 2
*

- – Ordered list

  *Example: First
Second
*

- – List item (within ul/ol)

  *Example: This is a list item.
*

- <form> – Form container

  Example: <form><input type="text"></form>

- <table> – Table container

  Example: <table><tr><td>Data</td></tr></table>

- <section> – Section of a page

  Example: <section><h2>About Us</h2></section>

- <article> – Self-contained content

  Example: <article><h2>News</h2><p>Details...</p></article>