

# **Protocol Audit Report**

Version 1.0

Cyfrin.io

Protocol Audit Report february 25, 2024

## **Protocol Audit Report**

## Ramprasad

february 25, 2024

Prepared by: Ramprasad Lead Auditors:

• Ramprasad

## **Table of Contents**

- Table of Contents
- Protocol Summary
- Disclaimer
- Risk Classification
- Audit Details
- The findings described in this document corresponded the following commmit hash:\*\*
  - Scope
  - Roles
- Executive Summary
  - Issues found
- Findings
  - High
    - \* [H-1] Storing the password on onchain males is visible to anyone, and no longer private.
  - likelihood & impact
    - \* [H-2] PasswordStore::setPassword has no access control, meaning a non owner could change the password.

Protocol Audit Report february 25, 2024

- likelihood and impact
- Informational
  - \* [I-1] PasswordStroe::getPassword natspec indicats a parameter that doesnt exist, causing the natspec to be incorrect.
- likelyhood and impact

## **Protocol Summary**

Password store is a protocall dedicated to storage and retreval of a users passwords. the protocall is designed to be used by a single user, and is not desined to be used multiple users. Only the owner is able to set and access the password.

## **Disclaimer**

The Ramprasad team makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the findings provided in this document. A security audit by the team is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the Solidity implementation of the contracts.

## **Risk Classification**

		Impact		
		High	Medium	Low
Likelihood	High	Н	H/M	М
	Medium	H/M	М	M/L
	Low	М	M/L	L

We use the CodeHawks severity matrix to determine severity. See the documentation for more details.

Protocol Audit Report february 25, 2024

## **Audit Details**

# The findings described in this document corresponded the following commmit hash:\*\*

1 2e8f81e263b3a9d18fab4fb5c46805ffc10a9990

## Scope

```
1 ./src/
2 PasswordStore.sol
```

#### **Roles**

-owner: The user who can set the password and read the password. -outsider: No one else should be able to set or read the password

## **Executive Summary**

## **Issues found**

Severtity	Number of issues found
High	2
Medium	0
Low	0
Information	1
Total	3

## **Findings**

#### High

[H-1] Storing the password on onchain males is visible to anyone, and no longer private.

**Description:** All data stored on onchain is visble to anyone. and can read it directly from the blockchain. the Passwordstore::s\_password variable is intended to be a aprivate variable and can access only through Passwordstore::getPassword function, which is intented to be only called by the owner of the contract.

we show one such method of reading any data off chain below.

**Impact:** Any one can read the private password directly from the blockchain.

**Proof of Concept:** (proof of code)

The below cast will show that any one can read the password directly from the blokchain.

1. Create a locally running chain.

```
1 make anvil
```

- 2. Deploy the contract on the chain. 'make deploy
- 3. Run the storage tool.

we use 1 because thats the storage slot of the s\_password in the contract.

```
1 cast storage <Address_here> 1 --rpc-url http://127.0.0.1:8545
```

You can praise that hex to a string with:

And get an out put of:

```
1 myPassword
```

**Recommended Mitigation:** Due to this, the overall architechture of the cotract should be rethought. one could encrypt the password of-chain and then store the encrypted password on on-chain. This is would require the user to remember the another password of-chain to decrypt the password. However

you would also likely want to remove the view function as you woudnt want the user to accidentally send a tracsaction with the password that decrypt your password.

## likelihood & impact

-impact: High -likelihood: High -Severity: High

## [H-2] PasswordStore::setPassword has no access control, meaning a non owner could change the password.

**Description:** The PasswordStore::setPassword function is set to be an external function, however, the natspec of the function and overall purpose of the smart contract is that This function allows only owner to set a password.

"'java script function setPassword(string memory newPassword) external { @> // @audit There are no access controls. s\_password = newPassword; emit SetNetPassword();

```
2 **Impact:** Any one can set/change the password of the contract.severly
       breaking the contract intended functionality.
3
4 **Proof of Concept:** Add the following to the `PasswordStore.t.sol` to
       test:
5
6 <details>
  <summary> CODE </summary>
8 ``java script
9
10 function test_anyone_can_set_password(address randomAddress) public {
11 vm.assume(randomAddress != owner);
12 vm.prank(randomAddress);
13 string memory expectedPassword = "MynewPassword";
14 passwordStore.setPassword(expectedPassword);
15
16
           vm.prank(owner);
           string memory actualPssword = passwordStore.getPassword();
17
           assertEq(actualPssword, expectedPassword);
18
19
       }
20
21
22
23 </details>
24
25 **Recommended Mitigation:** Add an access controll condition to `
      setPassword` function:
26
```

**Protocol Audit Report** 

```
27 ```java script
28 if(msg.sender != s_owner) {
29    revert PasswordStore_NotOwner()
30 }
```

## likelihood and impact

-impact: High -likelihood: High -Severity: High

#### Informational

[I-1] PasswordStroe: getPassword natspec indicats a parameter that doesnt exist, causing the natspec to be incorrect.

## **Description:**

```
java script //@audit there is no newPassword parameter; * @param
newPassword The new password to set. */ function getPassword()
external view returns (string memory){
```

the PasswordStroe: : getPassword function signature is getPassword() which the natspec say it should be getPassword(string).

**Impact:** The natspec is incorrect.

**Recommended Mitigation:** Remove the incorrect natspec line.

```
1 - * @param newPassword The new password to set.
```

### likelyhood and impact

-impact: High -likelihood: Low -severity: Informational/gas