



MISH 05

SAFETY FORMS

PRE JOB SAFETY PLANNING JOB HAZARD ANALYSIS

MHC INDUSTRIAL SAFETY AND HEALTH PROGRAM (MISH) — FORMS LIBRARY

FORM IDENTIFICATION & CONTROL

FORM NUMBER

MISH 05

REVISION

1.0

{{FORM_SECTION_LABEL}}

MISH 05

CATEGORY

Safety Forms

EFFECTIVE DATE

June 2026

DOCUMENT OWNER

Safety Officer (Matt Ramsey)

{{FORM_BRIEFING_HEAD}}

- ★ Authority: {{FORM_BRIEFING_AUTHORITY}}
- ★ Use: {{FORM_BRIEFING_USE}}
- ★ Retention: {{FORM_BRIEFING_RETENTION}}
- ★ Revision Control: {{FORM_BRIEFING_REVISION}}

REFERENCE



MISH 05

COMPANY CONTACT

MH Construction, Inc.

3111 N Capitol Ave.

Pasco, WA 99301

(509) 308-6489 • www.mhc-gc.com

WA Lic: MHCONCI907R7 • OR Lic: 194331 • ID Lic: RCE-49250

ACCREDITATION & TRUST



Pre Job Safety Planning Job Hazard Analysis

MISH 05

MH CONSTRUCTION, INC.

Industrial Safety & Health Program (MISH)

FORM-MISH-05 | Pre-Job Safety Planning Job Hazard Analysis

Rev. 3 | Effective: 04/07/2026 | Safety Officer: Matt Ramsey

Project Name / Number:	
Job Site Address:	
Date:	
Supervisor / Foreman:	
Employee Name(s) (where applicable):	
Subcontractor (where applicable):	

Task Description:

Pre-Task Hazard Identification Checklist:

☐ Fall Hazards (>6 ft)	☐ Material Handling / Lifting
☐ Electrical Hazards	☐ Hot Work (Welding/Cutting)
☐ Confined Space Entry	☐ Chemical / Hazardous Materials
☐ Trenching / Excavation	☐ Noise Exposure
☐ Heavy Equipment Operation	☐ Struck-By / Caught-Between

Required PPE Checklist:

☐ Hard Hat	☐ Work Gloves
☐ Safety Glasses	☐ Hearing Protection
☐ High-Visibility Vest	☐ Fall Protection Harness
☐ Steel-Toe Boots	☐ Respirator

Job Hazard Analysis:

Step #	Task Step Description	Potential Hazard	Hazard Control Measure	Responsible Party
1	Mobilize equipment to site	Struck by moving equipment	Use spotters, establish exclusion zones, wear high-vis vests	Foreman / Operator
2	Unload materials from truck	Strains/sprains, crushed hands/feet	Use proper lifting techniques, wear gloves and steel-toe boots, use forklift if >50 lbs	Laborers
3	Set up scaffolding	Fall from height, scaffold collapse	Inspect components, erect by competent person, use fall protection if >10 ft	Competent Person
4	Operate power tools	Electrical shock, flying debris	Inspect cords, use GFCI, wear safety glasses and face shield	Worker
5	Clean up work area	Slips, trips, falls	Maintain housekeeping, remove debris promptly, secure loose materials	All Personnel
6				
7				
8				
9				

10				
----	--	--	--	--

Emergency Contacts:

Nearest Hospital / Clinic:	
Emergency Number:	
Site First Aid Location:	

Regulatory Authority

OSHA: 29 CFR 1926.20(b)(1) Initiation and maintenance of programs; 29 CFR 1926.21(b)

WISHA: WAC 296-155-110(3) Accident Prevention Program Planning; WAC 296-155-035 General Requirements

AGC: JHA Guidelines; AGC SHIP Best Practices Handbook Ch. 4

This form supports compliance with the above regulations. Retain completed forms for minimum 3 years per 29 CFR 1904.33 and WAC 296-27.

Prepared by: _____ Title: _____ Date: _____

Reviewed by: _____ Title: _____ Date: _____
