



MISH 11

SAFETY FORMS

FALL PROTECTION PRETASK JHA

MHC INDUSTRIAL SAFETY AND HEALTH PROGRAM (MISH) — FORMS LIBRARY

FORM IDENTIFICATION & CONTROL

FORM NUMBER

MISH 11

REVISION

1.0**{{FORM_SECTION_LABEL}}****MISH 11**

CATEGORY

Safety Forms

EFFECTIVE DATE

June 2026

DOCUMENT OWNER

Safety Officer (Matt Ramsey)

{{FORM_BRIEFING_HEAD}}

- ★ Authority: {{FORM_BRIEFING_AUTHORITY}}
- ★ Use: {{FORM_BRIEFING_USE}}
- ★ Retention: {{FORM_BRIEFING_RETENTION}}
- ★ Revision Control: {{FORM_BRIEFING_REVISION}}

REFERENCE



MISH 11

COMPANY CONTACT

MH Construction, Inc.

3111 N Capitol Ave.

Pasco, WA 99301

(509) 308-6489 • www.mhc-gc.com

WA Lic: MHCONCI907R7 • OR Lic: 194331 • ID Lic: RCE-49250

ACCREDITATION & TRUST



Fall Protection Pretask JHA

MISH 11

MH CONSTRUCTION, INC.

Industrial Safety & Health Program (MISH)

FORM-MISH-11 | Fall Protection Pre-Task JHA

Rev. 3 | Effective: 04/07/2026 | Safety Officer: Matt Ramsey

Project Name / Number:		Date:	
Job Site Address:		Supervisor / Foreman:	
Employee Name(s):		Subcontractor:	

Task Description:

Pre-Task Hazard Identification Checklist:

☐ Unprotected edges/holes	☐ Leading edge work
☐ Roofing activities	☐ Scaffolding operations
☐ Aerial lift operations	☐ Steel erection
☐ Excavation/trenching	☐ Wall openings
☐ Hoist areas	☐ Formwork/reinforcing steel

Required PPE Checklist:

☐ Full body harness	☐ Shock-absorbing lanyard
☐ Self-retracting lifeline (SRL)	☐ Anchor point (5000 lbs)

☐ Hard hat	☐ Safety glasses
☐ Work boots	☐ Gloves

Step #	Task Step Description	Potential Hazard	Hazard Control Measure	Responsible Party
1	Inspect fall protection equipment	Using defective equipment	Inspect harness, lanyard, and anchor points before use. Remove defective equipment from service.	Employee
2	Identify anchor points	Inadequate anchor strength	Ensure anchor point can support 5,000 lbs per employee attached.	Competent Person
3	Don fall protection equipment	Improper fit	Adjust harness to fit snugly. Ensure D-ring is between shoulder blades.	Employee
4	Access work area	Slips, trips, falls	Maintain 3 points of contact on ladders. Keep walkways clear of debris.	Employee
5	Perform work at height	Fall to lower level	Remain tied off 100% of the time when exposed to fall hazard.	Employee
6				
7				
8				
9				
10				

Emergency Contacts:

Nearest Hospital: _____	Emergency Number: 911	Site First Aid Location: _____
----------------------------	--------------------------	-----------------------------------

Regulatory Authority

OSHA: 29 CFR 1926 Subpart M; 29 CFR 1926.501 Duty to Have Fall Protection; 29 CFR 1926.502 Fall Protection Systems Criteria; 29 CFR 1926.503 Training Requirements

WISHA: WAC 296-880 Unified Safety Standards for Fall Protection

AGC: Safety and Health Manual Ch. 7 Fall Protection

This form supports compliance with the above regulations. Retain completed forms for minimum 3 years per 29 CFR 1904.33 and WAC 296-27.

Prepared by: _____ | Title: _____ | Date:

Reviewed by: _____ | Title: _____ | Date:
