



MISH 17

SAFETY FORMS

LADDER INSPECTION CHECKLIST

MHC INDUSTRIAL SAFETY AND HEALTH PROGRAM (MISH) — FORMS LIBRARY

FORM IDENTIFICATION & CONTROL

FORM NUMBER

MISH 17

REVISION

1.0

{{FORM_SECTION_LABEL}}

MISH 17

CATEGORY

Safety Forms

EFFECTIVE DATE

June 2026

DOCUMENT OWNER

Safety Officer (Matt Ramsey)

{{FORM_BRIEFING_HEAD}}

- ★ Authority: {{FORM_BRIEFING_AUTHORITY}}
- ★ Use: {{FORM_BRIEFING_USE}}
- ★ Retention: {{FORM_BRIEFING_RETENTION}}
- ★ Revision Control: {{FORM_BRIEFING_REVISION}}

REFERENCE



MISH 17

COMPANY CONTACT

MH Construction, Inc.

3111 N Capitol Ave.

Pasco, WA 99301

(509) 308-6489 • www.mhc-gc.com

WA Lic: MHCONCI907R7 • OR Lic: 194331 • ID Lic: RCE-49250

ACCREDITATION & TRUST



Ladder Inspection Checklist

MISH 17

MH CONSTRUCTION, INC.

Industrial Safety & Health Program (MISH)

FORM-MISH-17 | Ladder Inspection Checklist

Rev. 3 | Effective: 04/07/2026 | Safety Officer: Matt Ramsey

Project Name / Number	
Job Site Address	
Date	
Supervisor / Foreman	
Employee Name(s) (where applicable)	
Subcontractor (where applicable)	

Inspection Frequency Note:

Ladders shall be inspected prior to each use and periodically by a competent person as required by OSHA 29 CFR 1926.1053(b)(15) and WISHA WAC 296-876-20030.

Ladder Inspection Checklist:

Item #	Inspection Item	Pass	Fail	N/A	Corrective Action Required
--------	-----------------	------	------	-----	----------------------------

1	Rungs/steps are free of grease, oil, and other slipping hazards (per 29 CFR 1926.1053(b)(6))	☐	☐	☐	
2	Rungs/steps are uniformly spaced and securely attached (per 29 CFR 1926.1053(a)(3))	☐	☐	☐	
3	Side rails are free of splinters, sharp edges, and other defects (per 29 CFR 1926.1053(b)(16))	☐	☐	☐	
4	Side rails are not bent, broken, or excessively worn (per 29 CFR 1926.1053(b)(16))	☐	☐	☐	
5	All hardware and fittings are securely attached and not corroded (per 29 CFR 1926.1053(b)(16))	☐	☐	☐	
6	Spreaders/locks are in good working order and properly engaged (per 29 CFR 1926.1053(b)(16))	☐	☐	☐	
7	Ladder feet/shoes are present, in good condition, and properly oriented (per 29 CFR 1926.1053(b)(7))	☐	☐	☐	
8	Labels and markings are legible and present (e.g., duty rating, warnings) (per 29 CFR 1926.1053(a)(1))	☐	☐	☐	
9	No structural damage (cracks, dents, bends) to any part of the ladder (per 29 CFR 1926.1053(b)(16))	☐	☐	☐	
10	Proper length for task, extending at least 3 feet above landing (per 29 CFR 1926.1053(b)(1))	☐	☐	☐	
11	Secured against displacement when in use (per 29 CFR 1926.1053(b)(8))	☐	☐	☐	
12	Used on a level and stable surface (per 29 CFR 1926.1053(b)(5))	☐	☐	☐	
13	Clearance around and behind ladder is adequate (per 29 CFR 1926.1053(b)(4))	☐	☐	☐	
14	No modifications or alterations have been made to the ladder (per 29 CFR 1926.1053(b)(16))	☐	☐	☐	

15	Ladder is clean and free of foreign materials (per 29 CFR 1926.1053(b)(6))	☐	☐	☐	
----	--	--------------------------	--------------------------	--------------------------	--

Deficiency Log:

Item #	Description of Deficiency	Corrective Action	Assigned To	Due Date	Completed Date

Inspector Signature Block:

Inspector Name:	_____	Date:	_____
Supervisor Review:	_____	Date:	_____

Regulatory Authority

OSHA: 29 CFR 1926 Subpart X; 29 CFR 1926.1053 Ladders

WISHA: WAC 296-876 Ladders Portable and Fixed

AGC: Safety and Health Manual Ch. 12 Ladders and Stairways

This form supports compliance with the above regulations. Retain completed forms for minimum 3 years per 29 CFR 1904.33 and WAC 296-27.

Prepared by:	_____	Title:	_____
Reviewed by:	_____	Title:	_____