



MISH 20

SAFETY FORMS

AERIAL LIFT PRE OPERATION INSPECTION AND JHA

MHC INDUSTRIAL SAFETY AND HEALTH PROGRAM (MISH) — FORMS LIBRARY

FORM IDENTIFICATION & CONTROL

FORM NUMBER

MISH 20

REVISION

1.0

{{FORM_SECTION_LABEL}}

MISH 20

CATEGORY

Safety Forms

EFFECTIVE DATE

June 2026

DOCUMENT OWNER

Safety Officer (Matt Ramsey)

{{FORM_BRIEFING_HEAD}}

- ★ Authority: {{FORM_BRIEFING_AUTHORITY}}
- ★ Use: {{FORM_BRIEFING_USE}}
- ★ Retention: {{FORM_BRIEFING_RETENTION}}
- ★ Revision Control: {{FORM_BRIEFING_REVISION}}

REFERENCE



MISH 20

COMPANY CONTACT

MH Construction, Inc.

3111 N Capitol Ave.

Pasco, WA 99301

(509) 308-6489 • www.mhc-gc.com

WA Lic: MHCONCI907R7 • OR Lic: 194331 • ID Lic: RCE-49250

ACCREDITATION & TRUST



Aerial Lift Pre Operation Inspection and JHA

MISH 20

MH CONSTRUCTION, INC.

Industrial Safety & Health Program (MISH)

FORM-MISH-20: Aerial Lift Pre-Operation Inspection and JHA

Rev. 3 | Effective: 04/07/2026 | Safety Officer: Matt Ramsey

Project Name / Number:		Supervisor / Foreman:	
Job Site Address:		Employee Name(s):	
Date:		Subcontractor:	

Task Description:

Pre-Task Hazard Identification:

☐ Overhead power lines / electrical hazards	☐ Overhead obstructions / pinch points
☐ Uneven or unstable ground conditions	☐ Inadequate lighting
☐ High winds or adverse weather	☐ Hazardous atmosphere
☐ Drop-offs, holes, or trenches	☐ Falling objects
☐ Pedestrian or vehicular traffic	☐ Equipment malfunction

Required PPE:

☐ Hard Hat	☐ Full Body Harness
☐ Safety Glasses	☐ Shock-Absorbing Lanyard

☐ High-Visibility Vest	☐ Work Gloves
☐ Steel-Toe Boots	☐ Hearing Protection

Job Hazard Analysis (JHA):

Step #	Task Step Description	Potential Hazard	Hazard Control Measure	Responsible Party
1	Pre-operation inspection	Missed defects, equipment failure	Complete inspection checklist thoroughly before use	Operator
2	Moving lift to work area	Struck-by, tip-over, crushing	Use spotter, check route for hazards, maintain safe speed	Operator / Spotter
3	Elevating platform	Fall, struck-by overhead objects, electrocution	Maintain 10ft clearance from power lines, wear harness/lanyard tied off to anchor point	Operator
4	Performing work from platform	Dropped objects, falls	Keep tools tethered, do not stand on guardrails, keep feet on floor	Operator
5	Lowering and parking lift	Crushing, unauthorized use	Check below before lowering, park on level ground, remove key	Operator
6				
7				
8				
9				
10				

Emergency Contacts:

Nearest Hospital: _____

Emergency Number: 911 or _____

Site First Aid Location: _____

Aerial Lift Pre-Operation Inspection Checklist

Inspection Frequency: Prior to each work shift (per 29 CFR 1926.453(b)(2)(i) and WAC 296-880).

Item #	Inspection Item	Pass	Fail	N/A	Corrective Action Required
1	Operating and emergency controls (29 CFR 1926.453)	☐	☐	☐	
2	Safety devices (limit switches, alarms) (29 CFR 1926.453)	☐	☐	☐	
3	Personal fall protection gear (WAC 296-880)	☐	☐	☐	
4	Tires and wheels (pressure, damage) (29 CFR 1926.453)	☐	☐	☐	
5	Outriggers, stabilizers, and extendable axles (29 CFR 1926.453)	☐	☐	☐	
6	Fluid levels (oil, hydraulic, fuel, coolant) (29 CFR 1926.453)	☐	☐	☐	
7	Hydraulic/pneumatic/electrical systems (leaks/damage) (29 CFR 1926.453)	☐	☐	☐	
8	Structural components (cracks, welds, rust) (29 CFR 1926.453)	☐	☐	☐	
9	Guardrail system and access gates (WAC 296-880)	☐	☐	☐	
10	Placards, warnings, and control markings (29 CFR 1926.453)	☐	☐	☐	
11	Operating manual in weather-resistant compartment (29 CFR 1926.453)	☐	☐	☐	
12	Steering and brakes (29 CFR 1926.453)	☐	☐	☐	
13	Battery and charger connections (29 CFR 1926.453)	☐	☐	☐	

14	Horn and backup alarm (29 CFR 1926.453)	☐	☐	☐	
15	Platform cleanliness (free of debris/grease) (29 CFR 1926.453)	☐	☐	☐	

Deficiency Log:

Item #	Description of Deficiency	Corrective Action	Assigned To	Due Date	Completed Date

Inspector Name: _____	Signature: _____	Date: _____
Supervisor Review: _____	Signature: _____	Date: _____

Regulatory Authority

OSHA: 29 CFR 1926.453 Aerial Lifts; ANSI/SIA A92 Series

WISHA: WAC 296-880 Unified Safety Standards for Fall Protection AWP's; WAC 296-155-53400 Cranes General Requirements for boom lifts

AGC: Safety and Health Manual Ch. 14 Aerial Work Platforms

This form supports compliance with the above regulations. Retain completed forms for minimum 3 years per 29 CFR 1904.33 and WAC 296-27.

Prepared by: _____ | Title: _____ | Date: _____

Reviewed by: _____ | Title: _____ | Date: _____