



MISH 22

SAFETY FORMS

SCAFFOLD ERECTION AND INSPECTION CHECKLIST

MHC INDUSTRIAL SAFETY AND HEALTH PROGRAM (MISH) — FORMS LIBRARY

FORM IDENTIFICATION & CONTROL

FORM NUMBER

MISH 22

REVISION

1.0

{{FORM_SECTION_LABEL}}

MISH 22

CATEGORY

Safety Forms

EFFECTIVE DATE

June 2026

DOCUMENT OWNER

Safety Officer (Matt Ramsey)

{{FORM_BRIEFING_HEAD}}

- ★ Authority: {{FORM_BRIEFING_AUTHORITY}}
- ★ Use: {{FORM_BRIEFING_USE}}
- ★ Retention: {{FORM_BRIEFING_RETENTION}}
- ★ Revision Control: {{FORM_BRIEFING_REVISION}}

REFERENCE



MISH 22

COMPANY CONTACT

MH Construction, Inc.

3111 N Capitol Ave.

Pasco, WA 99301

(509) 308-6489 • www.mhc-gc.com

WA Lic: MHCONCI907R7 • OR Lic: 194331 • ID Lic: RCE-49250

ACCREDITATION & TRUST



Scaffold Erection and Inspection Checklist

MISH 22

MH CONSTRUCTION, INC.

Industrial Safety & Health Program (MISH)

FORM-MISH-22 | Scaffold Erection and Inspection Checklist

Rev. 3 | Effective: 04/07/2026 | Safety Officer: Matt Ramsey

Project Name / Number	
Job Site Address	
Date	
Supervisor / Foreman	
Employee Name(s)	
Subcontractor	

Inspection Frequency Note: Scaffolds must be inspected by a competent person prior to each work shift and after any occurrence which could affect its structural integrity (e.g., severe weather, impact). (per 29 CFR 1926.451(f)(3) and WAC 296-869-200(2))

Item #	Inspection Item	Pass	Fail	N/A	Corrective Action Required
1	Base plates and mudsills	☐	☐	☐	

	are level and sound (per 29 CFR 1926.451(c) (2))				
2	Scaffold is plumb, level, and square (per 29 CFR 1926.451(d) (3))	☐	☐	☐	_____
3	All components are in good condition and free from damage (per 29 CFR 1926.451(b) (1))	☐	☐	☐	_____
4	Guardrails are installed on all open sides and ends of platforms (per 29 CFR 1926.451(g) (4))	☐	☐	☐	_____
5	Midrails are installed approximately halfway between the toprail and the platform surface (per 29 CFR 1926.451(g) (4)(ii))	☐	☐	☐	_____

6	Toeboards are installed on all open sides and ends of platforms (per 29 CFR 1926.451(g)(4)(iii))	☐	☐	☐	_____
7	Platforms are fully planked or decked between the front uprights and the guardrail supports (per 29 CFR 1926.451(b)(1))	☐	☐	☐	_____
8	Platforms are secured to prevent displacement (per 29 CFR 1926.451(b)(2))	☐	☐	☐	_____
9	Access to scaffold is safe and appropriate (ladders, ramps, etc.) (per 29 CFR 1926.451(e))	☐	☐	☐	_____

10	Scaffold is tied, guyed, or braced as required (per 29 CFR 1926.451(c) (1))	☐	☐	☐	
11	Competent person has inspected scaffold before each shift (per 29 CFR 1926.451(f) (3))	☐	☐	☐	
12	Fall protection is provided for employees working on scaffolds 10 feet or more above a lower level (per 29 CFR 1926.451(g) (1))	☐	☐	☐	
13	Scaffold is not overloaded (per 29 CFR 1926.451(a) (1))	☐	☐	☐	
14	Electrical hazards are identified and controlled (per 29 CFR 1926.451(f) (6))	☐	☐	☐	

15	Overhead protection is provided where necessary (per 29 CFR 1926.451(f) (7))	☐	☐	☐	
16	Wheels and casters are locked on mobile scaffolds (per 29 CFR 1926.452(w) (2))	☐	☐	☐	
17	Scaffold is erected, dismantled, or altered only under the supervision of a competent person (per 29 CFR 1926.451(f) (1))	☐	☐	☐	
18	Training has been provided to all employees working on scaffolds (per 29 CFR 1926.454)	☐	☐	☐	
19	Clearances from power lines are maintained (per 29 CFR	☐	☐	☐	

	1926.451(f) (6))				
20	Debris chutes or other means are used to remove debris (per 29 CFR 1926.451(f) (8))	☐	☐	☐	

Item #	Description of Deficiency	Corrective Action	Assigned To	Due Date	Completed Date

Inspector Name: _____ Signature: _____ Date: _____

Supervisor Review: _____ Signature: _____ Date: _____

Regulatory Authority

OSHA: 29 CFR 1926 Subpart L; 29 CFR 1926.451 General Requirements; 29 CFR 1926.454 Training Requirements

WISHA: WAC 296-869 Scaffolds

AGC: Safety and Health Manual Ch. 16 Scaffolding

This form supports compliance with the above regulations. Retain completed forms for minimum 3 years per 29 CFR 1904.33 and WAC 296-27.

Prepared by: _____ | Title: _____ | Date: _____
Reviewed by: _____ | Title: _____ | Date: _____