



MISH 26

SAFETY FORMS

EXCAVATION AND TRENCHING SAFETY INSPECTION AND JHA

MHC INDUSTRIAL SAFETY AND HEALTH PROGRAM (MISH) — FORMS LIBRARY

FORM IDENTIFICATION & CONTROL

FORM NUMBER

MISH 26

REVISION

1.0

{{FORM_SECTION_LABEL}}

MISH 26

CATEGORY

Safety Forms

EFFECTIVE DATE

June 2026

DOCUMENT OWNER

Safety Officer (Matt Ramsey)

{{FORM_BRIEFING_HEAD}}

- ★ Authority: {{FORM_BRIEFING_AUTHORITY}}
- ★ Use: {{FORM_BRIEFING_USE}}
- ★ Retention: {{FORM_BRIEFING_RETENTION}}
- ★ Revision Control: {{FORM_BRIEFING_REVISION}}

REFERENCE



MISH 26

COMPANY CONTACT

MH Construction, Inc.

3111 N Capitol Ave.

Pasco, WA 99301

(509) 308-6489 • www.mhc-gc.com

WA Lic: MHCONCI907R7 • OR Lic: 194331 • ID Lic: RCE-49250

ACCREDITATION & TRUST



Excavation and Trenching Safety Inspection and JHA

MISH 26

MH CONSTRUCTION, INC.

Industrial Safety & Health Program (MISH)

FORM-MISH-26 | Excavation and Trenching Safety Inspection and JHA

Rev. 3 | Effective: 04/07/2026 | Safety Officer: Matt Ramsey

Project Name / Number:		Job Site Address:	
Date:		Supervisor / Foreman:	
Employee Name(s):		Subcontractor:	

PART 1: EXCAVATION AND TRENCHING INSPECTION

Inspection Frequency: Daily prior to start of work, as needed throughout shift, and after every rainstorm or other hazard-increasing occurrence (per 29 CFR 1926.651(k)(1) and WAC 296-155-655(11)).

Item #	Inspection Item	Pass	Fail	N/A	Corrective Action Required
1	Surface encumbrances removed or supported (29 CFR 1926.651(a))	☐	☐	☐	
2	Underground utilities located and marked (29 CFR 1926.651(b))	☐	☐	☐	
3	Access/egress provided within 25 ft for trenches >4 ft deep (29 CFR 1926.651(c))	☐	☐	☐	
4	Employees protected from vehicular traffic (29 CFR 1926.651(d))	☐	☐	☐	
5	Employees protected from falling loads (29 CFR 1926.651(e))	☐	☐	☐	

6	Warning system for mobile equipment in place (29 CFR 1926.651(f))	☐	☐	☐	
7	Hazardous atmospheres tested (>4 ft deep) (29 CFR 1926.651(g))	☐	☐	☐	
8	Emergency rescue equipment available (29 CFR 1926.651(g)(2))	☐	☐	☐	
9	Protection from water accumulation provided (29 CFR 1926.651(h))	☐	☐	☐	
10	Adjacent structures supported/protected (29 CFR 1926.651(i))	☐	☐	☐	
11	Loose rock/soil scaled or barricaded (29 CFR 1926.651(j)(1))	☐	☐	☐	
12	Spoils/materials kept >2 ft from edge (29 CFR 1926.651(j)(2))	☐	☐	☐	
13	Fall protection provided at crossings (29 CFR 1926.651(l))	☐	☐	☐	
14	Protective system designed by competent person (29 CFR 1926.652(a))	☐	☐	☐	
15	Sloping/benching meets requirements (29 CFR 1926.652(b))	☐	☐	☐	
16	Shield system (trench box) installed correctly (29 CFR 1926.652(g))	☐	☐	☐	
17	Shield system extends >18 inches above top of vertical side (29 CFR 1926.652(g)(2))	☐	☐	☐	
18	No employees in shield during installation/removal (29 CFR 1926.652(g)(1))	☐	☐	☐	

19	Competent person on site during excavation (WAC 296-155-655)	☐	☐	☐	
20	Daily inspection completed by competent person (29 CFR 1926.651(k))	☐	☐	☐	

Deficiency Log

Item #	Description of Deficiency	Corrective Action	Assigned To	Due Date	Completed Date

Inspector Name:	Signature:	Date:
Supervisor Review:	Signature:	Date:

PART 2: JOB HAZARD ANALYSIS (JHA)

Task Description:

Pre-Task Hazard Identification:

☐ Cave-ins / Soil Collapse	☐ Mobile Equipment Traffic
☐ Underground Utilities	☐ Slips, Trips, and Falls
☐ Overhead Power Lines	☐ Falling Materials/Spoils
☐ Hazardous Atmosphere	☐ Confined Space Entry
☐ Water Accumulation	☐ Noise Exposure

Required PPE:

☐ Hard Hat	☐ Work Gloves
☐ Safety Glasses	☐ Hearing Protection

☐ High-Visibility Vest	☐ Gas Monitor
☐ Steel-Toe Boots	☐ Fall Protection

Step #	Task Step Description	Potential Hazard	Hazard Control Measure	Responsible Party
1	Site Preparation and Utility Locating	Striking underground utilities (gas, electric, water)	Call 811 before digging. Hand dig or pothole to verify utility locations. Maintain safe distance from marked lines.	Competent Person / Operator
2	Excavating / Trenching	Cave-in or soil collapse	Classify soil. Implement protective system (sloping, benching, shoring, or shielding) for trenches >5 ft deep.	Competent Person
3	Spoil Placement	Spoils falling back into trench	Keep spoils and equipment at least 2 feet from the edge of the excavation.	Operator / Laborers
4	Access and Egress	Slips, trips, falls; inability to exit quickly	Provide ladders, ramps, or stairs within 25 feet of travel for trenches >4 ft deep. Ensure ladder extends 3 ft above edge.	Competent Person
5	Working in Trench	Hazardous atmosphere or water accumulation	Test atmosphere if >4 ft deep and potential exists. Inspect for water accumulation daily. Use dewatering equipment if needed.	Competent Person
6				
7				
8				
9				
10				

Nearest Hospital:	Emergency Number: 911	Site First Aid Location:
-------------------	--------------------------	--------------------------

Regulatory Authority

OSHA: 29 CFR 1926 Subpart P; 29 CFR 1926.651 Specific Excavation Requirements; 29 CFR 1926.652 Requirements for Protective Systems

WISHA: WAC 296-155-650 Scope and Application; WAC 296-155-655 General Protection Requirements; WAC 296-155-657 Requirements for Protective Systems

AGC: Safety and Health Manual Ch. 20 Excavation and Trenching

This form supports compliance with the above regulations. Retain completed forms for minimum 3 years per 29 CFR 1904.33 and WAC 296-27.

Prepared by: _____	Title: _____	Date: _____
Reviewed by: _____	Title: _____	Date: _____