



MISH 35

SAFETY FORMS

RIGGING INSPECTION AND PRE LIFT JHA

MHC INDUSTRIAL SAFETY AND HEALTH PROGRAM (MISH) — FORMS LIBRARY

FORM IDENTIFICATION & CONTROL

FORM NUMBER

MISH 35

REVISION

1.0

{{FORM_SECTION_LABEL}}

MISH 35

CATEGORY

Safety Forms

EFFECTIVE DATE

June 2026

DOCUMENT OWNER

Safety Officer (Matt Ramsey)

{{FORM_BRIEFING_HEAD}}

- ★ Authority: {{FORM_BRIEFING_AUTHORITY}}
- ★ Use: {{FORM_BRIEFING_USE}}
- ★ Retention: {{FORM_BRIEFING_RETENTION}}
- ★ Revision Control: {{FORM_BRIEFING_REVISION}}

REFERENCE



MISH 35

COMPANY CONTACT

MH Construction, Inc.

3111 N Capitol Ave.

Pasco, WA 99301

(509) 308-6489 • www.mhc-gc.com

WA Lic: MHCONCI907R7 • OR Lic: 194331 • ID Lic: RCE-49250

ACCREDITATION & TRUST



Rigging Inspection and Pre Lift JHA

MISH 35

MH CONSTRUCTION, INC.

Industrial Safety & Health Program (MISH)

FORM-MISH-35 | Rigging Inspection and Pre-Lift JHA

Rev. 3 | Effective: 04/07/2026 | Safety Officer: Matt Ramsey

Project Name / Number:		Job Site Address:	
Date:		Supervisor / Foreman:	
Employee Name(s):		Subcontractor:	

RIGGING INSPECTION CHECKLIST

Inspection Frequency: Prior to each shift and as necessary during use per 29 CFR 1926.251(a)(1) and WAC 296-155-33700(1).

Item #	Inspection Item	Pass	Fail	N/A	Corrective Action Required
1	Slings - Synthetic web: No snags, punctures, tears, or cuts (29 CFR 1926.251(e)(8))	☐	☐	☐	
2	Slings - Synthetic web: No broken or worn stitches (29 CFR 1926.251(e)(8))	☐	☐	☐	
3	Slings - Synthetic web: Identification tags present and legible (29 CFR 1926.251(e)(1))	☐	☐	☐	
4	Slings - Wire rope: No excessive broken wires (29 CFR 1926.251(c)(4))	☐	☐	☐	

5	Slings - Wire rope: No severe localized abrasion or scraping (29 CFR 1926.251(c)(4))	☐	☐	☐	
6	Slings - Wire rope: No kinking, crushing, or bird caging (29 CFR 1926.251(c)(4))	☐	☐	☐	
7	Slings - Wire rope: Identification tags present and legible (29 CFR 1926.251(c)(1))	☐	☐	☐	
8	Slings - Alloy steel chain: No cracked or deformed master links/hooks (29 CFR 1926.251(b)(5))	☐	☐	☐	
9	Slings - Alloy steel chain: No excessive wear or stretching (29 CFR 1926.251(b)(5))	☐	☐	☐	
10	Slings - Alloy steel chain: Identification tags present and legible (29 CFR 1926.251(b)(1))	☐	☐	☐	
11	Shackles: No deformation, cracks, or excessive wear (29 CFR 1926.251(f)(1))	☐	☐	☐	
12	Shackles: Pins are correct type and properly seated (29 CFR 1926.251(f)(1))	☐	☐	☐	
13	Hooks: No cracks, nicks, or gouges (29 CFR 1926.251(a)(1))	☐	☐	☐	
14	Hooks: Throat opening not increased by more than 15% (29 CFR 1926.251(a)(1))	☐	☐	☐	
15	Hooks: Safety latches present and functioning properly (WAC 296-155-33810)	☐	☐	☐	
16	Eyebolts/Rings: No cracks, bends, or elongation (29 CFR 1926.251(a)(1))	☐	☐	☐	
17	Custom Lifting Devices: Marked with capacity and weight (29 CFR 1926.251(a)(4))	☐	☐	☐	

18	Custom Lifting Devices: Structurally sound, no visible defects (29 CFR 1926.251(a)(1))	☐	☐	☐	
19	Rigging Hardware: Free of excessive rust or corrosion (29 CFR 1926.251(a)(1))	☐	☐	☐	
20	Storage: Rigging stored properly off the ground and protected (WAC 296-155-33700)	☐	☐	☐	

DEFICIENCY LOG

Item #	Description of Deficiency	Corrective Action	Assigned To	Due Date	Completed Date

Inspector Name: _____	Signature: _____	Date: _____
Supervisor Review: _____	Signature: _____	Date: _____

PRE-LIFT JOB HAZARD ANALYSIS (JHA)

Task Description:

Pre-Task Hazard Identification:

☐ Overhead Power Lines	☐ Wind/Weather Conditions	☐ Uneven/Soft Ground
☐ Blind Lifts/Poor Visibility	☐ Swing Radius Hazards	☐ Traffic/Pedestrians
☐ Load Instability	☐ Sharp Edges on Load	☐ Pinch Points
☐ Communication Issues	☐ Equipment Failure	☐ Suspended Loads

Required PPE:

☐ Hard Hat	☐ Safety Glasses	☐ High-Vis Apparel
-----------------------------------	---	---

☐ Steel-Toe Boots	☐ Leather Gloves	☐ Fall Protection
☐ Hearing Protection	☐ Taglines	

Step #	Task Step Description	Potential Hazard	Hazard Control Measure	Responsible Party
1	Inspect rigging equipment	Using damaged rigging causing load drop	Perform pre-use inspection per checklist. Remove damaged rigging from service.	Rigger
2	Attach rigging to load	Pinch points, sharp edges cutting slings	Keep hands clear of pinch points. Use softeners/edge protection on sharp corners.	Rigger
3	Verify load weight and center of gravity	Overloading crane, load shifting/tipping	Confirm weight with documentation. Perform test lift to verify balance.	Lift Director / Rigger
4	Lift and move load	Struck by load, swing radius hazards	Use taglines to control load. Keep personnel out of fall zone and swing radius.	Operator / Rigger
5	Communicate during lift	Misunderstanding signals causing accident	Establish clear communication method (radio or standard hand signals). Designate one signal person.	Signal Person / Operator
6				
7				
8				
9				
10				

Nearest Hospital: _____	Emergency Number: 911	Site First Aid Location: _____
----------------------------	--------------------------	-----------------------------------

Regulatory Authority

OSHA: 29 CFR 1926 Subpart CC; 29 CFR 1926.251 Rigging Equipment for Material Handling

WISHA: WAC 296-155-336 through 296-155-340 Rigging Requirements for Material Handling; WAC 296-155-556 through 296-155-562 Crane Rigging Requirements

AGC: Safety and Health Manual Ch. 15 Cranes and Rigging

This form supports compliance with the above regulations. Retain completed forms for minimum 3 years per 29 CFR 1904.33 and WAC 296-27.

Prepared by: _____	Title: _____	Date: _____
Reviewed by: _____	Title: _____	Date: _____