



CONTROLLED ENTERPRISE DOCUMENT

TBT-01.03 | Hearing Conservation

MH Construction, INC Enterprise Management System

Document family: TOOLBOX TALK LIBRARY

Document title: TBT-01.03 | Hearing Conservation

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

TBT-01.03: Hearing Conservation

CSI Division: Div 01 | OSHA Reference: 29 CFR 1926.52

Delivery: Mandatory for all new hires; required annually for workers exposed to noise at or above 85 dBA.

DIRECTIVE — Policy Standard

All employees exposed to noise levels at or above the 8-hour time-weighted average of 85 dBA must participate in the MH Construction, INC Hearing Conservation Program.

GENERAL ORDER — Procedure

Hearing protection (earplugs or earmuffs) must be worn whenever noise levels exceed 90 dBA. As a rule of thumb, if you have to raise your voice to be heard by someone 3 feet away, hearing protection is required.

Key Hazards & Mitigation (The 'What If'):

- Heavy Equipment Operation: If working near a running excavator or generator, assume noise levels exceed 90 dBA and wear protection.
- Concrete Breaking/Chipping: If a crew is using jackhammers or chipping guns, dual protection (plugs + muffs) may be required depending on the equipment's decibel rating.
- Improper Fit: If foam earplugs are just pushed into the ear canal without being rolled and properly inserted, they offer almost zero protection. Foremen must train on the 'roll, pull, and hold' insertion method.

FIELD INSTRUCTION — Execution

FIELD INSTRUCTION: Foremen must demonstrate proper earplug insertion. Ensure an adequate supply of hearing protection is available in the gang box. Log attendance on MISH-F-10.1.

Attendance Roster (Log on MISH-F-10.1):

Print Name	Signature	Company/Trade