



CONTROLLED ENTERPRISE DOCUMENT

TBT-07.01 | Leading Edge Work And Barricades

MH Construction, INC Enterprise Management System

Document family: TOOLBOX TALK LIBRARY

Document title: TBT-07.01 | Leading Edge Work And Barricades

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

TBT-07.01: Leading Edge Work & Barricades

CSI Division: Div 07 | OSHA Reference: 29 CFR 1926.501

Delivery: Mandatory for crews working near unprotected roof edges, floor openings, or elevator shafts.

DIRECTIVE — Policy Standard

Any unprotected edge 6 feet or higher above a lower level must be protected by a guardrail system, safety net, or personal fall arrest system (PFAS).

GENERAL ORDER — Procedure

Warning line systems may only be used on low-slope roofs and must be erected at least 6 feet from the edge. Workers outside the warning line must be tied off.

Key Hazards & Mitigation (The 'What If'):

- Floor Hole Covers: If a 2x2 floor penetration is cut for ductwork, it must be immediately covered with 3/4-inch plywood, secured against displacement, and painted with the word 'HOLE' in high-visibility paint.
- Guardrail Removal: If a drywall crew removes a section of perimeter cable to load materials, they must tie off with a PFAS while the cable is down, and replace the cable immediately after loading.
- Swing Fall Hazard: If a worker is tied off to an anchor point 20 feet away from the leading edge and falls, they will swing like a pendulum and strike the lower structure. Keep the anchor point directly overhead.

FIELD INSTRUCTION — Execution

FIELD INSTRUCTION: Foremen must inspect all floor hole covers and perimeter cables in their work zone at the start of the shift. Repair any loose cables immediately. Log attendance on MISH-F-10.1.

Attendance Roster (Log on MISH-F-10.1):

Print Name	Signature	Company/Trade