



CONTROLLED ENTERPRISE DOCUMENT

TBT-08.01 | Ladder Safety And Three Point Contact

MH Construction, INC Enterprise Management System

Document family: TOOLBOX TALK LIBRARY

Document title: TBT-08.01 | Ladder Safety And Three Point Contact

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

TBT-08.01: Ladder Safety & Three-Point Contact

CSI Division: Div 08 | OSHA Reference: 29 CFR 1926.1053
Delivery: Mandatory for all crews utilizing A-frame or extension ladders.

DIRECTIVE — Policy Standard

Ladders must be inspected before each use. Workers must maintain three points of contact (two hands and one foot, or two feet and one hand) while ascending or descending.

GENERAL ORDER — Procedure

Do not carry tools or materials in your hands while climbing; use a tool belt or a hoist line. The top step and top cap of an A-frame ladder are not steps—do not stand on them.

Key Hazards & Mitigation (The 'What If'):

- Overreaching: If a worker leans out past the side rails to reach a junction box, the ladder's center of gravity shifts and it will tip. Keep your belt buckle between the rails.
- Uneven Ground: If setting a ladder on uneven concrete, do not use scrap wood or bricks to level the legs. Use a ladder with factory-installed leg levelers.
- Extension Ladder Angle: If an extension ladder is set too steep, it will tip backward. If set too shallow, the feet will kick out. Use the 4-to-1 rule: 1 foot out for every 4 feet up.

FIELD INSTRUCTION — Execution

FIELD INSTRUCTION: Foremen must instruct crews to inspect all ladders today and destroy any with bent rails or missing rivets. Log attendance on MISH-F-10.1.

Attendance Roster (Log on MISH-F-10.1):

Print Name	Signature	Company/Trade