



CONTROLLED ENTERPRISE DOCUMENT

TBT-09.01 | Powder Actuated Tools Ramset

MH Construction, INC Enterprise Management System

Document family: TOOLBOX TALK LIBRARY

Document title: TBT-09.01 | Powder Actuated Tools Ramset

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

TBT-09.01: Powder-Actuated Tools (Ramset)

CSI Division: Div 09 | OSHA Reference: 29 CFR 1926.302(e)
Delivery: Mandatory for framing, drywall, and MEP crews anchoring to concrete or steel.

DIRECTIVE — Policy Standard

Only employees who have been trained and certified by the tool manufacturer may operate powder-actuated tools. The certification card must be on their person.

GENERAL ORDER — Procedure

Tools must not be loaded until just prior to firing. If the tool misfires, hold it firmly against the work surface for 30 seconds before removing it, then extract the cartridge and place it in water.

Key Hazards & Mitigation (The 'What If'):

- Spalling Concrete: If firing into hard concrete, fragments will spall and fly backward. Safety glasses and a face shield are mandatory.
- Firing Near the Edge: If firing a pin less than 3 inches from the edge of a concrete slab, the concrete will blow out and the pin will fly free. Maintain minimum edge distances.
- Blind Penetration: If firing into a wall where the exact thickness or backing material is unknown, the pin may pass completely through and strike someone on the other side. Verify the substrate.

FIELD INSTRUCTION — Execution

FIELD INSTRUCTION: Foremen must verify the certification cards of all operators and ensure misfire water buckets are staged before work begins. Log attendance on MISH-F-10.1.

Attendance Roster (Log on MISH-F-10.1):

Print Name	Signature	Company/Trade