



CONTROLLED ENTERPRISE DOCUMENT

TBT-11.05 | Manual Material Handling And Ergonomics

MH Construction, INC Enterprise Management System

Document family: TOOLBOX TALK LIBRARY

Document title: TBT-11.05 | Manual Material Handling And Ergonomics

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

TBT-11.05: Manual Material Handling & Ergonomics

CSI Division: Div 11 | OSHA Reference: 29 CFR 1926.20

Delivery: Mandatory for all crews involved in manual loading, unloading, or staging of materials.

DIRECTIVE — Policy Standard

Employees must assess the weight and shape of a load before lifting. Any load exceeding 50 lbs requires a two-person team lift or mechanical assistance (dolly, pallet jack, forklift).

GENERAL ORDER — Procedure

When lifting, keep the load close to the body, bend at the knees, and lift with the legs—never the back. Do not twist the torso while carrying a load; pivot with your feet.

Key Hazards & Mitigation (The 'What If'):

- Awkward Shapes: If a worker needs to move a 40 lb piece of ductwork that is 10 feet long, the awkward shape makes it a two-person lift despite being under the 50 lb limit.
- Repetitive Stacking: If a crew is hand-unloading a truck of block, rotate tasks every hour to prevent fatigue. Use a conveyor or staging table to keep the work between knee and shoulder height.
- Dropped Loads: If a heavy load slips from your grip, let it fall. Do not attempt to catch it awkwardly, which causes severe back and shoulder injuries. Step back and let it drop.

FIELD INSTRUCTION — Execution

FIELD INSTRUCTION: Foremen must identify all heavy lifts scheduled for today's shift and assign team lifts or mechanical aids before work begins. Log attendance on MISH-F-10.1.

Attendance Roster (Log on MISH-F-10.1):

Print Name	Signature	Company/Trade