



CONTROLLED ENTERPRISE DOCUMENT

TBT-31.04 | Traffic Control And Flagger Safety

MH Construction, INC Enterprise Management System

Document family: TOOLBOX TALK LIBRARY

Document title: TBT-31.04 | Traffic Control And Flagger Safety

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

TBT-31.04: Traffic Control & Flagger Safety

CSI Division: Div 31 | OSHA Reference: MUTCD Part 6

Delivery: Mandatory for all crews working in or adjacent to public roadways.

DIRECTIVE — Policy Standard

All flaggers must be certified and wear ANSI Class 3 high-visibility apparel. Traffic control zones must be established with proper advance warning signs before work begins.

GENERAL ORDER — Procedure

Flaggers must stand on the shoulder or in the barricaded lane—never in the open traffic lane. They must maintain an escape route at all times and never turn their back to oncoming traffic.

Key Hazards & Mitigation (The 'What If'):

- Aggressive Driver: If a driver ignores the STOP paddle and breaches the work zone, the flagger must blow their warning whistle to alert the crew and utilize their escape route. Do not try to block the vehicle.
- Night Operations: If the pour extends past dusk, Class 3 apparel and illuminated STOP/SLOW paddles are mandatory. The flagger station must be illuminated by a light plant.
- Distracted Flagger: If a flagger is looking at their phone, they are a liability to the entire crew. Foremen must remove distracted flaggers from the roadway immediately.

FIELD INSTRUCTION — Execution

FIELD INSTRUCTION: Foremen must verify that all advance warning signs (e.g., 'Road Work Ahead') are properly spaced according to the speed limit before work starts. Log attendance on MISH-F-10.1.

Attendance Roster (Log on MISH-F-10.1):

Print Name	Signature	Company/Trade