



CONTROLLED ENTERPRISE DOCUMENT

SDS-QR-03 | Spray Polyurethane Foam

MH Construction, INC Enterprise Management System

Document family: SDS LIBRARY

Document title: SDS-QR-03 | Spray Polyurethane Foam

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

SDS Quick Reference: Spray Polyurethane Foam (SPF) - Part A (Isocyanate)

Manufacturer: Various

DIRECTIVE — Hazard Identification

DANGER: Harmful if inhaled. Causes skin and eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Sensitizer.

GENERAL ORDER — First Aid Measures

- **INHALATION:** Move to fresh air immediately. Administer oxygen if breathing is difficult.
- **EYES:** Flush immediately with water for 15 minutes.
- **SKIN:** Wash thoroughly with soap and water.

FIELD INSTRUCTION — Required PPE

FIELD INSTRUCTION: *Wear full-face supplied-air respirator (SAR), chemical-resistant suit, and nitrile gloves during application. Restrict access to area for 24 hours post-application.*