



CONTROLLED ENTERPRISE DOCUMENT

SDS-QR-07 | Acetylene Gas

MH Construction, INC Enterprise Management System

Document family: SDS LIBRARY

Document title: SDS-QR-07 | Acetylene Gas

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

SDS Quick Reference: Acetylene Gas (Compressed)

Manufacturer: Various (Airgas, Praxair, etc.)

DIRECTIVE — Hazard Identification

DANGER: Extremely flammable gas. Contains gas under pressure; may explode if heated. May displace oxygen and cause rapid suffocation. Forms explosive mixtures with air.

GENERAL ORDER — First Aid Measures

- **INHALATION:** Move to fresh air. If not breathing, give artificial respiration.
- **SKIN/EYES:** Contact with rapidly expanding gas may cause frostbite. Thaw frosted parts with lukewarm water.
- **FIRE:** Stop leak if safe to do so. Extinguish with dry chemical or CO2.

FIELD INSTRUCTION — Required PPE

FIELD INSTRUCTION: *Wear leather welding gloves, flame-resistant clothing, and welding goggles/helmet. Keep cylinders upright and secured. Store at least 20 feet away from oxygen cylinders.*