



CONTROLLED ENTERPRISE DOCUMENT

SDS-QR-09 | Hydraulic Fluid

MH Construction, INC Enterprise Management System

Document family: SDS LIBRARY

Document title: SDS-QR-09 | Hydraulic Fluid

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

SDS Quick Reference: Heavy Equipment Hydraulic Fluid (AW 46)

Manufacturer: Various (Mobil, Shell, etc.)

DIRECTIVE — Hazard Identification

WARNING: May cause skin irritation. High-pressure injection under the skin is a medical emergency and can cause severe tissue damage or amputation. Combustible liquid.

GENERAL ORDER — First Aid Measures

- **SKIN:** Wash thoroughly with soap and water. If injected under skin, seek immediate surgical treatment.
- **EYES:** Flush with water for 15 minutes.
- **SPILL:** Contain spill with absorbent materials. Do not flush to sewer.

FIELD INSTRUCTION — Required PPE

***FIELD INSTRUCTION:** Wear nitrile or neoprene gloves and safety glasses when checking fluid levels or replacing hoses. Keep spill kit accessible.*