



CONTROLLED ENTERPRISE DOCUMENT

SDS-QR-10 | Propane Lpg

MH Construction, INC Enterprise Management System

Document family: SDS LIBRARY

Document title: SDS-QR-10 | Propane Lpg

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

SDS Quick Reference: Propane (Liquefied Petroleum Gas - LPG)

Manufacturer: Various (AmeriGas, Ferrellgas, etc.)

DIRECTIVE — Hazard Identification

DANGER: Extremely flammable gas. Contains gas under pressure; may explode if heated. May cause frostbite upon contact with rapidly expanding gas. Asphyxiant in high concentrations.

GENERAL ORDER — First Aid Measures

- **INHALATION:** Move to fresh air. If breathing is difficult, administer oxygen.
- **SKIN:** Thaw frosted parts with lukewarm water. Do not rub.
- **FIRE:** Do not extinguish leaking gas fire unless leak can be stopped safely.

FIELD INSTRUCTION — Required PPE

***FIELD INSTRUCTION:** Wear leather gloves and safety glasses when changing forklift propane cylinders. Store cylinders upright in a secure, well-ventilated outdoor cage.*