



CONTROLLED ENTERPRISE DOCUMENT

SDS-QR-11 | Lead Acid Batteries

MH Construction, INC Enterprise Management System

Document family: SDS LIBRARY

Document title: SDS-QR-11 | Lead Acid Batteries

Version: 1.0 | Lifecycle: Rough Draft

Use only after required functional, technical, field-usability, and approval gates are complete.

Control: Version 1.0 | Status Rough Draft | Author and Chief Editor: Matt Ramsey | Co-Editor: Todd Shoeff | Final Approver: Jeremy Thamert

SDS Quick Reference: Lead-Acid Batteries (Wet, Filled with Acid)

Manufacturer: Various (Interstate, Deka, etc.)

DIRECTIVE — Hazard Identification

DANGER: Contains sulfuric acid. Causes severe skin burns and eye damage. May form explosive hydrogen gas during charging. Contains lead (toxic).

GENERAL ORDER — First Aid Measures

- **EYES:** Flush immediately with water for at least 15 minutes. Seek medical attention.
- **SKIN:** Remove contaminated clothing. Flush skin with water.
- **SPILL:** Neutralize acid spills with baking soda (sodium bicarbonate).

FIELD INSTRUCTION — Required PPE

FIELD INSTRUCTION: *Wear chemical-resistant apron, acid-resistant gloves, and a face shield when handling leaking batteries or adding water during charging.*