```python
import numpy as np

# AND data
X = np.array([
    [0,0],
    [0,1],
    [1,0],
    [1,1]
])

y = np.array([0,0,0,1])

# Parameters
w = np.array([0.1, 0.2])
b = 0.3
lr = 0.1

def sigmoid(z):
    return 1/(1+np.exp(-z))

# Training
for epoch in range(1000):
    for i in range(len(X)):
        z = np.dot(X[i], w) + b
        y_pred = sigmoid(z)

        # BCE + Sigmoid gradient shortcut
        dz = y_pred - y[i]
        dw = dz * X[i]
        db = dz
        w -= lr * dw
        b -= lr * db

print("Weights:", w)
print("Bias:", b)
```

```
Weights: [5.60154076 5.59544869]
Bias: -8.565987677634602
```


```python
import numpy as np

# AND data
X = np.array([
    [0,0],
    [0,1],
    [1,0],
    [1,1]
])

y = np.array([0,0,0,1])

# Parameters
w = np.array([0.1, 0.2])
b = 0.3
lr = 0.1

def sigmoid(z):
    return 1/(1+np.exp(-z))

# Training
for epoch in range(1000):
    for i in range(len(X)):
        z = np.dot(X[i], w) + b
        y_pred = sigmoid(z)

        # BCE + Sigmoid gradient shortcut
        dz = y_pred - y[i]
        dw = dz * X[i]
        db = dz
        w -= lr * dw
        b -= lr * db

print("Weights:", w)
print("Bias:", b)
```

```
Weights: [5.60154076 5.59544869]
Bias: -8.565987677634602
```

```python
import numpy as np

# OR data
X = np.array([
    [0,0],
    [0,1],
    [1,0],
    [1,1]
])

y = np.array([0,1,1,1])

# Parameters
w = np.array([0.1, 0.2])
b = 0.3
lr = 0.1

def sigmoid(z):
    return 1/(1+np.exp(-z))

# Training
for epoch in range(1000):
    for i in range(len(X)):
        z = np.dot(X[i], w) + b
        y_pred = sigmoid(z)

        # BCE + Sigmoid gradient shortcut
        dz = y_pred - y[i]
        dw = dz * X[i]
        db = dz
        w -= lr * dw
        b -= lr * db

print("Weights:", w)
print("Bias:", b)
```

```
Weights: [6.7832796  6.78742098]
Bias: -2.9139465005185365
```

```python
import numpy as np
import matplotlib.pyplot as plt

# Gate data
X = [(0,0),(0,1),(1,0),(1,1)]
Y_AND = [0,0,0,1]
Y_OR  = [0,1,1,1]

# Sigmoid
def sigmoid(z):
    return 1/(1+np.exp(-z))

# training function (same step style)
def train_gate(Y, lr):

    w1, w2, b = 0.2, -0.3, 0.4
    losses = []

    for epoch in range(50):
        total_loss = 0

        for (x1,x2), y in zip(X,Y):

            # Forward
            z = w1*x1 + w2*x2 + b
            y_pred = sigmoid(z)

            loss = 0.5*(y_pred-y)**2
            total_loss += loss

            # Backprop
            dL_dy_pred = y_pred - y
            dy_pred_dz = y_pred*(1-y_pred)
            dL_dz = dL_dy_pred * dy_pred_dz
```

```

            dL_dw1 = dL_dz * x1
            dL_dw2 = dL_dz * x2
            dL_db  = dL_dz

            # Update
            w1 -= lr*dL_dw1
            w2 -= lr*dL_dw2
            b  -= lr*dL_db

        losses.append(total_loss)

    return losses

learning_rates = [0.1,0.5,1]

# AND plot
plt.figure()
for lr in learning_rates:
    losses = train_gate(Y_AND, lr)
    plt.plot(losses,label=f"lr={lr}")
plt.title("AND Gate Loss")
plt.legend()
plt.show()
```




```
plt.figure()
for lr in learning_rates:
    losses = train_gate(Y_OR, lr)
    plt.plot(losses,label=f"lr={lr}")
plt.title("OR Gate Loss")
plt.legend()
plt.show()
```


OR Gate Loss
lr=0.1
lr=0.5
lr=1
0.45
0.40
0.35
0.30
0.25
0.20
0.15
0.10
0
10
20
30
40
50