RAJALAKSHMI ENGINEERING COLLEGE

Ramuna Bala T 250701583-2025-CSE

R2

Started on	Saturday, 29 August 2026, 3:04 PM
State	Finished
Completed on	Saturday, 29 August 2026, 3:09 PM
Time taken	4 mins 20 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int a[n], b[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &a[i]);
    }
    for (int i = 0; i < n; i++) {
        scanf("%d", &b[i]);
    }

    for (int i = 0; i < n - 1; i++) {
        for (int j = 0; j < n - i - 1; j++) {
            if (a[j] > a[j + 1]) {
                int temp = a[j];
                a[j] = a[j + 1];
                a[j + 1] = temp;
            }
        }
    }

    for (int i = 0; i < n - 1; i++) {
        for (int j = 0; j < n - i - 1; j++) {
            if (b[j] < b[j + 1]) {
                int temp = b[j];
                b[j] = b[j + 1];
                b[j + 1] = temp;
            }
        }
    }

    long long min_product_sum = 0;
    for (int i = 0; i < n; i++) {
        min_product_sum += (long long)a[i] * b[i];
    }

    printf("%lld", min_product_sum);
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course