Name:Ramya Ajay
Roll No:CB.EN.P2CYS22004
IP LAB ASSIGNMENT -12
Implementing Virtual Private Network

# Task 1: Network Setup

We set up the environment as follows:

```
(<mark>root® kali</mark>)-[~/Labset
docker-compose build
             li)-[~/Labsetup]
VPN_Client uses an image, skipping
Host1 uses an image, skipping
Host2 uses an image, skipping
Router uses an image, skipping
      oot® kali)-[~/Labsetup]
 -# docker-compose up
Creating network "net-10.9.0.0" with the default driver
Creating network "net-192.168.60.0" with the default driver
Pulling VPN_Client (handsonsecurity/seed-ubuntu:large)...
large: Pulling from handsonsecurity/seed-ubuntu
da7391352a9b: Pull complete
14428a6d4bcd: Pull complete
2c2d948710f2: Pull complete
b5e99359ad22: Pull complete
3d2251ac1552: Pull complete
1059cf087055: Pull complete
b2afee800091: Pull complete
c2ff2446bab7: Pull complete
4c584b5784bd: Pull complete
Digest: sha256:41efab02008f016a7936d9cadfbe8238146d07c1c12b39cd63c3e73a0297c07a
Status: Downloaded newer image for handsonsecurity/seed-ubuntu:large
Creating host-192.168.60.6 ... done
Creating host-192.168.60.5 ... done
Creating client-10.9.0.5 ... done
Creating server-router
Attaching to client-10.9.0.5, host-192.168.60.5, server-router, host-192.168.60.6
host-192.168.60.5 | * Starting internet superserver inetd
host-192.168.60.6 | * Starting internet superserver inetd
                                                                               [ OK ]
                                                                               [ ok ]
```

```
(root@ Wali)-[/home/kali]

# docker ps

COMTAINER ID IMAGE
PORTS NAMES

8e8b861b1822 handsonsecurity/seed-ubuntu:large server-router

2adb10cdb40a handsonsecurity/seed-ubuntu:large client-10.9.0.5

a5041b1442c4 handsonsecurity/seed-ubuntu:large host-192.168.60.5

adf271d51dc5 handsonsecurity/seed-ubuntu:large host-192.168.60.6

COMMAND

CREATED
STATUS

When a minute ago
Up About a minute ago
Up About a minute ago
Up About a minute
When a minute ago
Up About a minute
```

### From server to both the hosts

```
root@8e8b861b1822:/# ping 192.168.60.6
PING 192.168.60.6 (192.168.60.6) 56(84) bytes of data.
64 bytes from 192.168.60.6: icmp_seq=1 ttl=64 time=0.180 ms
64 bytes from 192.168.60.6: icmp_seq=2 ttl=64 time=0.054 ms
64 bytes from 192.168.60.6: icmp_seq=3 ttl=64 time=0.049 ms
64 bytes from 192.168.60.6: icmp_seq=4 ttl=64 time=0.050 ms
64 bytes from 192.168.60.6: icmp_seq=5 ttl=64 time=0.061 ms
^C
--- 192.168.60.6 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4075ms
rtt min/avg/max/mdev = 0.049/0.078/0.180/0.050 ms
root@8e8b861b1822:/# ping 192.168.60.5
PING 192.168.60.5 (192.168.60.5) 56(84) bytes of data.
64 bytes from 192.168.60.5: icmp_seq=1 ttl=64 time=0.274 ms
64 bytes from 192.168.60.5: icmp_seq=2 ttl=64 time=0.077 ms
64 bytes from 192.168.60.5: icmp_seq=3 ttl=64 time=0.081 ms
64 bytes from 192.168.60.5: icmp_seq=4 ttl=64 time=0.277 ms
^c
--- 192.168.60.5 ping statistics -
4 packets transmitted, 4 received, 0% packet loss, time 3270ms
rtt min/avg/max/mdev = 0.077/0.177/0.277/0.098 ms
```

### From client to server

```
root@2adb10cdb40a:/# ping 10.9.0.11

PING 10.9.0.11 (10.9.0.11) 56(84) bytes of data.

64 bytes from 10.9.0.11: icmp_seq=1 ttl=64 time=0.172 ms

64 bytes from 10.9.0.11: icmp_seq=2 ttl=64 time=0.091 ms

64 bytes from 10.9.0.11: icmp_seq=3 ttl=64 time=0.049 ms

64 bytes from 10.9.0.11: icmp_seq=4 ttl=64 time=0.057 ms

^C
--- 10.9.0.11 ping statistics ---

4 packets transmitted, 4 received, 0% packet loss, time 3081ms

rtt min/avg/max/mdev = 0.049/0.092/0.172/0.048 ms

root@2adb10cdb40a:/#
```

## Run tcpdump on server to capture all the traffic

```
root@8e8b861b1822:/# tcpdump

tcpdump: verbose output suppressed, use -v or -vv for full protocol decode

listening on eth0, link-type EN10MB (Ethernet), capture size 262144 bytes

13:16:38.239528 IP client-10.9.0.5.net-10.9.0.0 > 8e8b861b1822: ICMP echo request, id 8, seq 1, length

64

13:16:38.239547 IP 8e8b861b1822 > client-10.9.0.5.net-10.9.0.0: ICMP echo reply, id 8, seq 1, length 64

13:16:39.243597 IP client-10.9.0.5.net-10.9.0.0 > 8e8b861b1822: ICMP echo request, id 8, seq 2, length

64

13:16:39.243625 IP 8e8b861b1822 > client-10.9.0.5.net-10.9.0.0: ICMP echo reply, id 8, seq 2, length 64

13:16:40.643062 IP client-10.9.0.5.net-10.9.0.0 > 8e8b861b1822: ICMP echo reply, id 8, seq 3, length

64

13:16:40.643075 IP 8e8b861b1822 > client-10.9.0.5.net-10.9.0.0: ICMP echo reply, id 8, seq 3, length

64

13:16:43.403891 ARP, Request who-has client-10.9.0.5.net-10.9.0.0 tell 8e8b861b1822, length 28

13:16:43.403990 ARP, Request who-has 8e8b861b1822 tell client-10.9.0.5.net-10.9.0.0, length 28

13:16:43.403994 ARP, Reply 8e8b861b1822 is-at 02:42:0a:09:00:0b (oui Unknown), length 28

13:16:43.403996 ARP, Reply client-10.9.0.5.net-10.9.0.0 is-at 02:42:0a:09:00:05 (oui Unknown), length 28
```

Task 2: Create and Configure TUN Interface:

### Task 2.a: Name of the Interface:

### From client -

```
import fcntl
import struct
import os
import time
from scapy.all import *

TUNSETIFF = 0×400454ca
IFF_TUN = 0×0001
IFF_TAP = 0×0002
IFF_NO_PI = 0×1000

# Create the tun interface
tun = os.open("/dev/net/tun", os.O_RDWR)
ifr = struct.pack('16sH', b'shebu%d', IFF_TUN | IFF_NO_PI)
ifname_bytes = fcntl.ioctl(tun, TUNSETIFF, ifr)

# Get the interface name
ifname = ifname_bytes.decode('UTF-8')[:16].strip("\x00")
print("Interface Name: {}".format(ifname))
while True:
    time.sleep(10)
```

```
root@se8b861b1822:/# ip a

1: lo: 

1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 

1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1: lo: 
1:
```

Task 2.b: Set up the TUN Interface: First, we added the ip address manually using the command- ip addr add and command – ip link set up to bring up the interface:

```
root@8e8b861b1822:/# ip addr add 192.168.53.99/24 dev shebu0
                                                                                  root@8e8b861b1822:/
root@8e8b861b1822:/# ip a
                                                                                  # python3 tun.py
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group defa
                                                                                   Interface Name: she
ult qlen 1000
                                                                                  bu0
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
                                                                                  inet 127.0.0.1/8 scope host lo
      valid lft forever preferred lft forever
4: shebu0: <POINTOPOINT,MULTICAST,NOARP> mtu 1500 qdisc noop state DOWN group
default glen 500
   link/none
   inet 192.168.53.99/24 scope global shebu0
      valid_lft forever preferred_lft forever
12: eth1@if13: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state
UP group default
    link/ether 02:42:c0:a8:3c:0b brd ff:ff:ff:ff:ff:ff link-netnsid 0
    inet 192.168.60.11/24 brd 192.168.60.255 scope global eth1
       valid_lft forever preferred_lft forever
14: eth0@if15: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state
UP group default
    link/ether 02:42:0a:09:00:0b brd ff:ff:ff:ff:ff:ff link-netnsid 0
    inet 10.9.0.11/24 brd 10.9.0.255 scope global eth0
       valid lft forever preferred lft forever
root@8e8b861b1822:/#
root@8e8b861b1822:/# ip link set dev shebu0 up
root@8e8b861b1822:/# ip a
                                                                                  root@8e8b861b1822:/
                                                                                   # python3 tun.py
1: lo: <LOOPBACK,UP,LOWER_UP> mtu bbbbb qdisc noqueue state UNKNOWN group defa
                                                                                  Interface Name: she
ult qlen 1000
                                                                                  bu<sub>0</sub>
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid lft forever preferred lft forever
5: shebu0: <POINTOPOINT,MULTICAST,NOARP,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast
 state UNKNOWN group default glen 500
    link/none
12: eth1@i+13: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state
UP group default
    link/ether 02:42:c0:a8:3c:0b brd ff:ff:ff:ff:ff:ff link-netnsid 0
    inet 192.168.60.11/24 brd 192.168.60.255 scope global eth1
       valid_lft forever preferred_lft forever
14: eth0@if15: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noqueue state
```

Also, this is done automatically by adding the commands to the code:

link/ether 02:42:0a:09:00:0b brd ff:ff:ff:ff:ff:ff link-netnsid 0

inet 10.9.0.11/24 brd 10.9.0.255 scope global eth0
 valid\_lft forever preferred\_lft forever

UP group default

root@8e8b861b1822:/#

```
# Create the tun interface
tun = os.open("/dev/net/tun", os.0_RDWR)
ifr = struct.pack('16sH', b'shebu%d', IFF_TUN | IFF_NO_PI)
ifname_bytes = fcntl.ioctl(tun, TUNSETIFF, ifr)

# Get the interface name
ifname = ifname_bytes.decode('UTF-8')[:16].strip("\x00")
print("Interface Name: {}".format(ifname))

os.system("ip addr add 192.168.53.99/24 dev {}".format(ifname))
os.system("ip link set dev {} up".format(ifname))

while True:
    time.sleep(10)
```

```
root@8e8b861b1822:/# ip a

1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN
ult qlen 1000
    link/loopback 00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever

6: shebu0: <POINTOPOINT,MULTICAST,NOARP,UP,LOWER_UP> mtu 1500 qdisc
    state UNKNOWN group default qlen 500
    link/none
    inet 192.168.53.99/24 scope global shebu0
    valid lft forever preferred lft forever

12: eth1@if13: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc noq
```

Task 2.c: Read from the TUN Interface:

Code:

```
ifr = struct.pack( losh , b snebu%d , IFF_ION | IFF_NO_PI)
ifname_bytes = fcntl.ioctl(tun, TUNSETIFF, ifr)

# Get the interface name
ifname = ifname_bytes.decode('UTF-8')[:16].strip("\x00")
print("Interface Name: {}".format(ifname))

os.system("ip addr add 192.168.53.99/24 dev {}".format(ifname))
os.system("ip link set dev {} up".format(ifname))

while True:
    packet=os.read(tun, 2048)
    if packet:
        ip=IP(packet)
        print(ip.summary())

while True:
    time.sleep(10)
```

First, On Host U, we ping a host in the 192.168.53.0/24 network. Specifically, we ping the 192.168.53.1 network. As the interface is not yet configured to get a reply back, we can see that packets were not received back. However, being in the same LAN network, the packets get sent successfully.

```
root@deeb5999b181:/# ip a
1: los :GOOPMACK_UP_LOWER_UP> mtu 65336 ddisc noqueue state UNCNOWN group default to control of the control of the
```

Now, on Host U, we ping a host in the internal network 192.168.60.0/24. Specifically, we ping the 192.168.60.5 network. Similar to before, we can see that no packets are received. However, in this case, no packets were sent out as well due to which the client side screen is blank as it tried sending out packets to network outside of the host network which is unreachable

```
root@deeb5999b181:/# ping 192.168.60.5

PING 192.168.60.5 (192.168.60.5) 56(84) bytes of data.

^C
--- 192.168.60.5 ping statistics ---
18 packets transmitted, 0 received, 100% packet loss, time 17409ms

root@deeb5999b181:/#
```

Task 2.d: Write to the TUN Interface

We modified the code so that a spoofed packet is sent out with src IP as 192.168.53.3:

```
while True:
    packet = os.read(tun, 2048)
    if packet:
        ip = IP(packet)
        print(ip.summary)

newip = IP(src='192.168.53.3', dst=ip.src)
        newpkt = newip/ip.payload
        os.write(tun, bytes(newpkt))
```

We run the code to see that packets were sent and received successfully

Instead of writing an IP packet to the interface, we modify the code to write some arbitrary data to the interface to send it as bytes:

```
while True:
    packet = os.read(tun, 2048)
    if packet:
        ip = IP(packet)
        print(ip.summary)

    newip = IP(src='192.168.53.3', dst=ip.src)
        newpkt = newip/ip.payload
        arb_data = b'Any arbitrary data'
        os.write(tun, arb_data)
```

We run the code to see the output as follows:



Task 3: Send the IP Packet to VPN Server Through a Tunnel Tun-server.py code:

