

Name

CWID

Quiz 2

Due Saturday April 25th, 11:59am

CS525 - Advanced Database Organization Spring 2020 Grading Guidelines

Please leave this empty! 1

2

Sum

Instructions

- **You have to upload the assignment to the course blackboard.**
- This is an individual and not a group assignment. Fraud will result in **0** points
- For your convenience the number of points for each part and questions are shown in parenthesis.
- There are **2** parts in this quiz
 1. Result Size Estimations
 2. I/O Cost Estimation

Part 1 Result Size Estimations (Total: 25 Points)

Consider a table **student** with attributes **CWID**, **name**, **major**, **credits**, a table **course** with **title**, **instructor**, **credits**, and a table **registered** with attributes **student** and **course**. **registered.student** is a foreign key to **CWID**. Attribute **course** of relation **registered** is a foreign key to attribute **title** of relation **course**. Given are the following statistics:

$T(\text{student}) = 40,000$	$T(\text{course}) = 1,000$	$T(\text{registered}) = 20,000$
$V(\text{student}, \text{CWID}) = 40,000$	$V(\text{course}, \text{title}) = 1,000$	$V(\text{registered}, \text{student}) = 5,000$
$V(\text{student}, \text{name}) = 39,600$	$V(\text{course}, \text{instructor}) = 500$	$V(\text{registered}, \text{course}) = 100$
$V(\text{student}, \text{major}) = 50$	$V(\text{course}, \text{credits}) = 59$	
$V(\text{student}, \text{credits}) = 59$		

Assume the range $[0,90]$ for the **credits**.

Question 1.1 Estimate Result Size (5 Points)

Estimate the number of result tuples for the query $q = \sigma_{\text{instructor}=\text{Bob}}(\text{course})$ using the first assumption presented in class (values used in queries are uniformly distributed within the active domain).

Solution

$$T(q) = \frac{T(\text{course})}{V(\text{course}, \text{instructor})} = \frac{1,000}{500} = 2$$

Correction Guideline

5 Points for showing or using the correct formula

Question 1.2 Estimate Result Size (5 Points)

Estimate the number of result tuples for the query $q = \sigma_{\text{major}=\text{CS} \vee \text{major}=\text{EE}}(\text{students})$ using the first assumption presented in class.

Solution

$$T(q) = \frac{2 \cdot T(\text{student})}{V(\text{student}, \text{major})} = \frac{2 \cdot 40,000}{50} = 1,600$$

This answer is acceptable too. In case, students assume both predicates are independent:

$$\begin{aligned} T(q_1) &= (1 - [(1 - \frac{1}{V(\text{student}, \text{major})}) \cdot (1 - \frac{1}{V(\text{student}, \text{major})})]) \cdot T(\text{student}) \\ &= (1 - (1 - \frac{1}{50}) \cdot (1 - \frac{1}{50})) \cdot 40,000 = 1,584 \end{aligned}$$

Correction Guideline

5 Points for showing or using the correct formula

Question 1.3 Estimate Result Size (7 Points)

Estimate the number of result tuples for the query $q = \sigma_{credits \geq 39 \wedge credits \leq 44}(course)$ using the first assumption presented in class.

Solution

$$T(q) = \frac{(44 - 39 + 1) \cdot T(course)}{\max(course, credits) - \min(course, credits) + 1} = \frac{6 \cdot 1000}{90 - 0 + 1} = 66$$

Correction Guideline

7 Points for correct formula

Question 1.4 Estimate Result Size (8 Points)

Estimate the number of result tuples for the query q below using the first assumption presented in class.

$$q = \sigma_{credits \geq 30}(student) \bowtie_{CWID=student} registered \bowtie_{course=title} course$$

Solution

$$q_1 = \sigma_{credits \geq 30}(student)$$

$$\begin{aligned} T(q_1) &= \frac{\max(student, credits) - 30 + 1}{\max(student, credits) - \min(student, credits) + 1} \cdot T(student) \\ &= \frac{90 - 30 + 1}{90 + 1} \cdot 40,000 = 26,813 \end{aligned}$$

$$q_2 = q_1 \bowtie_{CWID=student} registered$$

$$\begin{aligned} T(q_2) &= \frac{T(q_1) \cdot T(registered)}{\max(V(q_1, CWID), V(registered, student))} \\ &= \frac{26,813 \cdot 20,000}{\max(26,813, 5,000)} = 20,000 \end{aligned}$$

Thus,

$$q = q_2 \bowtie_{course=title} course$$

$$\begin{aligned} T(q) &= \frac{T(q_2) \cdot T(course)}{\max(V(q_2, course), V(course, title))} \\ &= \frac{20,000 \cdot 1,000}{\max(100, 1,000)} = 20,000 \end{aligned}$$

Correction Guideline

8 Points for correct formula

Part 2 I/O Cost Estimations (Total: 30 Points)

Question 2.1 External Sorting (5 Points)

You have a block of size of 128KB and 2GB memory. Compute the maximum size of file that can be sorted by 3-Pass Multiway Sort.

Solution

$$M = \frac{2,097,152k}{128k} = 16,384 \text{ buffers}$$

$$\begin{aligned} B(R) &\leq M \cdot (M - 1)^2 \text{blocks} \\ &\leq 16,384 \cdot (16,384 - 1)^2 \\ &\leq 16,384 \cdot (16,384 - 1)^2 \cdot 128K \end{aligned}$$

Correction Guideline

5 Points for showing or using the correct formula

Question 2.2 I/O Cost Estimation (25 Points)

Consider two unordered, non-clustered relations R and S with $B(R) = 200,000$ and $B(S) = 2,000$ blocks, and $S(R) = \frac{1}{20}$, and $S(S) = \frac{1}{10}$. You have $M = 101$ memory pages available. Let R has an index on the joining attribute C . Compute the minimum number of I/O operations needed to join these two relations using **tuple-based-nested-loop join** (relations are not clustered), **block-nested-loop join** (relations are clustered), **merge-join** (the inputs are not sorted but contiguous), and **non-clustering index-join** (read of S with uniform distribution assumption and expected 20 matching tuples on R for S) and **hash-join** (relations are contiguous but not sorted). You can assume that the hash function evenly distributes keys across buckets. Justify your result by showing the I/O cost estimation for each join method.

Solution

- $T(R) = 200,000 \times 20 = 4,000,000$
- $T(S) = 2,000 \times 10 = 20,000$
- **TNL:**
 - S : Smaller relation as outer relation (better performance)
 $T(S) \times (1 + T(R)) = 20,000 \times (1 + 4,000,000) = 80,000,020,000$ I/Os
 - or R : Larger relation as outer relation
 $T(R) \times (1 + T(S)) = 4,000,000 \times (1 + 20,000) = 80,004,000,000$ I/Os
- **BNL:** S is smaller, thus, keep chunks of S in memory.
 - 100 buffers for S , 1 buffer for R
 - Cost for each S chunk:
read chunk: 100 I/Os
read R : 200,000 I/Os
 - $\frac{B(S)}{M-1} = \frac{2,000}{100} = 20$ S chunks
 - Total I/O cost is $20 \times (100 + 200,000) = 4,002,000$ I/Os
- **MJ:**
 - Sort cost R by 3-Pass Multiway Join algorithm $= 6 \times B(R)$
 - Sort cost S by 2-Pass Multiway Join algorithm $= 4 \times B(S)$
 - Total cost = sort cost + join cost $= 7 \times B(R) + 5 \times B(S) = 7 \times 200,000 + 4 \times 2,000 = 1,410,000$ I/Os
- **IJ:** $T(S) + T(S) \cdot \frac{T(R)}{V(R,C)} = 20,000 + (20,000 \cdot 20) = 420,000$ I/Os
- **HJ:** $3 \cdot (B(R) + B(S)) = 3 \cdot (200,000 + 2,000) = 606,000$ I/Os

Correction Guideline

5 Points for each subquestion.