

S.No: 1	Exp. Name: <b>sample programs on operator precedence and associativity</b>	Date: 2023-09-14
---------	--	------------------

**Aim:**

Write a java program to demonstrate operator precedence and associativity

**Source Code:**

OperatorPrecedence.java
<pre>import java.util.Scanner; class OperatorPrecedence {     public static void main(String args[])     {         int x,result;         Scanner sc = new Scanner(System.in);         System.out.print("Enter a num: ");         x=sc.nextInt();         result=x++ +x++*-- x/x++- --x+3&gt;&gt;1 2;         System.out.println("The operation going is x++ + x++ * --x / x++ - --x + 3 &gt;&gt; 1   2");         System.out.println("result = "+result);     } }</pre>

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
Enter a num:
4
The operation going is x++ + x++ * --x / x++ - --x + 3 >> 1   2
result = 3

Test Case - 2
<b>User Output</b>
Enter a num:
-3
The operation going is x++ + x++ * --x / x++ - --x + 3 >> 1   2
result = 2

<b>S.No: 2</b>	Exp. Name: <b><i>Sample program on java to demonstrate Control structures</i></b>	<b>Date: 2023-09-14</b>
----------------	---	-------------------------

**Aim:**

write a java program that uses if-else control statement and print the result

**Source Code:**

Control.java

```
import java.util.Scanner; class Control
{
    public static void main(String args[])
    {
        int x,y,sum;
        Scanner sc = new Scanner(System.in);
        System.out.print("Enter first num : ");
        x=sc.nextInt(); System.out.print ("Enter second num : ");
        y=sc.nextInt();
        sum=x+y;
        if(sum==20)
        System.out.println("x + y is equal to 20");
        else if(sum<20)
        System.out.println("x + y is less than 20");
        else
        System.out.println("x + y is greater than 20");
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
Enter first num :
13
Enter second num :
5
x + y is less than 20

Test Case - 2
<b>User Output</b>
Enter first num :
24
Enter second num :
10
x + y is greater than 20

<b>S.No: 3</b>	Exp. Name: <b><i>Sample Program to demonstrate constructor</i></b>	<b>Date: 2023-11-30</b>
----------------	--	-------------------------

**Aim:**

Write a program to demonstrate constructor class

**Source Code:**

Student.java

```
class Student {
    int id;
    String name;
    void display() {
        System.out.println(id+" "+name);
    }
    public static void main(String args[]) {
        Student s1=new Student();
        Student s2=new Student();
        s1.display();
        s2.display();
    }
};
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
0 null
0 null

S.No: 4	Exp. Name: <i>Sample program to demonstrate destructor</i>	Date: 2023-11-30
---------	--	------------------

**Aim:**

Write a program to demonstrate destructor class

**Source Code:**

DestructorExample.java

```
public class DestructorExample {
    public static void main(String[] args) {
        DestructorExample de = new DestructorExample ();
        de.finalize();
        de = null;
        System.gc();
        System.out.println("Inside the main() method");
    }
    protected void finalize(){
        System.out.println("Object is destroyed by the Garbage Collector");
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
Object is destroyed by the Garbage Collector
Inside the main() method
Object is destroyed by the Garbage Collector

S.No: 5	Exp. Name: <b>A program to print Half pyramid pattern</b>	Date: 2023-09-14
---------	---	------------------

**Aim:**

Write a Java program to print Half Pyramid pattern.

**Source Code:**

HalfPyramid.java

```
import java.util.Scanner;
class HalfPyramid
{
    public static void main(String args[])
    {
        int num;
        Scanner sc = new Scanner(System.in);
        System.out.print("Enter no of rows : ");
        num=sc.nextInt();
        for(int i=1;i<=num;i++)
        {
            for(int j=1;j<=i;j++)
            {
                System.out.print("* ");
            }
            System.out.println();
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
Enter no of rows :
5
*
* *
* * *
* * * *
* * * * *

Test Case - 2
<b>User Output</b>
Enter no of rows :
3
*
* *
* * *

Test Case - 3
User Output
Enter no of rows :
10
*
* *
* * *
* * * *
* * * * *
* * * * * *
* * * * * * *
* * * * * * * *
* * * * * * * * *
* * * * * * * * * *
* * * * * * * * * *

S.No: 6	Exp. Name: <b>A program to print Inverted Half pyramin pattern</b>	Date: 2023-09-14
---------	--	------------------

**Aim:**

Write a Program to Print Inverted Half Pyramid Pattern

**Source Code:**

HalfPyramidRev.java

```
import java.util.Scanner;
class HalfPyramidRev
{
    public static void main(String args[])
    {
        int num,i,j;
        Scanner sc = new Scanner(System.in);
        System.out.print("Enter no of rows : ");
        num=sc.nextInt();
        for(i=num;i>=1;i--)
        {
            for(j=i;j>=1;j--)
            {
                System.out.print("* ");
            }
            System.out.println();
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
Enter no of rows :
5
* * * * *
* * * *
* * *
* *
*

Test Case - 2
<b>User Output</b>
Enter no of rows :
3
* * *
* *
*

<b>S.No: 7</b>	Exp. Name: <b><i>A program to print Hollow Inverted Half Pyramid Pattern</i></b>	<b>Date: 2023-09-14</b>
----------------	--	-------------------------

Page No: 8

ID: 224G1A0582

2022-2026-CSE-B

Srinivasa Ramanujan Institute of Technology

**Aim:**

Write a Program to Print Hollow Inverted half Pyramid Pattern

**Source Code:**

HollowHalfPyramidRev.java

```
import java.util.Scanner;
class HollowHalfPyramidRev
{
    public static void main(String args[])
    {
        int num,i,j;
        Scanner sc = new Scanner(System.in);
        System.out.print("Enter no of rows : ");
        num=sc.nextInt();
        for(i=num;i>=1;i--)
        {
            if (i==num || i==1)
            {
                for(j=i;j>=1;j--)
                {
                    System.out.print("* ");
                }
            }
            else
            {
                for(j=i;j>=1;j--)
                {
                    if(j==i || j==1)
                        System.out.print("* ");
                    else
                        System.out.print("  ");
                }
            }
            System.out.println();
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
Enter no of rows :
5
* * * * *



* *
* *
*

Test Case - 2
User Output
Enter no of rows :
3
* * *
* *
*

**Aim:**

Write a Program to Print Pyramid Pattern

**Source Code:**

Pyramid.java

```
import java.util.Scanner;
class Pyramid
{
    public static void main(String args[])
    {
        int num,i,j;
        Scanner sc = new Scanner(System.in);
        System.out.print("Enter no of rows : ");
        num=sc.nextInt();
        for(i=1;i<=num;i++)
        {
            for(j=1;j<=num;j++)
            {
                if(j<=num-i)
                    System.out.print(" ");
                else
                    System.out.print("* ");
            }
            System.out.println();
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
Enter no of rows :
5
*
* *
* * *
* * * *
* * * * *

Test Case - 2
User Output
Enter no of rows :
6
*
* *

* * *
* * * *
* * * * *
* * * * * *

**Aim:**

Write a Program to Print inverted Pyramid Pattern

**Source Code:**

PyramidRev.java

```
import java.util.Scanner;
class PyramidRev
{
    public static void main(String args[])
    {
        int num,i,j;
        Scanner sc = new Scanner(System.in);
        System.out.print("Enter no of rows : ");
        num=sc.nextInt();
        for(i=num;i>=1;i--)
        {
            for(j=1;j<=num;j++)
            {
                if(j>num-i)
                    System.out.print("* ");
                else
                    System.out.print(" ");
            }
            System.out.println();
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
Enter no of rows :
5
* * * * *
* * * *
* * *
* *
*

Test Case - 2
User Output
Enter no of rows :
6

* * * * *
* * * * *
* * *
* *
*

**Aim:**

Write a Program to print the Hollow pyramid pattern

**Source Code:**

PyramidGap.java

```
import java.util.Scanner;
class PyramidGap
{
    public static void main(String args[])
    {
        int num,i,j;
        Scanner sc = new Scanner(System.in);
        System.out.print("Enter no of rows : ");
        num=sc.nextInt();
        for(i=1;i<=num;i++)
        {
            if(i!=num)
            {
                for(j=1;j<=num;j++)
                {
                    if(j<=num-i)
                        System.out.print(" ");
                    else if(j>1+num-i && j<num)
                        System.out.print(" ");
                    else
                        System.out.print("* ");
                }
            }
            else
                for(j=1;j<=num;j++)
                    System.out.print("* ");
            System.out.println();
        }
    }
}
```

Execution Results - All test cases have succeeded!	
Test Case - 1	
User Output	
Enter no of rows :	
5	
*	
* *	
*  *	
*    *	
* * * *	

Test Case - 2
<b>User Output</b>
Enter no of rows :
6
*
*  *
*     *
*         *
*             *
*             *
*             *
*             *
*             *

ID: 224G1A0582

Srinivasa Ramanujan Institute of Technology

<b>S.No: 11</b>	Exp. Name: <b>A program to illustrate Inheritance</b>	<b>Date: 2023-10-19</b>
-----------------	---	-------------------------

### Aim:

Write Java program on use of Inheritance.

Create a classVehicle

- contains the data members **color** of String type and **speed** and **size** of integer data type.
- write a method**setVehicleAttributes()**to initialize the data members

Create another classCarwhich is derived from the classVehicle

- contains the data members**cc**and**gearsofinteger**data type
- write a method**setCarAttributes()**to initialize the data members
- write a method**displayCarAttributes()**which will display all the attributes.

Write another class InheritanceDemo with **main()** it receives five arguments **color, speed, size, cc** and **gears**.

### Source Code:

InheritanceDemo.java

```
class Vehicle{
    String color;
    int speed,size;
    void setVehicleAttributes(String co,String sp,String si){
        color=co;
        speed=Integer.parseInt(sp);
        size=Integer.parseInt(si);
    }
}
class Car extends Vehicle{
    int cc,gears;
    void setCarAttributes(String co,String sp,String si,String c,String g){
        setVehicleAttributes(co,sp,si);
        cc=Integer.parseInt(c);
        gears=Integer.parseInt(g);
        displayCarAttributes();
    }
    void displayCarAttributes(){
        System.out.println("Color of Car : "+color);
        System.out.println("Speed of Car : "+speed);
        System.out.println("Size of Car : "+size);
        System.out.println("CC of Car : "+cc);
        System.out.println("No of gears of Car : "+gears);
    }
}
class InheritanceDemo{
    public static void main(String args[]){
        Car c = new Car();
        c.setCarAttributes(args[0],args[1],args[2],args[3],args[4]);
    }
}
```

**Execution Results - All test cases have succeeded!**



Test Case - 1
<b>User Output</b>
Color of Car : Blue
Speed of Car : 100
Size of Car : 20
CC of Car : 1000
No of gears of Car : 5

Test Case - 2
<b>User Output</b>
Color of Car : Orange
Speed of Car : 120
Size of Car : 25
CC of Car : 900
No of gears of Car : 5

S.No: 12	Exp. Name: <i>write a java program to prevent inheritance using abstract class.</i>	Date: 2023-10-19
----------	---	------------------

**Aim:**

write a java program to prevent inheritance using abstract class.

- Create an abstract class `Shape`
- Create a class `Rectangle` which extends the class `Shape`
- Class Rectangle contains a method **draw** whcih prints **drawing rectangle**
- Create another class `circle1` which extends `Shape`
- Class circle1 contains a method **draw** whcih prints **drawing circle**
- Create a main class `TestAbstraction1`
- Create object for the class circle1 and called the method draw

**Source Code:**

TestAbstraction1.java

```

abstract class Shape{
    abstract void draw();
}
class Rectangle extends Shape{
    void draw(){
        System.out.println("drwaing rectangle");
    }
}
class Circle1 extends Shape{
    void draw(){
        System.out.println("drawing circle");
    }
}
class TestAbstraction1{
    public static void main(String args[]){
        Circle1 c = new Circle1();
        c.draw();
    }
}

```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
drawing circle

**Aim:**

write a program on dynamic binding

**Source Code:**

Demo.java

```

class Human {
    void display()
    {
        System.out.println("Human walks");
    }
}
class Boy extends Human{
    void display(){
        System.out.println("Boy walks");
    }
}
class Demo{
    public static void main(String args[])
    {
        Boy b = new Boy();
        Human h = new Human();
        Human hu;
        hu = b;
        hu.display();
        hu = h;
        hu.display();
    }
}

```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
Boy walks
Human walks

<b>S.No: 14</b>	Exp. Name: <b><i>Sample program on method overloading</i></b>	<b>Date: 2023-10-19</b>
-----------------	---	-------------------------

**Aim:**

Write a program on method overloading

**Source Code:**

Sample.java

```
class A{
    String str;
    void display(String a){
        str=a;
        System.out.println(str);
    }
}
class B{
    int num;
    String str;
    void display(String a, int n){
        num=n;
        str=a;
        System.out.println(str+" "+num);
    }
}
class Sample{
    public static void main(String args[])
    {
        A a = new A();
        B b = new B();
        a.display("a");
        b.display("a",10);
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
a
a 10

S.No: 15	Exp. Name: <i>Sample program on method overriding</i>	Date: 2023-10-19
----------	---	------------------

**Aim:**

Write a program on method overriding

**Source Code:**

Bike.java

```
class Vehicle{
    void display(){
        System.out.println("Bike is running safely");
    }
}
class Bike extends Vehicle{
    public static void main(String args[]){
        Bike b = new Bike();
        b.display();
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
Bike is running safely

**Aim:**

Write a Java program that implements an **interface**.

Create an interface called `Car` with two abstract methods `String getName()` and `int getMaxSpeed()`. Also declare one **default** method `void applyBreak()` which has the code snippet

```
System.out.println("Applying break on " + getName());
```

In the same interface include a **static** method `Car getFastestCar(Car car1, Car car2)`, which returns `car1` if the **maxSpeed** of `car1` is greater than or equal to that of `car2`, else should return `car2`.

Create a class called `BMW` which implements the interface `Car` and provides the implementation for the abstract methods `getName()` and `getMaxSpeed()` (make sure to declare the appropriate fields to store **name** and **maxSpeed** and also the constructor to initialize them).

Similarly, create a class called `Audi` which implements the interface `Car` and provides the implementation for the abstract methods `getName()` and `getMaxSpeed()` (make sure to declare the appropriate fields to store **name** and **maxSpeed** and also the constructor to initialize them).

Create a **public** class called `MainApp` with the **main()** method.

Take the input from the command line arguments. Create objects for the classes `BMW` and `Audi` then print the fastest car.

**Note:**

**Java 8** introduced a new feature called `default` methods or `defender` methods, which allow developers to add new methods to the interfaces without breaking the existing implementation of these interface. These **default** methods can also be overridden in the implementing classes or made abstract in the extending interfaces. If they are not overridden, their implementation will be shared by all the implementing classes or sub interfaces.

Below is the syntax for declaring a `default` method in an **interface** :

```
public default void methodName() {  
    System.out.println("This is a default method in interface");  
}
```

Similarly, **Java 8** also introduced `static` methods inside interfaces, which act as regular static methods in classes. These allow developers group the utility functions along with the interfaces instead of defining them in a separate helper class.

Below is the syntax for declaring a `static` method in an **interface** :

```
public static void methodName() {  
    System.out.println("This is a static method in interface");  
}
```

**Note:** Please don't change the package name.

**Source Code:**

q11284/MainApp.java

```
package q11284;
interface Car {
    String getName();
    int getMaxSpeed();
    default void applyBreak() {
        System.out.println("Applying break on " + getName());
    }
    static Car getFastestCar(Car car1, Car car2) {
        return (car1.getMaxSpeed() >= car2.getMaxSpeed()) ? car1 : car2;
    }
}
class BMW implements Car {
    private String name;
    private int maxSpeed;
    public BMW(String name, int maxSpeed) {
        this.name = name;
        this.maxSpeed = maxSpeed;
    }
    public int getMaxSpeed() {
        return maxSpeed;
    }
    public String getName() {
        return name;
    }
}
class Audi implements Car {
    private String name;
    private int maxSpeed;
    public Audi(String name, int maxSpeed) {
        this.name = name;
        this.maxSpeed = maxSpeed;
    }
    public int getMaxSpeed() {
        return maxSpeed;
    }
    public String getName() {
        return name;
    }
}
public class MainApp {
    public static void main(String args[]) {
        String name = args[0];
        int speed = Integer.parseInt(args[1]);
        String name1 = args[2];
        int speed1 = Integer.parseInt(args[3]);
        Car car1 = new BMW(name, speed);
        Car car2 = new Audi(name1, speed1);
        System.out.println("Fastest car is : " + Car.getFastestCar(car1,
car2).getName());
    }
};
```

## Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Fastest car is : BMW

Test Case - 2
User Output
Fastest car is : Maruthi



<b>S.No: 17</b>	Exp. Name: <b><i>Write the code to create an exception</i></b>	<b>Date: 2023-11-09</b>
-----------------	--	-------------------------

**Aim:**

Write a Java program to create an exception.

**Source Code:**

q221/Exception1.java

```
package q221;
class Exception1{
    public static void main(String [] args)
    {
        int a=0;
        try{
            a=151/0;
        }
        catch(ArithmeticException ae)
        {
            System.out.println("Exception caught : divide by zero occurred");
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
Exception caught : divide by zero occurred

<b>S.No: 18</b>	Exp. Name: <b>Write the code for handling the exception</b>	<b>Date: 2023-11-09</b>
-----------------	---	-------------------------

**Aim:**

Write a Java code for handling the exception.

**Source Code:**

q222/handleError.java

```

package q222;
import java.util.Random;
public class handleError {
    public static void main(String args[]) {
        int a = 0, b = 0, c = 0;
        Random r = new Random(100);
        for(int i=0;i<32;i++){
            try{
                b=r.nextInt();
                c=r.nextInt();
                a=12345/(b/c);
            }
            catch(ArithmeticException ae){
                System.out.println("Division by zero.");
                a=0;
            }
            System.out.println("a: "+a );
        }
    }
}

```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
a: 12345
Division by zero.
a: 0
a: -1028
Division by zero.
a: 0
a: 12345
a: -12345
Division by zero.
a: 0
a: 3086
a: 12345
a: -12345
a: 12345
Division by zero.
a: 0

a: 12345
a: 342
a: 12345
a: -12345
a: 12345
a: -12345
Division by zero.
a: 0
a: -4115
Division by zero.
a: 0
a: -4115
a: 6172
a: 6172
Division by zero.
a: 0
Division by zero.
a: 0
Division by zero.
a: 0
a: 12345
a: -280
a: -12345
Division by zero.
a: 0

S.No: 19	Exp. Name: <b>Write the code to create an exception using the predefined exception</b>	Date: 2023-11-09
----------	--	------------------

**Aim:**

Write a Java code to create an exception using the predefined exception

**Source Code:**

q223/exception2.java

```
package q223;
class exception2{
    public static void main(String[] args){
        int a=0;
        try{
            a=123/a;
        }
        catch(ArithmeticException ae){
            System.out.println("Exception raised -Division by zero.");
        }
        System.out.println("After catch statement.");
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
Exception raised -Division by zero.
After catch statement.

S.No: 20	Exp. Name: <b>Write the code for creating your own exception</b>	Date: 2023-11-09
----------	--	------------------

**Aim:**

Write a Java code for creating your own exception

**Source Code:**

q224/demo.java

```
package q224;
class MyException extends Exception{
    private int ex;
    MyException(int s){
        ex=s;
    }
    public String toString(){
        return "MyException["+ex+"] is less than zero";
    }
}
class demo{
    static void validate(int num,int num1) throws MyException{
        if(num<0)
            throw new MyException(num);
        else
            System.out.println(num+num1);
    }
    public static void main(String args[]){
        try{
            validate(-10,10);
        }catch(MyException m){
            System.out.println(m);
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
User Output
MyException[-10] is less than zero

<b>S.No: 21</b>	Exp. Name: <b><i>program that takes inputs 5 numbers, each between 10 and 100</i></b>	<b>Date: 2023-11-30</b>
-----------------	---	-------------------------

Enter 5 unique values between 10 & 100
25
15
30
0
Entered value must be in between 10 & 100
34
89
The five unique values are :25 15 30 34 89

<b>Test Case - 2</b>
<b>User Output</b>
Enter 5 unique values between 10 & 100
48
92
34
92
Duplicate value found, retry
39
23
The five unique values are :48 92 34 39 23

S.No: 22	Exp. Name: <b><i>A program to illustrate threads</i></b>	Date: 2024-01-01
----------	--	------------------

**Aim:**

Write Java program(s) on creating multiple threads, assigning priority to threads, synchronizing threads, suspend and resume threads

**Source Code:**

```
TestThread.java
```



```

class RunnableDemo implements Runnable {
    public Thread t;
    private String threadName;
    boolean suspended = false;
    RunnableDemo(String name) {
        threadName = name;
        System.out.println("Creating " + threadName);
    }
    public void run() {
        System.out.println("Running " + threadName);
        try {
            for (int i = 10; i > 0; i--) {
                System.out.println("Thread: " + threadName + ", " + i);
                // Let the thread sleep for a while.
                Thread.sleep(200);
                synchronized(this) {
                    while (suspended) {
                        wait();
                    }
                }
            }
        } catch (InterruptedException e) {
            System.out.println("Thread " + threadName + " interrupted.");
        }
        System.out.println("Thread " + threadName + " exiting.");
    }
    public void start() {
        System.out.println("Starting " + threadName);
        if (t == null) {
            t = new Thread(this, threadName);
            t.start();
        }
    }
    void suspend() {
        suspended = true;
    }
    synchronized void resume() {
        suspended = false;
        notify();
    }
}

public class TestThread {
    public static void main(String args[]) {
        RunnableDemo R1 = new RunnableDemo("Thread-1");
        R1.start();

        RunnableDemo R2 = new RunnableDemo("Thread-2");
        R2.start();
        try {
            Thread.sleep(300);
            R1.suspend();
            System.out.println("Suspending First Thread");
            Thread.sleep(300);
            R1.resume();
            System.out.println("Resuming First Thread");
        }
    }
}

```

```

        Thread.sleep(300);
        R2.resume();
        System.out.println("Resuming thread Two");
    } catch (InterruptedException e) {
        System.out.println("Main thread Interrupted");
    }
    try {
        System.out.println("Waiting for threads to finish.");
        R1.t.join();
        R2.t.join();
    } catch (InterruptedException e) {
        System.out.println("Main thread Interrupted");
    }
    System.out.println("Main thread exiting.");
}
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Creating Thread-1
Starting Thread-1
Creating Thread-2
Starting Thread-2
Running Thread-1
Running Thread-2
Thread: Thread-2, 10
Thread: Thread-1, 10
Suspending First Thread
Thread: Thread-2, 9
Thread: Thread-2, 8
Resuming First Thread
Suspending thread Two
Thread: Thread-1, 9
Thread: Thread-1, 8
Resuming thread Two
Waiting for threads to finish.
Thread: Thread-2, 7
Thread: Thread-1, 7
Thread: Thread-2, 6
Thread: Thread-1, 6
Thread: Thread-2, 5
Thread: Thread-1, 5
Thread: Thread-2, 4
Thread: Thread-1, 4
Thread: Thread-2, 3
Thread: Thread-1, 3
Thread: Thread-2, 2
Thread: Thread-1, 2

Thread: Thread-2, 1
Thread: Thread-1, 1
Thread Thread-2 exiting.
Thread Thread-1 exiting.
Main thread exiting.

**Aim:**

Write a Java code to print a file into n parts

**Source Code:**

q226/split1.java

```
package q226;
import java.io.*;
import java.util.Scanner;
public class split1 {
    public static void main(String args[]) {
        try{
            String inputfile = "test.txt";
            double nol = 5.0;
            File file = new File(inputfile);
            Scanner scanner = new Scanner(file);
            int count = 0;
            while (scanner.hasNextLine()) {
                scanner.nextLine();
                count++;
            }
            System.out.println("Lines in the file: " + count);
            double temp = (count/nol);
            int temp1 = (int)temp;
            int nof = 0;
            if(temp1 == temp) {
                nof=temp1;
            }
            else {
                nof = temp1 + 1;
            }
            System.out.println("No. of files to be generated :"+nof);
            BufferedReader br = new BufferedReader(new FileReader(inputfile));
            String strLine;
            for (int j = 1; j <= nof; j++) {
                FileWriter fw= new FileWriter("File"+j+".txt");
                for (int i = 1; i <= nol; i++) {
                    strLine = br.readLine();
                    if (strLine!= null) {
                        strLine=strLine+"\r\n";
                        fw.write(strLine);
                    }
                }
                fw.close();
            }
            br.close();
        }
        catch (Exception e) {
            System.err.println("Error: " + e.getMessage());
        }
    }
}
```

test.txt

Insert text

h

ere : 1614065200486

## Execution Results - All test cases have succeeded!

### Test Case - 1

#### User Output

Lines in the file: 3

No. of files to be generated :1

S.No: 24	Exp. Name: <b><i>program to create a super class called Figure that it returns the area of a rectangle and triangle</i></b>	Date: 2023-11-09
----------	---	------------------

**Aim:**

Write a java program to create a super class called Figure that receives the dimensions of two dimensional objects. It also defines a method called area that computes the area of an object. The program derives two sub-classes from Figure. The first is Rectangle and second is Triangle. Each of the sub classes override area() so that it returns the area of a rectangle and triangle respectively

**Source Code:**

```
AbstractAreas.java
```

```

import java.util.*;
abstract class Figure{
    double dim1,dim2,dim3,dim4;
    Figure(double a,double b){
        dim1=a;
        dim2=b;
        dim3=a;
        dim4=b;
    }
    abstract void area();
}
class Rectangle extends Figure{
    Rectangle(double a,double b){
        super(a,b);
    }
    void area(){
        double area=dim1*dim2;
        System.out.println("Rectangle:");
        System.out.println("Area is "+area);
    }
}
class Triangle extends Figure{
    Triangle (double a,double b){
        super(a,b);
    }
    void area(){
        double area=0.5*dim1*dim2;
        System.out.println("Triangle:");
        System.out.println("Area is "+area);
    }
}
class AbstractAreas{
    public static void main(String args[]){
        Scanner sc = new Scanner(System.in);
        System.out.println("Enter lenght and breadth of Rectangle :");
        double dim1=sc.nextDouble();
        double dim2=sc.nextDouble();
        System.out.println("Enter height and side of Triangle :");
        double dim3=sc.nextDouble();
        double dim4=sc.nextDouble();
        Rectangle r=new Rectangle(dim1,dim2);
        Triangle t = new Triangle(dim3,dim4);
        Figure fig;
        fig=r;
        fig.area();
        fig=t;
        fig.area();
    }
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1

User Output
Enter lenght and breadth of Rectangle :
12
14
Enter height and side of Triangle :
7
5
Rectangle:
Area is 168.0
Triangle:
Area is 17.5

Test Case - 2
User Output
Enter lenght and breadth of Rectangle :
4
8
Enter height and side of Triangle :
5
3
Rectangle:
Area is 32.0
Triangle:
Area is 7.5



S.No: 25	Exp. Name: <b>Write a Java program demonstrating the usage of Threads</b>	Date: 2024-01-01
----------	---	------------------

### Aim:

Write a Java program that uses three threads to perform the below actions:

1. First thread should print "Good morning" for every 1 second for 2 times
2. Second thread should print "Hello" for every 1 seconds for 2 times
3. Third thread should print "Welcome" for every 3 seconds for 1 times

Write appropriate **constructor** in the `Printer` class which implements `Runnable` interface to take three arguments : **message**, **delay** and `count` of types **String**, **int** and **int** respectively.

Write code in the `Printer.run()` method to print the **message** with appropriate **delay** and for number of times mentioned in **count**.

Write a class called `ThreadDemo` with the `main()` method which instantiates and executes three instances of the above mentioned `Printer` class as threads to produce the desired output.

[**Note:** If you want to sleep for 2 seconds you should call `Thread.sleep(2000);` as the `Thread.sleep(...)` method takes milliseconds as argument.]

**Note:** Please don't change the package name.

### Source Code:

q11349/ThreadDemo.java

```

package q11349;
public class ThreadDemo {
    public static void main(String[] args) throws Exception {
        Thread t1 = new Thread(new Printer("Good morning", 1, 2));
        Thread t2 = new Thread(new Printer("Hello", 1, 2));
        Thread t3 = new Thread(new Printer("Welcome", 3, 1));
        t1.start();
        t2.start();
        t3.start();
        t1.join();
        t2.join();
        t3.join();
        System.out.println("All the three threads t1, t2 and t3 have completed
execution.");
    }
}
class Printer implements Runnable {
    private String message;
    private int delay;
    private int count;
    public Printer(String message, int delay, int count) {
        this.message = message;
        this.delay = delay;
        this.count = count;
    }
    public void run() {
        for (int i = 0; i < count; i++) {
            try {
                System.out.println(message);
                Thread.sleep(delay * 500);
            } catch (Exception e) {
                e.printStackTrace();
            }
        }
    }
}
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Good morning
Hello
Welcome
Good morning
Hello
All the three threads t1, t2 and t3 have completed execution.

S.No: 26	Exp. Name: <b>Program to find and replace pattern in a given file.</b>	Date: 2024-01-01
----------	--	------------------

**Aim:**

Write a java program to find and replace patterns in a given file. Replace the string "This is test string 20000" with the input string.

**Note:** Please don't change the package name.

**Source Code:**

q29790/ReplaceFile.java

```
package q29790;
import java.io.*;
import java.util.*;
public class ReplaceFile {
    public static void main(String args[]) {
        try {
            Scanner sc = new Scanner(System.in);
            String input = sc.nextLine();
            File file = new File("file.txt");
            BufferedReader reader = new BufferedReader(new FileReader(file));
            String line = "", oldtext = "";
            while((line = reader.readLine()) != null) {
                oldtext += line + "\r\n";
            }
            reader.close();
            String newtext = oldtext.replaceAll("This is test string 20000",
input);

            FileWriter writer = new FileWriter("file.txt");

            writer.write(newtext);writer.close();
            System.out.print("Previous string: "+oldtext);
            System.out.print("New String: "+newtext);

        }

        catch (IOException ioe) {
            ioe.printStackTrace();
        }

    }
}
```

file.txt

This is test string 20000. The test string is replaced with your input string, check the string you entered is now visible here.

**Execution Results - All test cases have succeeded!**

Test Case - 1

User Output
New string
Previous string: This is test string 20000. The test string is replaced with your input string, check the string you entered is now visible here.
New String: New string. The test string is replaced with your input string, check the string you entered is now visible here.

<b>S.No: 27</b>	Exp. Name: <b><i>A java program to demonstrate that the catch block for type Exception A catches the exception of type Exception B and Exception C.</i></b>	<b>Date: 2023-11-09</b>
-----------------	---	-------------------------

**Aim:**

Use inheritance to create an exception superclass called Exception A and exception subclasses Exception B and Exception C, where Exception B inherits from Exception A and Exception C inherits from Exception B. Write a java program to demonstrate that the catch block for type Exception A catches the exception of type Exception B and Exception C.

**Note:** Please don't change the package name.

**Source Code:**

q29793/TestException.java

```

package q29793;
import java.lang.*;
@SuppressWarnings("serial")
class ExceptionA extends Exception {
    String message;
    public ExceptionA(String message) {
        this.message = message;
    }
}
@SuppressWarnings("serial")
class ExceptionB extends ExceptionA {
    ExceptionB(String message){
        super(message);
    }
}
@SuppressWarnings("serial")
class ExceptionC extends ExceptionB {
    ExceptionC(String message){
        super(message);
    }
}
@SuppressWarnings("serial")
public class TestException {
    public static void main(String[] args) {
        try {
            getExceptionB();
        }
        catch(ExceptionA ea) {
            System.out.println("Got exception from Exception B");
        }
        try {
            getExceptionC();
        }
        catch(ExceptionA ea) {
            System.out.println("Got exception from Exception C");
        }
    }
    public static void getExceptionB() throws ExceptionB {
        throw new ExceptionB("Exception B");
    }
    public static void getExceptionC() throws ExceptionC {
        throw new ExceptionC("Exception C");
    }
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Got exception from Exception B
Got exception from Exception C

S.No: 28	Exp. Name: <b>Stack Implementation</b>	Date: 2024-01-01
----------	--	------------------

**Aim:**

Create an interface for stack with push and pop operations. Implement the stack in two ways fixed-size stack and Dynamic stack (stack size is increased when the stack is full).

**Note:** Please don't change the package name.

**Source Code:**

```
q29794/StaticAndDynamicStack.java
```

```

package q29794;
interface Stack {
    void push(int item);
    int pop();
}
class FixedSizeStack implements Stack {
    private int stck[];
    private int tos;

    FixedSizeStack(int size) {
        stck = new int[size];
        tos = -1;
    }
    // Push an item onto the stack
    public void push(int item) {
        if(tos == stck.length-1) // use length member
            System.out.println("Stack is full.");
        else
            stck[++tos] = item;
    }
    // Pop an item from the stack
    public int pop() {
        if(tos < 0) {
            System.out.println("Stack underflow");
            return 0;
        } else {
            return stck[tos--];
        }
    }
}
class DynamicStack {
    private int stck[];
    private int tos;

    DynamicStack(int size) {
        stck = new int[size];
        tos = -1;
    }
    // Push an item onto the stack
    public void push(int item) {
        if(tos == stck.length-1) { // use length member
            System.out.println("Stack is full and increased");
            stck=doublesize(stck);
        } else {
            stck[++tos] = item;
        }
    }
    // Pop an item from the stack
    public int pop() {
        if(tos < 0) {
            System.out.println("Stack underflow");
            return 0;
        } else {
            return stck[tos--];
        }
    }
}

```



```

        int[] newArray = new int[stck.length * 2];
        for(int i = 0; i<stck.length; i++) {
            newArray[i] = stck[i];
        }
        return newArray;
    }
}

public class StaticAndDynamicStack {
    public static void main(String args[]) {
        FixedSizeStack mystack1 = new FixedSizeStack(5);
        DynamicStack mystack2 = new DynamicStack(5);
        // push some numbers onto the stack
        for(int i=0; i<5; i++)
            mystack1.push(i);
        for(int i=0; i<10; i++)
            mystack2.push(i);
        // pop those numbers off the stack
        System.out.println("Stack in mystack1:");
        for(int i=0; i<5; i++) {
            System.out.println(mystack1.pop());
        }
        System.out.println ("Stack in mystack2 :");
        for (int i=0; i<10; i++)
            System.out.println(mystack2.pop());
    }
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Stack is full and increased
Stack in mystack1:
4
3
2
1
0
Stack in mystack2 :
9
8
7
6
4
3
2
1
0
Stack underflow
0

<b>S.No: 29</b>	Exp. Name: <b><i>Create multiple threads to access the contents of a stack</i></b>	<b>Date: 2024-01-01</b>
-----------------	--	-------------------------

**Aim:**

Create multiple threads to access the contents of a stack. Synchronize thread to prevent simultaneous access to push and pop operations.

**Note:** Please don't change the package name.

**Source Code:**

q29795/StackThreads.java

```

package q29795;
import java.util.*;
class Stack {
    int tos;
    int stck[];
    int size;
    Stack(int size) {
        this.size=size;
        tos=-1;
        stck=new int[this.size];
    }
    synchronized void push(int item) {
        if(tos==stck.length-1) {
            // use length member
            System.out.println("Stack is full");
        }
        else {
            stck[++tos] = item;
        }
    }
    // Pop an item from the stack
    synchronized int pop() {
        if(tos < 0) {

            System.out.println("Stack underflow");
            return 0;
        }
        else
            return stck[tos--];
    }
}

class PushThread extends Thread {
    Stack s;
    PushThread(Stack s) {
        this.s=s;
    }
    public void run() {
        for(int i=1;i<=s.size;i++) {
            s.push(i);
            try {
                Thread.sleep(100);
            }
            catch(Exception e) {
                System.out.println(e);
            }
        }
    }
}

class PopThread extends Thread {

    Stack s;
    PopThread(Stack s){
        this.s=s;
    }
}

```

```

        System.out.println(s.pop());
        try {
            Thread.sleep(100);
        }
        catch(Exception e) {
            System.out.println(e);
        }
    }
}

public class StackThreads {
    public static void main(String args[]) {
        int size;
        Scanner sc =new Scanner(System.in);
        System.out.println("Enter the size of the stack");
        size=sc.nextInt();
        Stack s = new Stack(size);//only one object
        PushThread t1=new PushThread(s);
        PopThread t2=new PopThread(s);
        t1.start();
        t2.start();
        t2.setPriority(9);
    }
}

```

## Execution Results - All test cases have succeeded!

Test Case - 1
<b>User Output</b>
Enter the size of the stack
4
1
2
3
4

Test Case - 2
<b>User Output</b>
Enter the size of the stack
9
1
2
3
4
5
6
7

8
9

<b>S.No: 30</b>	Exp. Name: <b>Write java program(s) that use collection framework classes.(TreeMap class)</b>	<b>Date: 2023-11-30</b>
-----------------	---	-------------------------

**Aim:**

Write a java program(s) that use collection framework classes.(TreeMap class)

**Source Code:**

```

Treemap.java

import java.util.*;
class Treemap{
    public static void main(String[] args){
        TreeMap<Integer, String> tm = new TreeMap<Integer, String>();
        System.out.print("No.Of Mapping Elements in TreeMap:");
        Scanner sc= new Scanner(System.in);
        int n = sc.nextInt();
        for (int i=0; i<n; i++){
            System.out.print("Integer:");
            Scanner b = new Scanner(System.in);
            int num= b.nextInt();
            System.out.print("String:");
            Scanner a = new Scanner(System.in);
            String str= a.nextLine();
            tm.put(num,str);
        }
        Set<Map.Entry<Integer, String> > entries = tm.entrySet();
        Iterator<Map.Entry<Integer, String> > iterator
            = entries.iterator();
        Map.Entry<Integer, String> entry = null;
        while (iterator.hasNext()) {
            entry = iterator.next();
            System.out.println(entry.getKey() + "->" + entry.getValue());
        }
    }
}

```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
No.Of Mapping Elements in TreeMap:
2
Integer:
1
String:
HELLO
Integer:
2
String:
WORLD

1->HELLO
2->WORLD

Test Case - 2
<b>User Output</b>
No.Of Mapping Elements in TreeMap:
3
Integer:
25
String:
UNIVERSITY
Integer:
26
String:
KNOWLEDGE
Integer:
27
String:
TECHNOLOGIES
25->UNIVERSITY
26->KNOWLEDGE
27->TECHNOLOGIES

<b>S.No: 31</b>	Exp. Name: <b>Write java program(s) that use collection framework classes.(TreeSet class)</b>	<b>Date: 2023-11-30</b>
-----------------	---	-------------------------

**Aim:**

Write java program(s) that use collection framework classes.(TreeSet class)

**Source Code:**

TreeSetclass.java

```
import java.util.*;
class TreeSetclass{
    public static void main(String args[]){
        TreeSet<String> al=new TreeSet<String>();
        System.out.print("No.Of Elements in TreeSet:");
        Scanner sc= new Scanner(System.in);
        int n = sc.nextInt();
        for (int i=0; i<n; i++){
            System.out.print("String:");
            Scanner b = new Scanner(System.in);
            String str= b.nextLine();
            al.add(str);
        }
        System.out.println("TreeSet Elements by Iterating:");
        Iterator<String> itr=al.iterator();
        while(itr.hasNext()){
            System.out.println(itr.next());
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
No.Of Elements in TreeSet:
3
String:
Never
String:
Give
String:
Up
TreeSet Elements by Iterating:
Give
Never
Up
<b>Test Case - 2</b>



User Output
No.Of Elements in TreeSet:
2
String:
Hello
String:
There
TreeSet Elements by Iterating:
Hello
There

<b>S.No: 32</b>	Exp. Name: <b>Write java program(s) that use collection framework classes.(LinkedList class)</b>	<b>Date: 2023-11-30</b>
-----------------	--	-------------------------

**Aim:**

Write a java program(s) that use collection framework classes.(LinkedList class)

**Source Code:**

LinkedListclass.java
<pre> import java.util.Scanner; import java.util.Iterator; import java.util.LinkedList; import java.util.Set; public class LinkedListclass {     public static void main(String[] args){         LinkedList&lt;String,String&gt; linkedHashMap = new LinkedList&lt;String,String&gt;();         System.out.print("No.Of Mapping Elements in LinkedList:");         Scanner sc= new Scanner(System.in);         int n = sc.nextInt();         for (int i=0; i&lt;n; i++){             System.out.print("String:");             Scanner b = new Scanner(System.in);             String str1= b.nextLine();             System.out.print("Corresponding String:");             String str2= b.nextLine();             linkedHashMap.put(str1,str2);         }         Set entrySet = linkedHashMap.entrySet();         Iterator it = entrySet.iterator();         System.out.println("LinkedList entries : ");         while (it.hasNext())             System.out.println(it.next());         }     } </pre>

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
No.Of Mapping Elements in LinkedList:
3
String:
ONE
Corresponding String:
hi
String:
TWO
Corresponding String:

hello
String:
THREE
Corresponding String:
everyone
LinkedHashMap entries :
ONE=hi
TWO=hello
THREE=everyone

Test Case - 2	
User Output	
No.Of Mapping Elements in LinkedHashMap:	
4	
String:	
1x1	
Corresponding String:	
1	
String:	
1x2	
Corresponding String:	
2	
String:	
1x3	
Corresponding String:	
3	
String:	
1x4	
Corresponding String:	
4	
LinkedHashMap entries :	
1x1=1	
1x2=2	
1x3=3	
1x4=4	

<b>S.No: 33</b>	Exp. Name: <b>Write java program(s) that use collection framework classes.(HashMap class)</b>	<b>Date: 2023-11-30</b>
-----------------	---	-------------------------

**Aim:**

Write a java program(s) that use collection framework classes.(HashMap class)

**Source Code:**

HashMapclass.java

```
import java.util.HashMap;
import java.util.*;
public class HashMapclass{
    public static void main(String[] args){
        HashMap<String,Integer> map = new HashMap<>();
        System.out.print("No.Of Mapping Elements in HashMap:");
        Scanner sc= new Scanner(System.in);
        int n = sc.nextInt();
        for (int i=0; i<n; i++){
            System.out.print("String:");
            Scanner b = new Scanner(System.in);
            String str= b.nextLine();
            System.out.print("Integer:");
            int num= b.nextInt();
            map.put(str,num);
        }
        for (Map.Entry<String,Integer> entry : map.entrySet())
            System.out.println("Key = " + entry.getKey() +", Value = "+
entry.getValue());
        System.out.println(map);
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
No.Of Mapping Elements in HashMap:
3
String:
hi
Integer:
1
String:
hello
Integer:
2
String:
world
Integer:

Key = hi, Value = 1
Key = world, Value = 3
Key = hello, Value = 2
{hi=1, world=3, hello=2}

Test Case - 2
User Output
No.Of Mapping Elements in HashMap:
3
String:
Students
Integer:
200
String:
Teachers
Integer:
5
String:
Principal
Integer:
1
Key = Teachers, Value = 5
Key = Students, Value = 200
Key = Principal, Value = 1
{Teachers=5, Students=200, Principal=1}

<b>S.No: 34</b>	Exp. Name: <b>Write java program(s) that use collection framework classes.(LinkedList class)</b>	<b>Date: 2023-11-30</b>
-----------------	--	-------------------------

**Aim:**

Write a java program(s) that use collection framework classes.(LinkedList class)

**Source Code:**

LinkedList.java

```
import java.io.*;
import java.util.*;
import java.util.LinkedList;
import java.util.ListIterator;
public class LinkedList{
    public static void main(String args[]) {
        System.out.println("No.Of Strings in LinkedList:");
        Scanner sc= new Scanner(System.in);
        int n = sc.nextInt();
        LinkedList<String> ll = new LinkedList<String>();
        for (int i=0; i<n; i++){
            System.out.println("Enter the String:");
            Scanner b = new Scanner(System.in);
            String str= b.nextLine();
            ll.add(str);
        }
        System.out.println("LinkedList:" + ll);
        ListIterator list_Iter = ll.listIterator(0);
        System.out.println("The List is as follows:");
        while(list_Iter.hasNext()){
            System.out.println(list_Iter.next());
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
No.Of Strings in LinkedList:
3
Enter the String:
Hi
Enter the String:
Hello
Enter the String:
World
LinkedList:[Hi, Hello, World]
The List is as follows:
Hi
Hello

World
-------

Test Case - 2
User Output
No.Of Strings in LinkedList:
2
Enter the String:
Human
Enter the String:
Being
LinkedList:[Human, Being]
The List is as follows:
Human
Being

<b>S.No: 35</b>	Exp. Name: <b>Write java program(s) that use collection framework classes.(ArrayList class)</b>	<b>Date: 2023-11-30</b>
-----------------	---	-------------------------

**Aim:**

Write a java program(s) that use collection framework classes.(ArrayList class)

**Source Code:**

ArraylistExample.java

```
import java.util.*;
class ArraylistExample{
    public static void main(String args[]){
        Scanner sc = new Scanner(System.in);
        System.out.println("Enter ArrayList length: ");
        int n = sc.nextInt();
        ArrayList<Integer> arrli=new ArrayList<Integer>();
        for (int i=1; i<=n; i++){
            arrli.add(i);
        }
        Iterator itr=arrli.iterator();
        System.out.println("ArrayList printing by using Iterator: ");
        while(itr.hasNext()){
            System.out.println(itr.next());
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
Enter ArrayList length:
5
ArrayList printing by using Iterator:
1
2
3
4
5

Test Case - 2
<b>User Output</b>
Enter ArrayList length:
3
ArrayList printing by using Iterator:
1
2
3



<b>S.No: 36</b>	Exp. Name: <b>Write java program(s) that use collection framework classes.(HashTable class)</b>	<b>Date: 2023-11-30</b>
-----------------	---	-------------------------

**Aim:**

Write a java program(s) that use collection framework classes.(HashTable class)

**Source Code:**

HashTableclass.java

```
import java.util.*;
import java.util.Enumeration;
class HashTableclass {
    public static void main(String[] args)
    {
        Hashtable<Integer, String> ht = new Hashtable<>();
        System.out.print("No.Of Mapping Elements in HashTable:");
        Scanner sc= new Scanner(System.in);
        int n = sc.nextInt();
        for (int i=0; i<n; i++){
            System.out.print("Rank:");
            Scanner b = new Scanner(System.in);
            int num= b.nextInt();
            System.out.print("Name:");
            Scanner a = new Scanner(System.in);
            String str= a.nextLine();
            ht.put(num,str);
        }
        Enumeration<Integer> e = ht.keys();
        while (e.hasMoreElements()) {
            int key = e.nextElement();
            System.out.println("Rank : " + key+ "\t\t Name : "+ ht.get(key));
        }
    }
}
```

**Execution Results - All test cases have succeeded!**

Test Case - 1
<b>User Output</b>
No.Of Mapping Elements in HashTable:
3
Rank:
4
Name:
Robert
Rank:
5
Name:
John
Rank:

6	
Name :	
Jennifer	
Rank : 6	Name : Jennifer
Rank : 5	Name : John
Rank : 4	Name : Robert

<b>Test Case - 2</b>	
<b>User Output</b>	
No.Of Mapping Elements in HashTable:	
3	
Rank:	
1	
Name:	
Jon	
Rank:	
2	
Name:	
Robert	
Rank:	
3	
Name:	
Jennifer	
Rank : 3	Name : Jennifer
Rank : 2	Name : Robert
Rank : 1	Name : Jon

