



Safra
SOL 1425TM

TECHNICAL DATA SHEET



MATERIAL SAFETY DATA SHEET

Safety Department

Review:2.5

September 13, 2006

10-QSR-MDS

Page : 1 of 4

1) MATERIAL IDENTIFICATION:

Safra Product Name	Safrasol 1425
Product Trade Name	Safrasol 1425™
Chemical Symbol	C6 with some C7 & C5 hydrocarbons
ID # & CAS #	UN # 3295 & CAS # not available
Manufacturer:	Safra Company in its Yanbu Refinery
Address:	P.O.Box: 30063, Yanbu Al Sinaiyah, Kingdom of Saudi Arabia
Country of Origin & Production	Kingdom of Saudi Arabia

2) PHYSICAL PROPERTIES:

Boiling Range	40 - 110 °C
Vapor Density (Air = 1)	Heavier than air
Density (H2O = 1)	0.70 - 0.71
Solubility in Water	Negligible
Vapor Pressure (KPA)	35 KPA approx.
Evaporation rate	Not available
(Butyl Acetate = 1)	
Appearance and odor	Clear, bright liquid with benzol like strong and characteristic petroleum odor.
Color	+ 30 (ASTM D156 method)

3) INGREDIENTS AND HAZARD

Aromatic Content	15 % Volume approx.
Sulfur Content	Less than 5 ppm
Hazard	Flammable, irritant, harmful if swallowed or inhaled in large quantities.

4) FIRE AND EXPLOSION HAZARD

Flash Point	< 0 °C
Extinguishing Media	Use foam, dry chemical powder, Carbon dioxide.
Special Fire Fighting	Use self contained breathing apparatus and protective clothing. Avoid spreading, burning liquid with water which should be used for cooling containers as water spray.
Unusual Fire and Explosion Hazard	Moderately explosive when exposed to flame or chemically reacted. Vapor form from this product, may travel or be moved by air currents and be ignited by pilot lights, other flames, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from handling point.
Small Fire	Dry chemical powder, Co2 & water supply.
Large Fire	Water spray, fog or foam. Move containers or drums from fire area, If you can do it without risk. Cool containers that are exposed to flames with water from the sides until/and after fire is out.



MATERIAL SAFETY DATA SHEET

Safety Department

Review:2.5

September 13, 2006

10-QSR-MDS

Page : 2 of 4

5) HEALTH HAZARDS:

TLV	100 ppm Max.
Effect of single over exposure	Low order of toxicity, very small amounts aspirated into lung during ingestion or vomiting, may cause severe lung congestion resulting in labored breathing.
Swallowing	
Skin Absorption	None currently known.
Inhalation	Irritating to the respiratory tract. In high concentration may cause central nervous system effects leading to drowsiness, dizziness and marcosis.
Skin Contact	Frequent or prolonged may irritate and cause dermatitis.
Eye Contact	Irritation but does not injure eye tissue.
Effect of repeated over exposure	No evidence of adverse effects from available information.

6) EMERGENCY AND FIRST AID MEASURES UPON EXPOSURE TO THE MATERIAL:

Swallowing	Do not induce vomiting. Keep patient at rest. Seek immediate medical attention.
Inhalation	Move victim to fresh air, call emergency medical care. If not breathing give artificial respiration. If breathing is difficult give oxygen.
Skin Contact	Remove contaminated clothing and wash affected area with soap and water. Seek Medical advise.
Eye contact	Immediately flush eyes with running water for at least 15 minutes. Get medical care without delay.

7) STABILITY & REACTIVITY DATA:

Hazardous Combustion or Decomposition products	Burning may produce carbon monoxide and/or carbon dioxide. When heated it emits irritating fumes, can react vigorously with oxidizing materials.
Hazardous polymerization	Will not occur.
Condition to avoid	None.
Waste disposal method	Incinerate in a special furnace or if the quantity is small, expose for weathering, abide to Royal Commission regulations. Other disposal method is burial in approved land fill.

8) ACCIDENTAL RELEASE/SPILL/LEAK MEASURES:

Steps to be taken if the material is released or spilled :

1. Notify safety personnel of leaks or spills.
2. Eliminate all sources of ignition until area is determined to be free from explosion hazard.
3. Provide adequate ventilation & instruct personnel to use protection against liquid contact and vapor or mist inhalation.
4. Contain spill by diking
5. Small spills could be washed away to the API separator or may be contained by using absorbents. Large spill after diking should be recovered by pumping (Use explosion proof pump).
6. Stop leak if you can without risk.
7. Use water spray to reduce vapors.



MATERIAL SAFETY DATA SHEET

Safety Department

Review:2.5

September 13, 2006

10-QSR-MDS

Page : 3 of 4

9) DISPOSAL CONSIDERATION:

Disposal Method Incinerate in a special furnace or if the quantity is small expose for weathering, abide to local regulations. Other disposal method is burial in approved land fill.

10) EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT FOR DEALING WITH THE MATERIAL:

Respiratory Protection	Use gas mask for respiratory protection.
Ventilation	Provide adequate ventilation where operating conditions may create excessive vapors or mists. This product should be confined within closed containers in which case general (mechanical) ventilation should be sufficient. Use explosion proof equipments. Special local ventilation is recommended at points where vapors can be expected to escape to the work place air.
Hand/body protection	PVC or neoprene gloves/Impermeable apron
Eye Protection	Chemical splash goggles. An eye wash fountain and washing facilities to be readily available near handling areas.

11) HANDLING & STORAGE:

Handling	Use non sparking tools and explosion proof electrical equipments; Prevent static electric spark by grounding transfer equipment; Avoid breathing vapors; Use with adequate ventilation; Don't get in eyes or skin or clothing, wash thoroughly after handling; Call safety for any problem.
Storage	Store in closed containers in a cool, dry and well ventilated area away from source of open flame, heat, strong oxidizing agents and ignitions; Label all containers and sample bottles.

12) TOXICOLOGICAL INFORMATION:

Carcinogenicity	Mildly toxic by ingestion and inhalation
Skin Absorption	None currently known.

13) ECOLOGICAL INFORMATION:

Not established

14) TRANSPORT INFORMATION:

Package Type	Metallic Drums
Hazard Class or Division	3
ID # & CAS #	UN # 3295 & CAS # not available
Label & Placard	Flammable Liquid & Flammable



MATERIAL SAFETY DATA SHEET

Safety Department

Review:2.5

September 13, 2006

10-QSR-MDS

Page : 4 of 4

15) REGULATORY INFORMATION

Flammable, Harmful: may cause lung damage if swallowed /Avoid exposure-Obtain special instructions before use- In case of accident or if you feel unwell seek medical advice immediately- Keep away of children reach- Do not breath vapors- Avoid contact with skin- Do not empty into drains- In case of fire use foam/ DCP/ CO2/ Halon- If swallowed do not induce vomiting and show label or container.