



Safra
LITETM

[Light White Spirit]

SPECIFICATIONS



Safralite™

(Light White Spirit)

Property	ASTM Test Method	Units	Typical	Guarantee
Distillation Range I B P FBP	D86	°C	100 124	85 Min. 130 Max.
Density@ 15°C	D4052	Kg/L	0.730	0.700 – 0.750
Aromatic Content	D1319	Vol. %	10.5	15 Max.
Doctor Test		D4952	Negative	Negative
Color (Saybolt)		D156	+30	+28 Min.
Sulphur Content	D3120	ppmwt	< 1	5 Max.
Copper Corrosion	D130	Rating		1 Max.

Note:

SAFRA guarantees data provided in the specification column. Typical values do not constitute the specification limits and will not be guaranteed.

PRODUCT APPLICATIONS

INKS:

For the processing of miscellaneous types of inks.
For the application of inks to achieve specific properties

DRY CLEANING:

Removes all the oil, dirt & grime for cloth, chamois, leather, upholstery etc.
Dries swiftly, thanks to its boiling range

LEATHER TANNERIES:

A Solvent carrier for dyes, finishes and processing along with other solvents.

CLEANING AND MAINTENANCE CHEMICALS:

Used to remove grease and grime from machines and equipment along with other chemicals. Cleans metallic surfaces quickly

RUBBER SOLVENT:

Safralite is used in many adhesives and glues along with other solvents especially rubber (natural or synthetic).