



Safra Pine™

1. Identification

Commercial Name : Normal Paint Thinner Chemical Family : Thinners/Diluents

Formula : Mixture of hydrocarbons

Molecular Weight : >140

2. Physical Data

Boiling Range (°C) : 150-285°C

Freezing Point : -

Specific Gravity (Water = 1) 0.760-0.790

Vapor Density (Air = 1) : -

Vapor Pressure (mPa) : Not defined Solubility in Water : Insoluble Evaporation : 550

(Butyl Acetate = 1)

3. Ingredients:

Materials : Petroleum Spirit

Hazards : Flammable. Harmful if swallowed or inhaled in large

quantities for long

4. Fire and Explosion Hazard Data:

Flash Point (°C) : >40 min. (43°C average)

Extinguishing Media : Use foam, dry chemical powder or water spray

Special Fire Fighting : Do not spray water directly into storage container

due to danger of boil over

Unusual fire explosion hazard : None

5. Health Hazard Data TLV & Store:

Effect of single over- : 150 ppm (recommended exposure limit). Harmful if

exposure aspirated in large amount into lungs during ingestion

or vomiting may cause severe lung congestion

resulting in labored breathing.

Skin Absorption : Not known

Inhalation : In high concentration may cause drowsiness.

Skin Contact : Frequent or prolonged contact may irritate the skin

Eye Contact : Does not injure eye tissues

Effect or repeated exposures : No adverse effects

MSDS PT 01 UN # 3295



6. Emergency and first aid procedure

Swallowing : Do not induce vomiting. Keep patent at rest

Inhalation : Remove at once to fresh air using proper respiratory

protection, in case of severe exposure

Strong oxidizing agents, halogen, molten sulphur

Skin Contact : Wash with soap and water after removing

contaminated clothing

Eye Contact : Flush eyes with plenty of water

7. Reactivity Date:

Stability : Stable Condition to Avoid : None

Incompatibility (material to

avoid)

Hazardous Combustion or : Burning may produce carbon monoxide and/or

Decomposition Products carbon dioxide
Hazardous Polymerization : Will not occur

8. Spill or Leak Protection:

Steps to be taken if material is released or spilled

1. Eliminate all source of ignition

2. Call fire brigade

3. Contain spilled Liquid with Sand

4. Recover by pumping "explosion proof pump"

5. Collect all contaminated material for disposal

Waste Disposal Method : Incinerate in a special furnace or if the quantity is

small expose for weathering.

9. Special Protection Information:

Respiratory Protection : Required

Ventilation : The product should be confined within closed

containers in which case general (mechanical)

ventilation should be sufficient.

Protection Glove : PVC or Neoprene Eye Protection : Safety Glasses

10. Special Precautions:

Keep away from heat, spark and flame

Keep away from children

MSDS PT 01 UN # 3295