

1. Identification:

Commercial Name : Safra Bond Cement

Chemical Family : Solvent Cement/Adhesive

Formula : Contains synthetic polymers, oxygenated solvents and

Additives

Molecular Weight : NA

2. Hazard Data TLV:

Toxicity : Category 4

into

Effect of single over- : Harmful, not recommended for long exposure congestion

Exposure resulting in labored breathing aspirated in large amount

Lungs may cause severe lung damaged.

Skin Absorption : Not known

Inhalation : Harmful In high concentration may cause drowsiness. Skin Contact : Frequent or prolonged contact may irritate the skin

Eye Contact : May injure eye tissues on prolonged contact

Effect or repeated : No adverse effects

exposures

3. Ingredients:

Materials : Contain CPVC resin, Tetrahydrofuran, MEK &

Cyclohexanone

4. Emergency and first aid procedure

Swallowing : Do not induce vomiting. Keep patent at rest

Inhalation : Remove at once to fresh air using proper respiratory

Protection, in case of severe exposure.

Skin Contact : Wash with soap and water after removing

Contaminated clothing.

Eve Contact : Flush eyes with plenty of water

5. Fire and Explosion Hazard Data:

Flash Point (°C) : <4°C

Extinguishing Media : Use foam, dry chemical powder.

Unusual fire explosion : None.

Hazard.

6. Spill or Leak Protection:

Steps to be taken if material is released or spilled

- 1. Eliminate all source of ignition
- 2. Call fire brigade
- 3. Contain spilled Liquid with Sand
- 4. Recover by pumping "explosion proof pump"
- 5. Collect all contaminated material for disposal



7. Handling & Storage:

The product should be confined within closed containers; in any case a general (mechanical) ventilation should be sufficient.

8. Special Protection Information:

Respiratory Protection : Required : Neoprene : Safety Glasses

Special Precautions

- Keep away from heat, spark and flame

Keep away from childrenStore in cold & dry area

9. Physical Data:

Appearance : Flowable Bodied liquid

Freezing Point : Not reported
Specific Gravity (Water=1) : 0.90-1.00
Vapor Density (Air = 1) : Not reported
Vapor Pressure (mPa) : Not defined
Solubility in Water : Insoluble
Evaporation : 5.0-8.0

(Butyl Acetate = 1)

10. Reactivity Data:

Stability : Stable Condition to Avoid : None

Incompatibility (material to: Strong oxidizing agents, halogen, molten sulphur

avoid)

Hazardous Combustion or : Burning may produce carbon monoxide and/or carbon

dioxide

Decomposition Products

Hazardous Polymerization : Will not occur

11. TOXICOLOGICAL Information:

TOXICITY LD50 LC50 Target Organs
Tetrahydrofuran (THF): Oral: 2842 mg/kg(rat) Inhalation 3hrs. 21,000 mg/m3(rat) STOT SE3
Methyl Ethyl Ketone: Oral: 2737 mg/kg Inhalation 8hrs. 23,500 mg/m3 STOT SE3

Cyclohexanone: Oral: 1535 mg/kg Inhalation 4hrs. 8000 ppm Not

Established

				Sensitization to	
Reproductive Effects	Teratogenicity	<u>Mutagenicity</u>	Embryotoxicity	<u>Product</u>	Synergistic Products
Not Established	Not Established	Not Established	Not Established	Not Established	Not Established

12. ECOLOGICAL Information:

Aquatic Life Toxicity: This product can be harmful or fatal to contaminated aquatic plant or animal life. Especially if released in large quantity in a body of water.

Mobility in soil: If released into the environment, this product can move rapidly through the soil.



13. Waste Disposal Method:

Incinerate in a special furnace or if the quantity is small expose for weathering.

14. TRANSPORT Information:

Proper shipping name: Adhesives

Hazard Class: 3
Secondary Risk: None
Identification Number: UN1133
Packing Group: PG II

Label Required: Class 3 Flammable Liquid

Marine Pollutant: NO AU Hazchem Code: 3YE

15. REGULATORY INFORMATION:

Precautionary Label Information: Highly Flammable, Irritant, Carc, Car. 2

Symbols: F, Xi

16. OTHER INFORMATION:

Specification Information:

Training necessary: Yes, training in practices and procedures contained in product

Literature.

Intended Use of Product: Solvent Cement for CPVC Plastic Pipe.