

SAFRA BOND PVC&CPVC CLEANER

CPVC & PVC PLASTIC PIPE CLEANER

PRODUCT DESCRIPTION: Mixture of oxygenated solvent.

DESIGNED USE: Is low VOC emission CPVC & PVC pipe cleaner.

PHYSICAL DATA:

Parameter	Description	Standard Method
Density (@ 25°C)	0.78 (g/ml) ±2 %	Calculated
Color	Water white	
Solids by Volume	0 %	ISO 3233
VOC (g/liter)	< 450 (g/liter)	VOC tester
Flash Point	< -20°C	ISO 3679 Method 1

PACKAGING: single pack providing by $\frac{1}{16}$ L, $\frac{1}{8}$ L, $\frac{1}{4}$ L, $\frac{1}{2}$ L, 1L in cans.

HANDILING & STORAGE: it must be stored in original pack in dry, shaded, cool well-ventilated Space and away from sources of heat and ignition furthermore containers must be kept tightly closed and handle with care.

SHELF LIFE Preferred using up to 24 months from production date in original tightly closed containers away from direct sunlight, excessive heat and ignition.

INSTRUCTION & USAGE using as the following instruction:



- 1) Squarely cut the pipe to the desired length.
- 2) Deburr and bevel the pipe.
- 3) Apply cleaner by can brush around fitting area.
- 4) apply suitable pipe cement at the same area then make the fitting.

CAUTIONS



The applicators and operators shall be trained, experienced and have the capability and equipment Use according to SAFRA technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product.

HEALTH & SAFETY



Please observe the precautionary notices displayed on the container. Use under well-ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately, any Further Information Refer to Material Safety Data Sheet (MSDS) before using the product.