**TECHNICAL DATA SHEET**

# SAFRA SUPER TC THINNER

THINNER FOR PAINTS & LAQUERS

**PRODUCT DESCRIPTION:** A Mixture of hydrocarbon and oxygenated solvent for paint works.

**DESIGNED USE:** Designed to dilute and improve the flow of acrylic paints, varnishes, lacquers, automotive, wood works, especially for sealers and undercoat primers.

**PHYSICAL DATA:**

| Parameter | Description | Standard Method |
|---|---|---|
| **Density (@ 25°C)** | 0.76 (g/ml) ±2% | Calculated |
| **Color** | Water White | |
| **Solids by Volume** | 0 % | ISO 3233 |
| **VOC (g/liter)** | < 400 (g/liter) | ASTM D5116 |
| **Flash Point** | < 2°C | ISO 3679 Method 1 |

**PACKAGING:** single pack providing 15L Pails, 200L Drum, Schultz tank.

**HANDLING & STORAGE:** It must be stored in the original pack in a dry, shaded, cool, well-ventilated Space and away from sources of heat and ignition. Furthermore, containers must be kept tightly closed and handled with care.

**SHELF LIFE:** Preferred using up to 24 months from production date in original tightly closed containers away from direct sunlight, excessive heat, and ignition.

**INSTRUCTIONS & USAGE**: Use the following instructions:



1) Wear your Occupational safety and health tools.
2) Open the thinner can carefully.
3) Adjust your percentage of thinner gradually to the paint to get the required viscosity.
4) Use a proper application tool and method to apply the paint.
5) Clean your tool after you finish painting with it.
6) Keep the thinner container closed to avoid losses of materials by evaporation.

**CAUTIONS:**



The applicators and operators shall be trained, experienced, and have the capability and equipment. Use according to SAFRA technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product.

**HEALTH & SAFETY:**



Please observe the precautionary notices displayed on the container. Use under well-ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with a suitable cleanser, soap, and water. Eyes should be well flushed with water, and medical attention should be sought immediately. For any further Information, refer to the Material Safety Data Sheet (MSDS) before using the product.