PRODUCT CATALOGUE

Engine Oils · Transmission Fluids · Antifreeze Coolants

2026



Three brands.
One protection system.

The Auron catalogue covers product lines for passenger and commercial vehicles: **SIENA** engine oils, **ZMEEX** transmission fluids and **ZEROX** antifreeze coolants, plus a premium **metal tin series** of fully synthetic 5W-30 oils. Each entry lists type, viscosity grade, performance specifications, OEM approvals and key technologies for fast, accurate selection.

SIENA
Engine oils: Optimum (mineral), Dynamic (semi-synthetic), Force (fully synthetic)

METAL TIN SERIES
Fully synthetic 5W-30 in 4 L metal tins: API SP, ILSAC GF-6A, ACEA C3

ZMEEX
Transmission fluids: ATF Dexron II / III / VI, Multi ATF PRO, G-Master (MTF)

ZEROX
G12+ antifreeze −40 °C: blue and green (I-OAT), red (OAT carboxylate)

CONTENTS

Promotional pages: engine oils, transmission fluids, antifreeze, metal tin series	03
SIENA engine oils: Dynamic, Force, Optimum	08
Metal tin series: 5W-30 fully synthetic	11
ZMEEX transmission fluids: ATF Dexron, ATF PRO, G-Master	13
ZEROX antifreeze coolants: G12+	16
Technical information: labelling, specifications, ATF/MTF, coolant types	17
Packaging and container sizes	21
Product summary table	23



ENGINE OILS
SERIES OF SIENA

The SIENA range spans mineral to fully synthetic engine oils. Select the series by engine type, climate and OEM approval requirements.

01 **Three series**
Optimum (mineral), Dynamic (semi-synthetic), Force (fully synthetic)

02 **European OEM approvals**
BMW Longlife-04, MB 229.31 / 229.51 / 229.52, VW 505 00 / 505 01, Opel Ov0401547 (diesel only): Dynamic and Force

03 **Protection technologies**
Double Synth, Molecular Bonding, Thermal Stability Control

04 **5W-30 to 20W-50**
Seven grades, 4 L canister



SIENA · OPTIMUM · DYNAMIC · FORCE

TRANSMISSION FLUIDS ZMEEX

ZMEEX fluids for automatic and manual transmissions: controlled friction, gear protection and seal compatibility.

01 **ATF Dexron II / III / VI**
Fully synthetic ATF: S-MDF 2, 3 and 6

02 **Multi ATF PRO**
S-MDF 8: multi-vehicle approvals, incl. DEXRON®, MERCON®, Allison C-4, ZF, MAN, Voith

03 **G-Master 75W-85 / 80W-90**
Fully synthetic MTF: API GL-4 and GL-5

04 **Technologies**
Friction Modifier, Multi-Spec Friction, Seal Compatibility



ZMEEX · DEXRON · MULTI ATF PRO · G-MASTER

ANTIFREEZE
ZEROX G12+

Extended-life coolants for European and Asian vehicles. Protection against freezing down to −40 °C, boil-over and corrosion.

01 **Three colours**
Blue and green (I-OAT), red (OAT carboxylate)

02 **Protection to −40 °C**
Prevents freeze-up, boil-over and corrosion in the cooling system

03 **Standards**
ASTM D3306, JIS K2234, KSM 2142

04 **5 kg canister**
Cap colour identifies the coolant type



ZEROX · G12+ · I-OAT · OAT



PREMIUM
METAL TIN SERIES

Fully synthetic 5W-30 engine oils in a 4 L metal tin. API SP, ILSAC GF-6A and ACEA C3 specifications for modern passenger-car engines.

01

Engine protection

Wear and deposit control

02

Clean performance

Clean engine technology

03

Fuel economy

Low-friction fully synthetic base

04

Long drain interval

Extended oil life

ENGINEERED FOR MODERN ENGINES

One viscosity grade, three specification routes. Select the label that matches your vehicle manufacturer’s requirement.

01 **API SP**

Current gasoline-engine category: low-speed pre-ignition (LSPI) and timing-chain wear protection, deposit and sludge control.

02 **ILSAC GF-6A**

API SP performance plus fuel-economy and fuel-economy-retention requirements.

03 **ACEA C3**

Mid-SAPS formulation compatible with DPF and three-way catalysts; HTHS viscosity ≥ 3.5 mPa·s.

04 **4 L metal tin**

Fully synthetic 5W-30 in four label variants with carry handle and screw closure.







API SP · ILSAC GF-6A · ACEA C3

ENGINE OILS

SIENA Dynamic

Semi-synthetic 10W-40 engine oils with European OEM approvals. Two API specifications: SL/CF and SN/CF.





SIENA Dynamic SL/CF

TYPE
Semi-synthetic engine oil

SAE VISCOSITY
10W-40

API SPECIFICATION
SL/CF

APPROVALS
BMW Longlife-04; MB-Approval 229.31, 229.51, 229.52; VW 505 00, 505 01; Opel/Vauxhall Ov0401547 (diesel only)

TECHNOLOGY
Double Synth Technology

PACK
Plastic canister, 4 L

SIENA Dynamic SN/CF

TYPE
Semi-synthetic engine oil

SAE VISCOSITY
10W-40

API SPECIFICATION
SN/CF

APPROVALS
BMW Longlife-04; MB-Approval 229.31, 229.51, 229.52; VW 505 00, 505 01; Opel/Vauxhall Ov0401547 (diesel only)

TECHNOLOGY
Molecular Bonding Technology

PACK
Plastic canister, 4 L

Data are taken from product labels. Always consult the vehicle owner's manual before use.

ENGINE OILS

SIENA Force

Fully synthetic API SN Plus engine oils with Double Synth Technology in a gold canister. Grades 5W-30 and 5W-40.





SIENA Force 5W-30

TYPE
Fully synthetic engine oil

SAE VISCOSITY
5W-30

API SPECIFICATION
SN Plus

APPROVALS
BMW Longlife-04; MB-Approval 229.31, 229.51, 229.52; VW 505 00, 505 01; Opel/Vauxhall Ov0401547 (diesel only)

TECHNOLOGY
Double Synth Technology

PACK
Plastic canister, 4 L

SIENA Force 5W-40

TYPE
Fully synthetic engine oil

SAE VISCOSITY
5W-40

API SPECIFICATION
SN Plus

APPROVALS
BMW Longlife-04; MB-Approval 229.31, 229.51, 229.52; VW 505 00, 505 01; Opel/Vauxhall Ov0401547 (diesel only)

TECHNOLOGY
Double Synth Technology

PACK
Plastic canister, 4 L

Data are taken from product labels. Always consult the vehicle owner's manual before use.

ENGINE OILS

SIENA Optimum

Mineral engine oils for gasoline and diesel engines with Thermal Stability Control. Grades 15W-40, 15W-50 and 20W-50.



SIENA Optimum 15W-40

TYPE
Mineral engine oil

SAE VISCOSITY
15W-40

API SPECIFICATION
SG/CD

TECHNOLOGY
Thermal Stability Control

PACK
Plastic canister, 4 L

SIENA Optimum 15W-50

TYPE
Mineral engine oil

SAE VISCOSITY
15W-50

API SPECIFICATION
SJ/CF

TECHNOLOGY
Thermal Stability Control

PACK
Plastic canister, 4 L

SIENA Optimum 20W-50

TYPE
Mineral engine oil

SAE VISCOSITY
20W-50

API SPECIFICATION
SG/CD

TECHNOLOGY
Thermal Stability Control

PACK
Plastic canister, 4 L

Data are taken from product labels. Always consult the vehicle owner's manual before use.

METAL TIN SERIES

Metal Tin: ILSAC GF-6A

Fully synthetic 5W-30 engine oils in 4 L metal tins, formulated to API SP and ILSAC GF-6A.





Premium · API SP / ILSAC GF-6A

TYPE
Fully synthetic engine oil

SAE VISCOSITY
5W-30

SPECIFICATIONS
API SP; ILSAC GF-6A

APPLICATION
Modern gasoline engines

KEY FEATURES
Superior engine protection; fuel economy; clean engine technology

PACK
Metal tin, 4 L

Gasoline & Diesel · API SP / GF-6A

TYPE
Fully synthetic engine oil

SAE VISCOSITY
5W-30

SPECIFICATIONS
API SP; ILSAC GF-6A

APPLICATION
Gasoline & diesel (as stated on label)

KEY FEATURES
Engine protection; high performance; long drain interval

PACK
Metal tin, 4 L

Data are taken from product labels. Always consult the vehicle owner's manual before use.

METAL TIN SERIES

Metal Tin: ACEA C3

Fully synthetic 5W-30 engine oils in 4 L metal tins, formulated to ACEA C3 and API SP.





Synthetic · ACEA C3 / API SP

TYPE
Fully synthetic engine oil

SAE VISCOSITY
5W-30

SPECIFICATIONS
ACEA C3; API SP

APPLICATION
Gasoline, diesel, hybrid (as stated on label)

KEY FEATURES
Engine protection; clean performance; long engine life; low-temperature performance; fuel efficiency

PACK
Metal tin, 4 L

Passenger car · API SP / ACEA C3

TYPE
Fully synthetic engine oil

SAE VISCOSITY
5W-30

SPECIFICATIONS
API SP; ACEA C3

APPLICATION
Passenger car engines

KEY FEATURES
Maximum engine protection; clean engine performance; fuel efficiency

PACK
Metal tin, 4 L

Data are taken from product labels. Always consult the vehicle owner's manual before use.

TRANSMISSION FLUIDS

ZMEEX Dexron ATF

Fully synthetic automatic transmission fluids in three specification levels: Dexron II, III and VI.







ZMEEX Dexron ATF II

TYPE
Fully synthetic ATF

CLASS
S-MDF 2

APPROVALS
GM DEXRON® II (F, G, H); Ford MERCON® ; Allison C-4; Caterpillar TO-2; MAN 339 Type V1 / Z1; ZF TE-ML 04D / 14A / 17C; Voith H55.6335

TECHNOLOGY
Friction Modifier Technology

PACK
Plastic canister, 4 L

ZMEEX Dexron ATF III

TYPE
Fully synthetic ATF

CLASS
S-MDF 3

APPROVALS
GM DEXRON® III (F, G, H); Ford MERCON® ; Allison C-4; Caterpillar TO-2; MAN 339 Type V1 / Z1; ZF TE-ML 04D / 14A / 17C; Voith H55.6335

TECHNOLOGY
Friction Modifier Technology

PACK
Plastic canister, 4 L

ZMEEX Dexron ATF VI

TYPE
Fully synthetic ATF

CLASS
S-MDF 6

APPROVALS
GM DEXRON® VI (F, G, H); Ford MERCON® ; Allison C-4; Caterpillar TO-2; MAN 339 Type V1 / Z1; ZF TE-ML 04D / 14A / 17C; Voith H55.6335

TECHNOLOGY
Friction Modifier Technology

PACK
Plastic canister, 4 L

Data are taken from product labels. Always consult the vehicle owner's manual before use.

TRANSMISSION FLUIDS

ZMEEX Multi ATF PRO

Class S-MDF 8 multi-vehicle ATF with Multi-Spec Friction Technology for a broad range of OEM approvals.



ZMEEX Multi ATF PRO

TYPE
Fully synthetic multi-vehicle ATF

CLASS
S-MDF 8

APPROVALS
GM DEXRON® (F, G, H); Ford MERCON® ; Allison C-4; Caterpillar TO-2; MAN 339 Type V1 / Z1; ZF TE-ML 04D / 14A / 17C; Voith H55.6335

TECHNOLOGY
Multi-Spec Friction Technology

PACK
Plastic canister, 4 L

Data are taken from product labels. Always consult the vehicle owner's manual before use.

TRANSMISSION FLUIDS

ZMEEX G-Master

Fully synthetic manual transmission fluids: 75W-85 (API GL-4) and 80W-90 (API GL-5).





ZMEEX G-Master 75W-85

TYPE
Fully synthetic manual transmission fluid

SAE VISCOSITY
75W-85

API SPECIFICATION
GL-4

APPROVALS
MIL-L-2105; ZF TE-ML 02B, 16A, 17A; MAN 341 Typ Z-2; MB 235.4; IVECO; Renault Trucks; DAF (recommended)

TECHNOLOGY
Seal Compatibility Technology

PACK
Plastic canister, 4 L

ZMEEX G-Master 80W-90

TYPE
Fully synthetic manual transmission fluid

SAE VISCOSITY
80W-90

API SPECIFICATION
GL-5

APPROVALS
MIL-L-2105; ZF TE-ML 02B, 16A, 17A; MAN 341 Typ Z-2; MB 235.4; IVECO; Renault Trucks; DAF (recommended)

TECHNOLOGY
Seal Compatibility Technology

PACK
Plastic canister, 4 L

Data are taken from product labels. Always consult the vehicle owner's manual before use.

ANTIFREEZE COOLANTS

ZEROX G12+

Extended-life −40 °C coolants for Euro-Asian vehicles. Cap colour identifies the inhibitor technology.



ZEROX G12+ Blue	ZEROX G12+ Green	ZEROX G12+ Red
CLASS G12+	CLASS G12+	CLASS G12+
FREEZE PROTECTION down to −40 °C	FREEZE PROTECTION down to −40 °C	FREEZE PROTECTION down to −40 °C
TECHNOLOGY I-OAT	TECHNOLOGY I-OAT	TECHNOLOGY OAT
INHIBITOR TYPE Hybrid (I-OAT)	INHIBITOR TYPE Hybrid (I-OAT)	INHIBITOR TYPE Carboxylate (OAT)
STANDARDS ASTM D3306; JIS K2234; KSM 2142	STANDARDS ASTM D3306; JIS K2234; KSM 2142	STANDARDS ASTM D3306; JIS K2234; KSM 2142
APPLICATION Extended life, Euro-Asian vehicles	APPLICATION Extended life, Euro-Asian vehicles	APPLICATION Extended life, Euro-Asian vehicles
PACK Plastic canister, 5 kg	PACK Plastic canister, 5 kg	PACK Plastic canister, 5 kg

Data are taken from product labels. Always consult the vehicle owner's manual before use.

How to read an engine oil label

10W – 40

10W: winter grade (W = Winter). The lower the number, the better the low-temperature pumpability and cold-start performance.

40: viscosity grade at operating temperature. The higher the number, the thicker the oil film in a hot engine.

Viscosity grades in the Auron range

SAE grade	Series	Characteristics
5W-30	Force; Metal Tin	Low viscosity: fast oil flow at cold start, fuel-economy oriented
5W-40	Force	Good cold start with a more robust oil film at high temperature
10W-40	Dynamic	Versatile all-season grade for temperate climates
15W-40	Optimum	Temperate and warm climates
15W-50 / 20W-50	Optimum	Warm climates and higher thermal loads

API classification

First letter: **S** = gasoline (spark-ignition) engines, **C** = diesel (compression-ignition) engines. The second letter indicates the generation: the later in the alphabet, the newer and stricter the requirements. **SP** and **SN Plus** are the most current categories in this catalogue; **SG, SJ and SL** are earlier categories and should be used only where the vehicle manufacturer permits.

Base oil type

Type	Series	Positioning
Mineral	Optimum	Conventional solution for engines with modest oil requirements
Semi-synthetic	Dynamic	Balance of cost and protection; BMW, MB, VW and Opel approvals
Fully synthetic	Force; Metal Tin	Highest property stability; cold-start flow and component protection

Always follow the vehicle owner's manual: viscosity grade and approvals must match the manufacturer's requirements.

API SP, ILSAC GF-6A and ACEA C3

The metal tin series is a fully synthetic 5W-30 range. The label specification tells you which engine requirement the oil is formulated to meet.

Specification	Issued by	Focus	Key points
API SP	American Petroleum Institute	Gasoline engines	LSPI and timing-chain wear protection; improved deposit, sludge and oxidation control; designed to be backward compatible with earlier S categories
ILSAC GF-6A	ILSAC (Japanese and US automakers)	Gasoline engines; fuel economy	API SP performance plus fuel-economy and fuel-economy-retention requirements; covers grades 0W-20, 0W-30, 5W-20, 5W-30 and 10W-30
ACEA C3	ACEA (European automakers)	Gasoline and diesel passenger cars with aftertreatment	Mid-SAPS formulation compatible with DPF and three-way catalysts; minimum HTHS viscosity 3.5 mPa·s

Metal tin variants

Variant	Specifications	Application stated on label
5W-30 (Premium)	API SP; ILSAC GF-6A	Modern gasoline engines
5W-30 (Gasoline & Diesel)	API SP; ILSAC GF-6A	Gasoline & diesel
5W-30 (Synthetic)	ACEA C3; API SP	Gasoline, diesel, hybrid
5W-30 (Passenger car)	API SP; ACEA C3	Passenger car

Selection notes

Follow the OEM. Choose the specification and viscosity grade stated in the vehicle owner's manual.

ILSAC GF-6A and API SP are gasoline-engine specifications. For diesel engines, use the approval required by the manufacturer.

ACEA C3 is the relevant route for vehicles with a DPF that require a mid-SAPS oil with HTHS ≥ 3.5 mPa·s.

ATF and MTF: what is the difference?

ATF (automatic transmission fluid) transmits hydraulic power, lubricates, and provides a precisely controlled friction coefficient for the clutches. **MTF** (manual transmission fluid) lubricates manual gearboxes and axles, where gear-tooth protection under high load is the priority.

ZMEEX ATF specifications

Product	Class	Primary standard
ATF II	S-MDF 2	GM DEXRON® II (F, G, H)
ATF III	S-MDF 3	GM DEXRON® III (F, G, H)
ATF VI	S-MDF 6	GM DEXRON® VI (F, G, H)
Multi ATF PRO	S-MDF 8	GM DEXRON® (F, G, H) and multi-vehicle approvals

Common ATF approvals: Ford MERCON® ; Allison C-4; Caterpillar TO-2; MAN 339 Type V1 / Z1; ZF TE-ML 04D / 14A / 17C; Voith H55.6335.

API GL classes for manual gearboxes

Class	Product	Characteristics
API GL-4	G-Master 75W-85	Synchromesh manual gearboxes under moderate load
API GL-5	G-Master 80W-90	Axles and final drives under high contact load (hypoid gears)

Caution: some manual gearboxes do not permit GL-5 oils because the active additives can attack yellow-metal components. Use the class specified by the manufacturer. G-Master approvals: MIL-L-2105; ZF TE-ML 02B, 16A, 17A; MAN 341 Typ Z-2; MB 235.4; IVECO; Renault Trucks; DAF (recommended).

Technologies

- **Friction Modifier Technology**: stable clutch friction and smooth shifting
- **Multi-Spec Friction Technology**: one product for multiple OEM specifications
- **Seal Compatibility Technology**: compatibility with elastomer seals

ZEROX G12+ antifreeze coolants

Engine coolant protects the cooling system against freezing, boil-over and corrosion. ZEROX G12+ are extended-life coolants for European and Asian vehicles with freeze protection down to −40 °C.







Property	ZEROX Blue	ZEROX Green	ZEROX Red
Class	G12+	G12+	G12+
Technology	I-OAT	I-OAT	OAT (carboxylate)
Freeze protection	−40 °C	−40 °C	−40 °C
Cap colour	Blue	Green	Red
Pack	5 kg	5 kg	5 kg

Key points

- **Standards:** ASTM D3306 (USA), JIS K2234 (Japan), KSM 2142 (Korea), the basis for Euro-Asian applications.
- **Inhibitor technology:** I-OAT is a hybrid technology combining inorganic and organic-acid inhibitors; OAT is a carboxylate organic acid technology.
- **Do not mix** coolants of different types or classes unless the vehicle manufacturer permits it. Colour alone does not guarantee compatibility.
- **Selection:** follow the vehicle manufacturer's coolant specification.

Packaging and container sizes: plastic canisters



Plastic canister, 4 L

ENGINE OILS AND TRANSMISSION FLUIDS



Plastic canister, 5 kg

ZEROX G12+ ANTIFREEZE COOLANTS

VOLUME
4 L

CANISTER COLOUR
Metallic silver: Optimum, Dynamic, ZMEEX; gold: Force

FEATURES
Ergonomic handle, embossed grip texture on neck and handle, black closure, QR code on label

RANGES
SIENA Optimum, Dynamic, Force; ZMEEX ATF, ATF PRO, G-Master

NET WEIGHT
5 kg

CANISTER COLOUR
White

CAP COLOUR
Blue, green or red according to coolant type

RANGE
ZEROX G12+ −40 °C (I-OAT and OAT)

Packaging and container sizes: metal tin









VOLUME
4 L

CONTAINER
Metal tin with carry handle and screw closure

FINISH
Navy label with metallic silver accents

RANGE
Fully synthetic 5W-30, four label variants

Label variant	Specifications	Application
Premium	API SP; ILSAC GF-6A	Modern gasoline engines
Gasoline & Diesel	API SP; ILSAC GF-6A	Gasoline & diesel
Synthetic	ACEA C3; API SP	Gasoline, diesel, hybrid
Passenger car	API SP; ACEA C3	Passenger car

Product summary table

Product	Type	Viscosity / class	Specification	Pack
SIENA Optimum 15W-40	Mineral	15W-40	API SG/CD	4 L
SIENA Optimum 15W-50	Mineral	15W-50	API SJ/CF	4 L
SIENA Optimum 20W-50	Mineral	20W-50	API SG/CD	4 L
SIENA Dynamic SL/CF	Semi-synthetic	10W-40	API SL/CF	4 L
SIENA Dynamic SN/CF	Semi-synthetic	10W-40	API SN/CF	4 L
SIENA Force 5W-30	Fully synthetic	5W-30	API SN Plus	4 L
SIENA Force 5W-40	Fully synthetic	5W-40	API SN Plus	4 L
AURON Metal Tin Premium · API SP / ILSAC GF-6A	Fully synthetic	5W-30	API SP; ILSAC GF-6A	4 L tin
AURON Metal Tin Gasoline & Diesel · API SP / GF-6A	Fully synthetic	5W-30	API SP; ILSAC GF-6A	4 L tin
AURON Metal Tin Synthetic · ACEA C3 / API SP	Fully synthetic	5W-30	ACEA C3; API SP	4 L tin
AURON Metal Tin Passenger car · API SP / ACEA C3	Fully synthetic	5W-30	API SP; ACEA C3	4 L tin
ZMEEX Dexron ATF II	Synthetic ATF	S-MDF 2	DEXRON® II	4 L
ZMEEX Dexron ATF III	Synthetic ATF	S-MDF 3	DEXRON® III	4 L
ZMEEX Dexron ATF VI	Synthetic ATF	S-MDF 6	DEXRON® VI	4 L
ZMEEX Multi ATF PRO	Synthetic ATF	S-MDF 8	DEXRON® / multi-vehicle	4 L
ZMEEX G-Master 75W-85	Synthetic MTF	75W-85	API GL-4	4 L
ZMEEX G-Master 80W-90	Synthetic MTF	80W-90	API GL-5	4 L
ZEROX G12+ Blue	Coolant, I-OAT	G12+ −40 °C	ASTM D3306; JIS K2234; KSM 2142	5 kg
ZEROX G12+ Green	Coolant, I-OAT	G12+ −40 °C	ASTM D3306; JIS K2234; KSM 2142	5 kg
ZEROX G12+ Red	Coolant, OAT	G12+ −40 °C	ASTM D3306; JIS K2234; KSM 2142	5 kg

auron

ENGINE OILS · TRANSMISSION FLUIDS · ANTIFREEZE COOLANTS

