DOCUMENTATION PACK · 2 OF 6

The 5 Checks, Explained

Email · Username · Phone · Password · IP — what each check answers, and what it never does.

Exposure-Check-OSINT v1.0 · Apache-2.0 · self-hosted · keyless · no AI · https://github.com/RanaKhan77/Exposure-Check-OSINT

At a glance: 📧 Email (breaches, stealer logs, COMB) · 👤 Username (150-platform logo grid) · 📱 Phone (validity + leak association) · 🔑 Password (HIBP k-anonymity, never leaves your browser) · 🌐 IP (ports, VPN/proxy/hosting)

1. Email exposure 📧

Paste any email address. The engine fans out to all supporting sources in parallel (stealer logs, breach analytics, COMB corpus, disposable-domain flags, Gravatar, GitHub public associations) and answers:
where is this email exposed, and what does that expose about its owner?

- Breach names, dates and record counts (never other victims' data)
- Infostealer infection counts + machine classifications (no raw cookies/logs)
- Whether the address is disposable/temp (affects how trustworthy it is)
- Public GitHub code/profile associations

> **v1.1 roadmap:** the consent-gated ~120-platform linked-account probe (needs the optional browser-service add-on)

2. Username exposure 👤

One username → which of 150 popular platforms (Maigret + WhatsMyName corpus) have that handle registered, rendered as a platform logo grid. Also Bluesky and Hacker News with profile details. Each found account is a public identity footprint.

3. Phone exposure 📱

An E.164 number (with or without `+`) → validity, country, line type classification, and COMB leak association. No SMS is ever sent; the checks are database/API lookups only.

4. Password exposure 🔑

Your password never leaves your device. The page hashes it with SHA-1 **in your browser** and sends only the **first 5 hex characters** to this server (k-anonymity — the same design as Troy Hunt's Pwned Passwords). The server fetches the ~800 hash suffixes for that prefix from HIBP and returns them; **your browser matches the full hash locally** and shows how many times the password appears in known breach corpora. The full hash — and the password — never reach the server, the database, or any logs.

5. IP exposure 🌐

An IPv4/IPv6 → open ports and exposed services (Shodan InternetDB, keyless), VPN/proxy/hosting classification (ipapi.is). For auditing your own servers and egress IPs.

What this tool is NOT for

- **Not for domains/websites** — use the Website Vulnerability Scanner CE (200 modules) for that job.
- **Not for checking people you have no authorization to assess.** This is a self-audit tool: your own identifiers, or identifiers you are explicitly authorized to assess (your organization's, with permission).
- **Not an attack tool.** Every lookup is a read-only question to a public API. No credential stuffing, no account takeover, no mass scraping — by construction.