DOCUMENTATION PACK · 5 OF 6

# Privacy by Design

What is stored, what leaves the server, and to whom — the honest, complete list.

Exposure-Check-OSINT v1.0 · Apache-2.0 · self-hosted · keyless · no AI · https://github.com/RanaKhan77/Exposure-Check-OSINT

This page is the honest, complete list. If it is not listed here, it does not happen.

## What is stored locally (and only locally)

| Data | Where | Form |
|---|---|---|
| Check history | `exposure_checks` table (SQLite on your machine) | Type + **salted SHA-256 hash** of the identifier + masked display form ( `j***n@gmail.com` ) + aggregated results. The raw identifier is **never** stored. |
| Password checks | nothing | Password checks store **no result rows at all** — matching happens in your browser |
| Settings, license state | local tables | Quotas, toggles, license key |
| Platform logos cache | `storage/app/osint-logos` | Public favicons, cache only, purgeable |

Delete any record from the History page, or **Purge all** — one click, gone.

## What leaves the server, and to whom

1. **The identifier you type** (email/username/phone/IP) — sent over HTTPS to the keyless OSINT sources listed in SOURCES.md, because that is literally what a lookup is. Each source sees only what it needs.
2. **For password checks: only the first 5 hex chars of the SHA-1** (k-anonymity). Not the password. Not the full hash. See CHECKS.md.
3. **License heartbeat** (daily, if you activate a free key): install ID, status, version, PHP version — to `2mny.com` . This powers the public install counter and free update notifications. It carries **no check data and no identifiers**. The whole license client is ~300 readable lines: `app/Services/CommunityLicenseService.php` .

## What is deliberately NOT collected

- No analytics, no tracking pixels, no third-party JavaScript
- No raw identifiers in any log (audit rows store hashes + masked forms only)
- No credential material in the database ( `credential_lines` are stripped before storage)
- No telemetry beyond the license heartbeat above

## Threat-model honesty

- The OSINT sources themselves learn that *someone at your IP* checked a given identifier — that is inherent to any lookup tool, hosted or self-hosted. Running this yourself means the *results* never touch anyone else's server.
- The result cache (30 min default, configurable) is keyed by a SHA-1 of type + identifier and stored in your local cache store only.